



Publisher Correction: On design and performance analysis of improved shuffle exchange gamma interconnection network layouts

Gaurav Khanna¹ · Sanjay K. Chaturvedi² · Mohamed Othman^{3,4}

Published online: 7 October 2022

© The Author(s), under exclusive licence to Springer Science+Business Media, LLC, part of Springer Nature 2022

Publisher Correction: J Supercomput

<https://doi.org/10.1007/s11227-022-04735-6>

A correction has been made for clearer presentation of the formula under Expression in Table 7.

Correct is

The original article can be found online at <https://doi.org/10.1007/s11227-022-04735-6>.

✉ Gaurav Khanna
gaurav.khanna@jiit.ac.in

Sanjay K. Chaturvedi
skrec@hijli.iitkgp.ac.in

Mohamed Othman
mothman@upm.edu.my

¹ Department of Electronics and Communication Engineering, Jaypee Institute of Information Technology, Noida, Uttar Pradesh, India

² Subir Chowdhury School of Quality and Reliability, Indian Institute of Technology Kharagpur, Kharagpur, West Bengal, India

³ Department of Communication Technology and Network, Universiti Putra Malaysia (UPM), 43400 Serdang, Selangor D.E, Malaysia

⁴ Laboratory of Computational Sciences and Mathematical Physics, Institute for Mathematical Research, Universiti Putra Malaysia (UPM), 43400 Serdang, Selangor D.E, Malaysia

Table 7 2-Terminal reliability expression for an 8×8 EA-SEGIN

Reliability measure	Total (disjoint) paths	Expression
R_{2T}	24 (2)	$12r^6 + 4r^7 - 36r^8 + 10r^9 + 17r^{10} + 2r^{11} - 5r^{12} - 8r^{13} + 4r^{14} + 2r^{15} - r^{16}$

The original article has been corrected.

Publisher's Note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.