## **PUBLISHER CORRECTION**



## Publisher Correction to: On design and performance analysis of improved shuffle exchange gamma interconnection network layouts

Gaurav Khanna<sup>1</sup> • Sanjay K. Chaturvedi<sup>2</sup> • Mohamed Othman<sup>3,4</sup>

Published online: 12 December 2022

© The Author(s), under exclusive licence to Springer Science+Business Media, LLC, part of Springer Nature

## Publisher Correction to: The Journal of Supercomputing https://doi.org/10.1007/s11227-022-04735-6

A publisher correction has been made to reduce the repeated formula under Expression in Table 7.

The original article can be found online at https://doi.org/10.1007/s11227-022-04735-6.

☐ Gaurav Khanna gaurav.khanna@jiit.ac.in

Sanjay K. Chaturvedi skcrec@hijli.iitkgp.ernet.in

Mohamed Othman mothman@upm.edu.my

- Department of Electronics and Communication Engineering, Jaypee Institute of Information Technology, Noida, Uttar Pradesh, India
- Subir Chowdhury School of Quality and Reliability, Indian Institute of Technology Kharagpur, Kharagpur, West Bengal, India
- Department of Communication Technology and Network, Universiti Putra Malaysia (UPM), 43400 Serdang, Selangor D.E, Malaysia
- Laboratory of Computational Sciences and Mathematical Physics, Institute for Mathematical Research, Universiti Putra Malaysia (UPM), 43400 Serdang, Selangor D.E, Malaysia



**Table 7** 2-Terminal reliability expression for an  $8 \times 8$  EA-SEGIN

| Reliability measure | Total (Disjoint) paths | Expression   |
|---------------------|------------------------|--|
| $R_{2T}$            | 24 (2)                 | $12r^6 + 4r^7 - 36r^8 + 10r^9$ $+17r^{10} + 2r^{11} - 5r^{12} - 8r^{13}$ |
|                     |                        | $+1/r^{13} + 2r^{13} - 5r^{12} - 8r^{13}$ $+4r^{14} + 2r^{15} - r^{16}$  |

The original article has been corrected.

**Publisher's Note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

