CORRECTION

Correction to: robust two-phase registration method for three-dimensional point set under the bayesian mixture framework

Lijuan Yang[1] · **Nannan Ji[1]** · **Changpeng Wang[1]** · **Tianjun Wu[1]** · **Fuxiao Li[2]**

International Journal of Machine Learning and Cybernetics
https://doi.org/10.1007/s13042-022-01673-w

In the online published article, Fig. 8 legend and the affiliations are published incorrectly. The correct details are given below.

1 School of Science, Chang'an University, Xi'an, Shaanxi 710064, People's Republic of China

2 School of Science, Xi'an University of Technology, Xi'an, Shaanxi 710048, People's Republic of China

---

The online version of the original article can be found at https://doi.org/10.1007/s13042-022-01673-w

✉ Lijuan Yang
yanglijuan1987@163.com

Nannan Ji
jinannan18@163.com

Changpeng Wang
cpwang@chd.edu.cn

Tianjun Wu
tjwu@chd.edu.cn

Fuxiao Li
fx_lmzq@163.com

1 School of Science, Chang'an University, Xi'an, Shaanxi 710064, People's Republic of China

2 School of Science, Xi'an University of Technology, Xi'an, Shaanxi 710048, People's Republic of China

Fig. 8 The average F1-scores after applying six methods on six shapes under the affine (left) and nonrigid (right) cases with random degrees of rotation and outliers