

Document details

[Back to results](#) | 1 of 1

[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More...](#)

[Full Text](#) [View at Publisher](#)

Conference Record - IEEE Instrumentation and Measurement Technology Conference

Volume 2019-May, May 2019, Article number 8827053

2019 IEEE International Instrumentation and Measurement Technology Conference, I2MTC

2019; Auckland; New Zealand; 20 May 2019 through 23 May 2019; Category

numberCFP19IMTART; Code 151873

UWB antenna based time-domain approach for through the walls gap estimation (Conference Paper)

Shaikh, F.A.^a , Khan, S.^a , Alam, A.H.M.Z.^a , Habaebi, M.H.^a , Baillargeat, D.^b , Kadir, K.^a , Shah, J.^a , Shahid, Z.^c , Yahya, M.^a 

^aDept. of ECE, International Islamic University Malaysia (IIUM), Kuala Lumpur, Malaysia

^bDept. of Research XLIM, University of Limoges, Limoges, France

^cDept. of Eng, Institute of Business Management (IoBM), Karachi, Pakistan

Abstract

[View references \(33\)](#)

This paper has introduced a novel experimental system adopted a time domain approach for estimating through wall distance and recognizes buried objects behind the wall. The designed and fabricated balanced antipodal Vivaldi antenna (BAVA) has been used for the development of UWB system. The working mechanism of an intended detection system based on time domain reflectometry (TDR) and ground-penetrating radar (GPR). A miniature pulse in the UWB range is generated by the vector network analyzer (VNA) to irradiate a barrier made of two walls separated by airgap between them. The signal radiations reflect partially from the front wall while remaining goes through for getting reflected from the rear wall. The VNA is used for measuring the time interval passed between the instant when an incident signal irradiates the first wall and the instant when the incident signal gets reflected from the rear wall. The investigational process of a system is carried out by UWB antenna probe. The detected information is attained using the values of reflection coefficient (S_{11}) represented in time domain measurements. Experimental results have been proved the ability to detect wall gap as well as the width estimation between two walls with high accuracy. The maximum percentage error has been found to not exceeding 4.5% in the worst condition. © 2019 IEEE.

SciVal Topic Prominence

Topic: Slot antennas | Antennas | Vivaldi antenna





Prominence percentile: 91.138 

Author keywords




      

Indexed keywords

Engineering controlled terms:

Engineering uncontrolled terms:

Metrics  [View all metrics >](#)



PlumX Metrics

Usage, Captures, Mentions,
Social Media and Citations
beyond Scopus.

Cited by 0 documents

Inform me when this document
is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

Related documents

Design and parametric evaluation
of UWB antenna for array
arrangement

Shaikh, F.A. , Khan, S. , Alam,
A.H.M.Z.
*(2019) Bulletin of Electrical
Engineering and Informatics*

Comparative Analysis of UWB
Balance Antipodal Vivaldi
Antenna for Array Configuration

Shaikh, F.A. , Khan, S. , Alam,
A.Z.
*(2018) Proceedings of the 2018
7th International Conference on
Computer and Communication
Engineering, ICCCE 2018*

Recognition of metal objects
inside wall using antipodal vivaldi
antenna

Shaikh, F.A. , Khan, S. ,
Zaharudin, Z.
*(2018) Indonesian Journal of
Electrical Engineering and
Computer Science*

[View all related documents based
on references](#)

Find more related documents in
Scopus based on:

[Authors >](#) [Keywords >](#)

ISSN: 10915281
ISBN: 978-153863460-8
CODEN: CRIIE
Source Type: Conference Proceeding
Original language: English

DOI: 10.1109/I2MTC.2019.8827053
Document Type: Conference Paper
Sponsors: 100% Pure New Zealand, IEEE, IEEE Instrumentation and Measurement Society
Publisher: Institute of Electrical and Electronics Engineers Inc.

References (33)

[View in search results format >](#)

All Export Print E-mail Save to PDF [Create bibliography](#)

- 1 Moosazadeh, M., Kharkovsky, S., Case, J.T., Samali, B.
Improved Radiation Characteristics of Small Antipodal Vivaldi Antenna for Microwave and Millimeter-Wave Imaging Applications
(2017) *IEEE Antennas and Wireless Propagation Letters*, 16, art. no. 7891602, pp. 1961-1964. Cited 23 times.
www.ieee.org
doi: 10.1109/LAWP.2017.2690441
[View at Publisher](#)
- 2 Peng, K.-C., Lin, C.-C., Li, C.-F., Hung, C.-Y., Hsieh, Y.-S.
A Compact 9 GHz Microwave Imaging System
(2018) *2018 IEEE International Workshop on Electromagnetics: Applications and Student Innovation Competition, iWEM 2018*, art. no. 8536676.
<http://ieeexplore.ieee.org/xpl/mostRecentIssue.jsp?punumber=8517201>
ISBN: 978-153864834-6
doi: 10.1109/iWEM.2018.8536676
[View at Publisher](#)
- 3 Shaikh, F.A., Khan, S.
Design and optimization of ultra-wideband antipodal vivaldi antenna for radar and microwave imaging application
(2018) *Sindh University Research Journal (Science Series)*, 50 (3 D), pp. 06-09. Cited 2 times.
- 4 Dhakad, S.K.
(2018) *Design of Wideband UWB Antenna for Radar-based Imaging, Microwave Tomography and Other Medical Imaging Applications.*, pp. 47-53.
- 5 Shaikh, F.A., Khan, S., Alam, Z., Hassan, A., Hashim, A., Badron, K., Yaacob, M.
High gain UWB horn antenna for concealed metal detection and microwave imaging application
(2018) *Sindh University Research Journal (Science Series)*, 50 (3 D), pp. 161-164. Cited 2 times.