ANALYZING THE ROBUSTNESS OF UNSUPERVISED SPEECH RECOGNITION

Guan-Ting Lin^{1*}, Chan-Jan Hsu^{1,2*}, Da-Rong Liu¹, Hung-Yi Lee¹, Yu Tsao²

¹National Taiwan University, Taiwan
²Academia Sinica, Taiwan
{r10942104, r09946011, hungyilee}@ntu.edu.tw

ABSTRACT

Unsupervised speech recognition (unsupervised ASR) aims to learn the ASR system with non-parallel speech and text corpus only. Wav2vec-U [1] has shown promising results in unsupervised ASR by self-supervised speech representations coupled with Generative Adversarial Network (GAN) training, but the robustness of the unsupervised ASR framework is unknown. In this work, we further analyze the training robustness of unsupervised ASR on the domain mismatch scenarios in which the domains of unpaired speech and text are different. Three domain mismatch scenarios include: (1) using speech and text from different datasets, (2) utilizing noisy/spontaneous speech, and (3) adjusting the amount of speech and text data. We also quantify the degree of the domain mismatch by calculating the JS-divergence of phoneme n-gram between the transcription of speech and text. This metric correlates with the performance highly. Experimental results show that domain mismatch leads to inferior performance, but a self-supervised model pre-trained on the targeted speech domain can extract better representation to alleviate the performance drop.

Index Terms— Unsupervised ASR, Generative Adversarial Network, Robustness

1. INTRODUCTION

Automatic speech recognition (ASR) is a long-standing research area that predicts transcriptions given the input speech feature. The performance of ASR has rapidly improved due to the deep learning method with an increasing amount of labeled data. However, collecting hundreds or thousands of hours of paired speech and text data is costly and even infeasible for the low-resource or endangered languages.

On the other hand, unsupervised ASR aims only to leverage unpaired speech and text data for training an ASR system. Unsupervised ASR systems learn the cross-modal mapping between speech and text [2, 3, 4, 5, 6]. In particular, [5] and [6] propose to learn the mapping by Generative Adversarial Network (GAN) [7]. They demonstrate encouraging results for completely unsupervised ASR training, but the performance is still far from the supervised ASR system. Notably, a recent work named Wav2vec-U [1] has shown remarkable performance breakthroughs in unsupervised ASR. The performance is comparable with some supervised methods [8, 9, 10].

This paper intends to investigate the robustness of Wav2vec-U under three different domain mismatch scenarios, where the domain of unpaired speech and text are different. Figure 1 shows the main




Fig. 1. A brief illustration of our work.

concept of our work. The three scenarios are as below:

Content dissimilarity: One major experiment in Wav2vec-U is trained with an unpaired speech from Librispeech [11] and text from Librispeech language modeling corpus, which both come from the audiobook but are collected in speech and text form, respectively. The experimental setup is unrealistic in the unsupervised learning scenario because no prior knowledge about speech transcription exists. The intrinsic properties of the selected text corpus and speech data may be reasonably different. Therefore, we investigate the robustness of Wav2vec-U by utilizing the speech and text that come from different datasets to simulate dissimilarities in content.

Spontaneous speech: The audio data used in the training of Wav2vec-U, even in low-resource experiments, are all read speech. Read speech is clean and well-structured; on the other hand, real-world speech data contains noises and disfluencies. Furthermore, real-world speech lacks literary expressions and causes dissimilarity to text corpus in content. To investigate the robustness of Wav2vec-U with real-world speech, we conduct further experiments on spontaneous speech datasets such as conversational speech and live talk, which is real-time generated with the casual styles.

Quantity limitation: The results of Wav2vec-U show that it is possible to train an unsupervised ASR model by a minimal amount of speech and text from the audiobook. However, in the domain-mismatched conditions, whether we can still use a limited amount of data to train an unsupervised ASR model is under-explored. The more significant variance present in fewer data intensifies the degree of domain mismatch. Hence, we restrict the amount of data in domain mismatch conditions for testing the training robustness.

The main findings of our work are listed below:

- When the content of speech and text is dissimilar, using a large amount of text retains the performance, but reducing to the small amount of texts considerably degrades the results.
- We discover that 4-gram information distribution of phoneme is critical for successfully training the GAN-based unsupervised ASR model.
- Self-supervised pre-training on targeted speech domain enables extracting better feature representation and significantly improves the performance.

^{*} These authors contributed equally.

This material is based on work that is partially funded by an unrestricted gift from Google.

Corpus	LibriLM	Wiki	NewsCrawl	ImageC	
Domain	Literature	Encyclopedia	News	Image Caption	
Size (word)	635M	82M	432M	33M	
Description	Librispeech language	Extracted from	Extracted article text	Combination of COCO [12]	
	modeling data with the	the set of verified	from multiple online news	and Conceptual Caption [13]	
	Libri-Light removed [14] ¹	"Good" and "Featured"	publications ²	containing annotated and	
		articles on Wikipedia [15]		web-scraped image captions.	

Table 1. Descriptions of text corpora.

Name	Domain	Size (hr)	Speech Characteristics
Librispeech train-960 [11]	Read Literature	960	Read speech, speak clearly
SwitchBoard [16]	Telephone conversation	300	Spontaneous, noisy, speak fast
TED-LIUM v3 [17]	Live talk	452	Spontaneous, little noise, speak clearly

Table 2. Descriptions of speech dataset

2. GAN-BASED UNSUPERVISED ASR

Unsupervised ASR takes audio signals as input and outputs the phoneme sequences without phoneme-labeled supervision. [5] first proposes to cluster the speech embedding into discrete tokens and applies Generative Adversarial Network [7] to learn a mapping matrix that aligns discrete acoustic sequences and phoneme sequences. Although this pioneering work shows encouraging preliminary results, the method requires annotations of phoneme boundaries. [6] propose to use unsupervised audio segmentation approaches as the initial segmentation, then adopting Hidden Markov Model (HMM)/GAN harmonization to refine the segmentation boundaries iteratively. This method does not need any annotated phoneme boundaries and can even improve performance.

Recently, Wav2vec-U [1] has shown promising results in unsupervised speech recognition using self-supervised speech representation coupled with GAN training and self-training. Specifically, they extract acoustic representation by the self-supervised pretrained model, Wav2vec 2.0 [18], which consists of a convolutional feature encoder to convert raw waveform into latent representation and a Transformer [19] for learning context representation by the self-supervised objective. Next, they cluster the representations extracted by Wav2vec 2.0, apply PCA to reduce dimension, and mean-pool the representations in the same cluster to generate condensed segment representations. They apply GAN to map the segment representation to phoneme prediction, and the preliminary phoneme prediction has already outperformed previous work by a large margin. Finally, to further refine the prediction, they adopt self-training for HMM, which retrains HMMs by treating GAN outputs as pseudo labels or fine-tuning another Wav2vec 2.0 model by pseudo labels. After subsequent self-training, the error rate is close to the supervised ASR model.

3. EXPERIMENTAL SETUP

The primary interest of this work is to examine the robustness of the state-of-the-art unsupervised ASR method, Wav2vec-U. Our work focuses on how domain mismatch affects cross-modal GAN training, so we do not use tricks like HMM self-training and fine-tuning for refinement. We measure the phoneme error rate (PER) of the Viterbidecoded generator output.

3.1. Data preparation

We designed three main testing setups, and the data information is in Table 1 and 2.

Content dissimilarity: We test the GAN performance when the text corpus represents different domains, including encyclopedia (Wiki), News (NewsCrawl), and image captions (ImageC). The vocabulary usages and narrative styles are pretty dissimilar among them. For instance, the text in News is used to report current affairs, whereas the ImageC text consists of descriptions of images. The sentence length for ImageC is short, and adjectives and nouns consist of a larger proportion.

Spontaneous speech: We regard spontaneous speech as the domain mismatched speech because it is naturally generated and relatively easy to collect. We choose the SwitchBoard dataset to represent telephone/conversational speech and the TED-LIUM v3 dataset for lectures/monologue. The quality of the TED talk speech is clean and includes multiple types of oratory skills by the speakers. In contrast, the speech in the SwitchBoard contains telephone channel noise, disfluency, and various speaking styles.

Quantity limitation: [1] successfully trained Wav2vec-U with 9.6 hours of LibriSpeech and 3k text sentences in LibriLM. We are interested in how the low amount of speech and text data affects performance when the content of speech and text are mismatched. Therefore, we cap the speech data to 10 hours and the text data to 3k or 30k sentences and repeat experiments in the first two settings.

3.2. Implementation Details

We train unsupervised speech recognition using the official code³. All the English text corpora are transformed to phoneme by graphemeto-phoneme conversion [20] and pre-processed with 0.25 rate of silence token insertion as [1]. The speech pre-processing involves silence removal by the unsupervised robust voice activity detection (rVAD) [21] and audio representation extracted by self-supervised pre-training speech model. Specifically, we leverage two kinds of pre-trained Wav2vec 2.0 Large model [18]. One is only pre-train on reading speech from Libri-Light [22] (*w2v2*), the other is pre-train on heterogeneous sources, including Libri-Light, CommonVoice [23], Switchboard [16] and Fisher [24][25]) from [26] (*w2v2-all*)⁴.

The training and evaluation are based on the standard training

¹https://github.com/flashlight/wav2letter/tree/main/recipes/sota/2019

²http://www.statmt.org/wmt14/translation-task.html

 $^{^3} https://github.com/pytorch/fairseq/tree/main/examples/wav2vec/unsupervised$

⁴Both pre-trained models' checkpoint are open-source and can be down-loaded on https://github.com/pytorch/fairseq/tree/main/examples/wav2vec

Speech	Text						
Corpus Hour		LibriLM	Wiki	NewsCrawl	ImageC	matched*	unmatched*
Full amount of speech							
Librispeech train	960	20.25	26.02	21.83	31.59	N/A	N/A
TED-LIUM v3	452	31.62	35.21	32.05	41.87	28.13	N/A
SwitchBoard	300	92.10	93.08	95.25	80.15	35.80	N/A
SwitchBoard-w2v2-all	300	44.38	94.12	43.44	72.10	32.34	N/A
Little amount of speech							
Librispeech train	9.6	22.51	29.03	24.65	105.00	-	-
TED-LIUM v3	10	36.01	88.26	33.52	85.92	29.13	32.44
SwitchBoard	10	95.86	-	-	-	95.13	93.48
SwitchBoard-w2v2-all	10	92.10	-	-	-	96.14	93.48

Table 3. Phoneme Error Rate (PER) of different speech-text corpus pairs. If not specified, we use w2v2 for feature extraction. We use the entire text data of the text corpus in Table 1. A dashed line denotes that we do not experiment on that combination because experimental results in the most feasible setting (speech/in-domain exact matched text) have already failed to converge (higher than 90% PER). Therefore, we expect those speech and out-of-domain text combinations to fail with a PER around 90, and the exact numerical PER result is no longer meaningful in that range. N/A denotes that the combination is non-applicable.

Speech		Text						
Name	Hour	LibriLM	Wiki	NewsCrawl	ImageC	matched*	unmatched*	
Librispeech train	960	0.0058	0.1697	0.0785	0.2635	N/A	N/A	
Librispeech train	9.6	0.0720	0.2228	0.1375	0.3003	-	-	
SwitchBoard	300	0.1357	0.2513	0.1499	0.3174	0	N/A	
SwitchBoard	10	0.2248	0.3339	0.2407	0.3869	0	0.0866	
TED-LIUM v3	452	0.0880	0.1825	0.0841	0.2678	0	N/A	
TED-LIUM v3	10	0.1909	0.2855	0.1928	0.3452	0	0.1014	

Table 4. 4-gram JS-Divergence of different speech-text corpus pairs. We use the entire text data of the text corpus in Table 1. N/A denotes that the combination is non-applicable

and validation split for Librispeech and TED-LIUM v3. There is no standard split for Switchboard, so we create the training/validation set by 80/20 random sampling ratio. The content of two settings: "matched" and "unmatched" depends on the speech dataset; the matched set is the transcription of the speech dataset, while the unmatched setting is the transcription of the unused portion in the speech dataset. If the entire audio dataset is used for training, such as the Librispeech train-960 dataset, the "unmatched" set does not exist. For hyperparameter settings, we set code penalty to 4, gradient penalty to 2, and smoothness weight to 0.5. We train 150000 steps with a batch size of 128. Following the unsupervised model selection metric in Wav2vec-U, we use the perplexity of the phoneme language model to choose the best model. Each setup is trained with three random seeds and reports the average PER.

3.3. Domain mismatch measurement

To quantify the content difference between speech and text, we use the phoneme sequence of speech transcription and text to count the n-grams, then converting counting into n-gram phoneme distributions. Finally, we measure the n-gram Jensen-Shannon Divergence (JSD) between the two distributions to estimate the extent of domain mismatch between speech and text content.

JSD is a smoothed symmetric version of the Kullback–Leibler divergence (KLD), and the formula for JSD between two distributions P and Q is:

$$JSD(P||Q) = \frac{1}{2}KLD(P||\frac{Q+P}{2}) + \frac{1}{2}KLD(Q||\frac{Q+P}{2})$$

with

$$KLD(P||Q) = \sum P(x)log\frac{P(x)}{Q(x)}$$

4. EXPERIMENTAL RESULTS

We conclude the experimental results with three critical questions about Wav2vec-U training robustness.

4.1. How do different text influence the performance?

We apply JSD to measure the degree of content dissimilarity. Table 4 shows the 4-gram JSD of experimented speech-text corpora pairs. For the matched setup, the JSD is always zero. As expected, the JSD between Librispeech and LibriLM is very low. For spontaneous speech such as TED-LIUM and SwitchBoard, pairing with both LibriLM and NewsCrawl produce similar low scores. The 4-gram distribution is larger when the text corpus is the Wiki or ImageC, suggesting their content is more dissimilar to spontaneous speech.

The results of PER under different settings are in Table 3. Pairing the PER results in Table 3 the corresponding JSD in Table 4, we observe a correlation between n-gram JSD and the performance, so we plotted the n-gram JSD to PER for Librispeech-960 experiments in Figure 2, where we analyze phoneme collocations from length 1 to 4. Our experiments observe that the PER rises sharply when 4-gram JSD increases to a certain degree. For 3-gram, the boundary is not perfect but provides rough guidance, while such a boundary is nonexistent in both 1-gram and 2-gram. We can therefore infer that the GAN training mainly relies on 3-gram and 4-gram information. Since the 4-gram JSD is the most discriminant among our experimented n-grams, we only focus on 4-grams in the following sections, and we refer *trainability threshold* as the 4-gram JSD value that corresponds to the large PER gap around 40 to 60.

4.2. Does spontaneous speech influence the performance?

In the upper part of Table 3 labeled with "Full amount of speech", the resulting PER shows that we can successfully train GAN with




Fig. 2. JSD-PER between Librispeech-960 and text. Each set of 1 to 4-gram connected by one horizontal PER line represents one experimental setting. For all experiments, the corresponding text corpus can be found in Table 3 and 5 using PER as the index.




Fig. 3. 4-gram JSD-PER between Speech and text. Each notation corresponds to a kind of speech, while different points of the same notation denote different experimental settings. The detailed speechtext pairings can be found in Table 3 and 5 using PER as the index.

TED talk speech paired with all kinds of text corpora. As for the results of Switchboard, when the feature representations are extracted from w2v2, only training with matched text is successful. The undesirable performance may come from telephone noise, disfluency in spoken conversation, and diversity of speaking styles, which degrade the feature representation extracted from w2v2. The poor representations result in less accurate speech segmentation and further hinder GAN training.

We leverage w2v2-all for feature extraction to extract better feature representations, which is pre-trained on broad domains, including Switchboard. Table 3 demonstrates encouraging results that w2v2-all improve PER from 92.10 to 44.38 with LibirLM and 95.23 to 43.44 with NewsCrawl. This result indicates that the quality of representation is crucial for training unsupervised ASR and self-supervised pre-training on target-domain speech helps extract better representations, significantly improving GAN performance.

In the 4-gram JSD-PER plot of different speech data (Figure 2), the trainability threshold changes depending on the speech quality and extracted representation. For the Librispeech and TED talk speech data, the trainability threshold lies around 0.27. On the other hand, for Switchboard data extracted by w2v2, only training with matched text results in reasonable PER, so the trainability threshold is close to 0. When we extract features by w2v2-all, the trainability threshold increases to around 0.25. We conclude that since TED-

Text	Hour	LibriLM	Wiki	NewsCrawl	ImageC
30k	960	23.46	22.56	22.40	34.05
3k	960	25.85	70.08	69.20	62.22
3k	9.6	33.03	-	-	_

Table 5. Phoneme Error Rate (PER) for Librispeech and the limited amount of text, only 3k or 30k sentences. A dashed line in the Table denotes that we do not experiment on that combination because the same scenarios with more speech training data have already failed.

Text	Hour	LibriLM	Wiki	NewsCrawl	ImageC
30k	960	0.0822	0.1332	0.1070	0.2213
3k	960	0.2478	0.3525	0.3420	0.3647
3k	9.6	0.2607	0.3583	0.3492	0.3716

Table 6. JSD for Librispeech and the limited amount of text, only 3k or 30k sentences for training.

LIUM is clean spontaneous speech, the content similarity is the primary factor, while for noisy speech such as SwitchBoard, a better representation is required.

4.3. Does the amount of data matter when the domain is mismatched?

In the bottom part of Table 3 labeled with "Limited amount of speech", training with the limited amount of speech data produces inferior results to full-speech data setups, especially on the Switchboard dataset, where training fails across all text settings, including training with the "matched" corpus with no divergence at all. Table 6 shows that sub-sampling speech data increases JS-divergence and content dissimilarity given the same text corpus.

The results of using the limited amount of text data are listed in Table 5 and 6. We can observe that training with full Librispeech (960 hours of speech data) and 3k text in domains other than LibriLM fails. The poor performance can be explained by a significant increase in JS-divergence value when the text dataset is limited to 3k sentences. When JSD exceeds its trainability threshold, the performance drops sharply as a result. Overall, the experimental results demonstrate that when speech and text data are already domain-mismatched, the amount of data plays an essential role in GAN training.

5. CONCLUSION

In this paper, we comprehensively investigate the robustness of the Wav2vec-U in different domain mismatch scenarios. The experimental results indicate that content dissimilarity indeed degrades the performance, which correlates with the 4-gram JSD metric. Besides, spontaneous speech makes the GAN training more difficult, but pretraining the self-supervised model on the target speech data dramatically reduces the phoneme error rate. In addition, when non-parallel speech and text are from different domains, more data is required to make unsupervised ASR feasible. We conclude that unsupervised ASR requires improvement in domain mismatch scenarios and hope to incentivize future research on this kind of direction.

6. ACKNOWLEDGEMENT

We thank National Center for High-performance Computing (NCHC) of National Applied Research Laboratories (NARLabs) in Taiwan for providing computational and storage resources.

7. REFERENCES

- [1] Alexei Baevski, Wei-Ning Hsu, Alexis Conneau, and Michael Auli, "Unsupervised speech recognition," *arXiv preprint arXiv:2105.11084*, 2021.
- [2] Chih-Kuan Yeh, Jianshu Chen, Chengzhu Yu, and Dong Yu, "Unsupervised speech recognition via segmental empirical output distribution matching," in *Proc. ICLR*, 2019.
- [3] Hanan Aldarmaki, Asad Ullah, and Nazar Zaki, "Unsupervised automatic speech recognition: A review," arXiv preprint arXiv:2106.04897, 2021.
- [4] Alexander H. Liu, Tao Tu, Hung yi Lee, and Lin-Shan Lee, "Towards unsupervised speech recognition and synthesis with quantized speech representation learning," ICASSP 2020 -2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 7259–7263, 2020.
- [5] Da-Rong Liu, Kuan-Yu Chen, Hung-Yi Lee, and Lin shan Lee, "Completely unsupervised phoneme recognition by adversarially learning mapping relationships from audio embeddings," in *Proc. Interspeech*, 2018.
- [6] Kuan-Yu Chen, Che-Ping Tsai, Da-Rong Liu, Hung-Yi Lee, and Lin shan Lee, "Completely unsupervised speech recognition by a generative adversarial network harmonized with iteratively refined hidden markov models," in *Proc. Interspeech*, 2019.
- [7] Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio, "Generative adversarial networks," 2014.
- [8] Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, et al., "Deep speech 2: End-to-end speech recognition in english and mandarin," in *International conference on machine learning*. PMLR, 2016, pp. 173–182.
- [9] Yu Zhang, James Qin, Daniel S Park, Wei Han, Chung-Cheng Chiu, Ruoming Pang, Quoc V Le, and Yonghui Wu, "Pushing the limits of semi-supervised learning for automatic speech recognition," *arXiv preprint arXiv:2010.10504*, 2020.
- [10] Hainan Xu, Ke Li, Yiming Wang, Jian Wang, Shiyin Kang, Xie Chen, Daniel Povey, and Sanjeev Khudanpur, "Neural network language modeling with letter-based features and importance sampling," in 2018 IEEE international conference on acoustics, speech and signal processing (ICASSP). IEEE, 2018, pp. 6109–6113.
- [11] Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur, "Librispeech: An asr corpus based on public domain audio books," in 2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2015, pp. 5206–5210.
- [12] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick, "Microsoft coco: Common objects in context," in European conference on computer vision. Springer, 2014, pp. 740–755.
- [13] Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut, "Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning," in *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2018, pp. 2556–2565.

- [14] Gabriel Synnaeve, Qiantong Xu, Jacob Kahn, Edouard Grave, Tatiana Likhomanenko, Vineel Pratap, Anuroop Sriram, Vitaliy Liptchinsky, and Ronan Collobert, "End-to-end asr: from supervised to semi-supervised learning with modern architectures," arXiv preprint arXiv:1911.08460, 2019.
- [15] Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher, "Pointer sentinel mixture models," arXiv preprint arXiv:1609.07843, 2016.
- [16] John J. Godfrey and Edward Holliman, "Switchboard-1 release 2 ldc97s62," in Web Download. Philadelphia: Linguistic Data Consortium, 1993.
- [17] François Hernandez, Vincent Nguyen, Sahar Ghannay, Natalia Tomashenko, and Yannick Estève, "Ted-lium 3: Twice as much data and corpus repartition for experiments on speaker adaptation," *Lecture Notes in Computer Science*, p. 198–208, 2018.
- [18] Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli, "wav2vec 2.0: A framework for self-supervised learning of speech representations," in *Advances in Neural Information Processing Systems*, H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, Eds. 2020, vol. 33, pp. 12449–12460, Curran Associates, Inc.
- [19] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin, "Attention is all you need," in *Advances in neural information processing systems*, 2017, pp. 5998–6008.
- [20] Kyubyong Park and Jongseok Kim, "g2pe," https://github.com/Kyubyong/g2p, 2019.
- [21] Zheng Hua Tan, Achintya kr Sarkar, and Najim Dehak, "rvad: An unsupervised segment-based robust voice activity detection method," *Computer Speech and Language*, vol. 59, pp. 1–21, Jan. 2020.
- [22] J. Kahn, M. Rivière, W. Zheng, E. Kharitonov, Q. Xu, P. E. Mazaré, J. Karadayi, V. Liptchinsky, R. Collobert, C. Fuegen, T. Likhomanenko, G. Synnaeve, A. Joulin, A. Mohamed, and E. Dupoux, "Libri-light: A benchmark for asr with limited or no supervision," in *ICASSP 2020 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2020, pp. 7669–7673.
- [23] Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis Tyers, and Gregor Weber, "Common voice: A massively-multilingual speech corpus," in *Proceedings of the 12th Language Resources and Evaluation Conference*, Marseille, France, May 2020, pp. 4218–4222, European Language Resources Association.
- [24] Cieri and Christopher, "Fisher english training speech part 1 and 2 speech ldc200{4,5}s13," in *Web Download. Philadel-phia: Linguistic Data Consortium*, 2004, 2005.
- [25] Cieria and Christopher, "Fisher english training speech part 1 and 2 speech ldc200 transcripts {4,5}t19," in *Web Download. Philadelphia: Linguistic Data Consortium*, 2004, 2005.
- [26] Wei-Ning Hsu, Anuroop Sriram, Alexei Baevski, Tatiana Likhomanenko, Qiantong Xu, Vineel Pratap, Jacob Kahn, Ann Lee, Ronan Collobert, Gabriel Synnaeve, and Michael Auli, "Robust wav2vec 2.0: Analyzing domain shift in selfsupervised pre-training," arXiv preprint arXiv:2104.01027, 2021.