Efficient Computation of Representative Sets with Applications in Parameterized and Exact Algorithms^{*}

Fedor V. Fomin[†] Daniel Lokshtanov[†] Fahad Panolan[†] Saket Saurabh^{‡ †}

Abstract

Let $M = (E, \mathcal{I})$ be a matroid and let $S = \{S_1, \ldots, S_t\}$ be a family of subsets of E of size p. A subfamily $\widehat{S} \subseteq S$ is *q*-representative for S if for every set $Y \subseteq E$ of size at most q, if there is a set $X \in S$ disjoint from Y with $X \cup Y \in \mathcal{I}$, then there is a set $\widehat{X} \in \widehat{S}$ disjoint from Y with $\widehat{X} \cup Y \in \mathcal{I}$. By the classical result of Bollobás, in a uniform matroid, every family of sets of size phas a *q*-representative family with at most $\binom{p+q}{p}$ sets. In his famous "two families theorem" from 1977, Lovász proved that the same bound also holds for any matroid representable over a field \mathbb{F} . As observed by Marx, Lovász's proof is constructive. In this paper we show how Lovász's proof can be turned into an algorithm constructing a *q*-representative family of size at most $\binom{p+q}{p}$ in time bounded by a polynomial in $\binom{p+q}{p}$, t, and the time required for field operations.

We demonstrate how the efficient construction of representative families can be a powerful tool for designing single-exponential parameterized and exact exponential time algorithms. The applications of our approach include the following.

- In the LONG DIRECTED CYCLE problem the input is a directed *n*-vertex graph G and the positive integer k. The task is to find a directed cycle of length at least k in G, if such a cycle exists. As a consequence of our $6.75^{k+o(k)}n^{\mathcal{O}(1)}$ time algorithm, we have that a directed cycle of length at least $\log n$, if such cycle exists, can be found in polynomial time. As it was shown by Björklund, Husfeldt, and Khanna [ICALP 2004], under an appropriate complexity assumption, it is impossible to improve this guarantee by more than a constant factor. Thus our algorithm not only improves over the best previous $\log n/\log\log n$ bound of Gabow and Nie [SODA 2004] but also closes the gap between known lower and upper bounds for this problem.
- In the MINIMUM EQUIVALENT GRAPH (MEG) problem we are seeking a spanning subdigraph D' of a given *n*-vertex digraph D with as few arcs as possible in which the reachability relation is the same as in the original digraph D. The existence of a single-exponential c^n -time algorithm for some constant c > 1 for MEG was open since the work of Moyles and Thompson [JACM 1969].
- To demonstrate the diversity of applications of the approach, we provide an alternative proof of the results recently obtained by Bodlaender, Cygan, Kratsch and Nederlof for algorithms on graphs of bounded treewidth, who showed that many "connectivity" problems such as HAMILTONIAN CYCLE or STEINER TREE can be solved in time $2^{\mathcal{O}(t)}n$ on *n*-vertex graphs of treewidth at most *t*. We believe that expressing graph problems in "matroid language" shed light on what makes it possible to solve connectivity problems single-exponential time parameterized by treewidth.

For the special case of uniform matroids on n elements, we give a faster algorithm to compute a representative family. We use this algorithm to provide the fastest known deterministic parameterized algorithms for k-PATH, k-TREE, and more generally, for k-SUBGRAPH ISOMORPHISM, where the k-vertex pattern graph is of constant treewidth. For example, our k-PATH algorithm runs in time $\mathcal{O}(2.619^k n \log n \log W)$ on weighted graphs with maximum edge weight W.

^{*}Preliminary versions of this paper appeared in the proceedings of SODA 2014 and ESA 2014. Supported by Rigorous Theory of Preprocessing, ERC Advanced Investigator Grant 267959 and Parameterized Approximation, ERC Starting Grant 306992.

[†]University of Bergen, Norway. {fomin|daniello}@ii.uib.no

[‡]Institute of Mathematical Sciences, India. saket@imsc.res.in

Contents

1	1 Introduction			2						
2	2 Preliminaries	Preliminaries								
	2.1 Randomized Al	gorithms		8						
	2.2 Matroids	~		8						
	2.3 Linear Matroids	s and Representable Matroids		8						
	2.4 Direct Sum of M	Matroids		9						
	2.5 Uniform and Pa	artition Matroids		9						
	2.6 Graphic Matroi	ds		10						
	2.7 Truncation of a	$Matroid. \ldots \ldots$		10						
3	3 Fast Computation	for Representative Sets for Linear Matroids		10						
4	4 Fast Computation	Fast Computation for Representative Sets for Uniform Matroids								
	4.1 Representative	Sets using Lopsided Universal Sets		14						
	4.2 Representative	Sets using Separating Collections		16						
5	5 Applications	Applications								
	5.1 Long Directed (Cycle		33						
	5.2 Faster Long Dir	cected Cycle		37						
	5.3 Minimum Equiv	valent Graph		39						
	5.4 Dynamic Progra	amming over graphs of bounded treewidth		43						
	5.4.1 Treewidt	th		43						
	5.4.2 Steiner	R TREE parameterized by treewidth		44						
	5.5 Path, Trees and	Subgraph Isomorphism		49						
	5.5.1 <i>k</i> -Path	· · · · · · · · · · · · · · · · · · ·		49						
	5.5.2 k -Tree	and k-Subgraph Isomorphism		50						
	5.6 Other Applicati	ions		56						
_										

6 Conclusion and Recent Developments

56

1 Introduction

The theory of matroids provides a deep insight into the tractability of many fundamental problems in Combinatorial Optimizations like MINIMUM WEIGHT SPANNING TREE or PERFECT MATCHING. Marx in [42] was the first to apply matroids to design fixed-parameter tractable algorithms. The main tool used by Marx was the notion of *representative families*. Representative families for set systems were introduced by Monien in [44].

Let $M = (E, \mathcal{I})$ be a matroid and let $S = \{S_1, \ldots, S_t\}$ be a family of subsets of E of size p. A subfamily $\hat{S} \subseteq S$ is *q*-representative for S if for every set $Y \subseteq E$ of size at most q, if there is a set $X \in S$ disjoint from Y with $X \cup Y \in \mathcal{I}$, then there is a set $\hat{X} \in \hat{S}$ disjoint from Y and $\hat{X} \cup Y \in \mathcal{I}$. In other words, if a set Y of size at most q can be extended to an independent set of size |Y| + p by adding a subset from S, then it also can be extended to an independent set of size |Y| + p by adding a subset from \hat{S} as well.

The Two-Families Theorem of Bollobás [9] for extremal set systems and its generalization to subspaces of a vector space of Lovász [38] (see also [25]) imply that every family of sets of size p has a q-representative family with at most $\binom{p+q}{p}$ sets. These theorems are the corner-stones in extremal set theory with numerous applications in graph and hypergraph theory, combinatorial

geometry and theoretical computer science. We refer to Section 9.2.2 of [31], surveys of Tuza [54, 55], and Gil Kalai's $blog^1$ for more information on the theorems and their applications.

For set families, or equivalently for uniform matroids, Monien provided an algorithm computing a q-representative family of size at most $\sum_{i=0}^{q} p^{i}$ in time $\mathcal{O}(pq \cdot \sum_{i=0}^{q} p^{i} \cdot t)$ [44]. Marx in [41] provided another algorithm, also for uniform matroids, for finding q-representative families of size at most $\binom{p+q}{p}$ in time $\mathcal{O}(p^{q} \cdot t^{2})$. For linear matroids, Marx [42] has shown how Lovász's proof can be transformed into an algorithm computing a q-representative family. However, the running time of the algorithm given in [42] is $f(p,q)(||A_{M}||t)^{\mathcal{O}(1)}$, where f(p,q) is a polynomial in $(p+q)^{p}$ and $\binom{p+q}{p}$, that is, $f(p,q) = 2^{\mathcal{O}(p\log(p+q))} \cdot \binom{p+q}{p}^{\mathcal{O}(1)}$, and A_{M} is the matroid's representation matrix. Thus, when p is a constant, which is the way this lemma has been recently used in the kernelization algorithms [36], we have that $f(p,q) = (p+q)^{\mathcal{O}(1)}$. However, for unbounded p (for an example when $p = q = \frac{k}{2}$) the running time of this algorithm is bounded by $2^{\mathcal{O}(k\log k)}(||A_{M}||t)^{\mathcal{O}(1)}$.

Our results. We give two faster algorithms computing representative families and show how they can be used to obtain improved parameterized and exact exponential algorithms for several fundamental and well studied problems.

Our first result is the following

Theorem 1. Let $M = (E, \mathcal{I})$ be a linear matroid of rank p + q = k given together with its representation matrix A_M over a field \mathbb{F} . Let $S = \{S_1, \ldots, S_t\}$ be a family of independent sets of size p. Then a q-representative family $\hat{S} \subseteq S$ for S with at most $\binom{p+q}{p}$ sets can be found in $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega}+t\binom{p+q}{q}^{\omega-1}\right)$ operations over \mathbb{F} . Here, $\omega < 2.373$ is the matrix multiplication exponent.

Actually, we will prove a variant of Theorem 1 which allows sets to have weights. This extension will be used in several applications. This theorem uses the notion of weighted representative families and computes a weighted q-representative family of size at most $\binom{p+q}{p}$ within the running time claimed in Theorem 1. The proof of Theorem 1 relies on the exterior algebra based proof of Lovász [38] and exploits the multi-linearity of the determinant function.

For the case of uniform matroids, we provide the following theorem

Theorem 2. Let $S = \{S_1, \ldots, S_t\}$ be a family of sets of size p over a universe of size nand let 0 < x < 1. For a given q, a q-representative family $\widehat{S} \subseteq S$ for S with at most $x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)}$ sets an be computed in time $\mathcal{O}((1-x)^{-q} \cdot 2^{o(p+q)} \cdot t \cdot \log n)$.

As in the case of Theorem 1, we prove a more general version of Theorem 2 for weighted sets. The proof of Theorem 2 is essentially an algorithmic variant of the "random permutation" proof of Bollobás Lemma (see [31, Theorem 8.7]). A slightly weaker variant of Bollobás Lemma can be proved using random partitions instead of random permutations, the advantage of the random partitions proof being that it can be de-randomized using efficient constructions of *universal sets* [47]. To obtain our results we define *separating collections* and give efficient constructions of them.

Separating collections can be seen as a variant of universal sets. In its simplest form, an *n*-*p*-*q*-separating collection \mathcal{C} is a pair (\mathcal{F}, χ) , where \mathcal{F} is a family of sets over a universe U of size n and χ is a function from $\binom{U}{p}$ to $2^{\mathcal{F}}$ such that the following two properties are satisfied; (a) for every $A \in \binom{U}{p}$ and every $F \in \chi(A), A \subseteq F$, (b) for every $A \in \binom{U}{p}$ and $B \in \binom{U \setminus A}{q}$, there is an $F \in \chi(A)$ such that $A \subseteq F$ and $F \cap B = \emptyset$. The size of (\mathcal{F}, χ) is $|\mathcal{F}|$, whereas the max

¹http://gilkalai.wordpress.com/2008/12/25/lovaszs-two-families-theorem/

degree of (\mathcal{F}, χ) is $\max_{A \in \binom{U}{p}} |\chi(A)|$. Here 2^S for a set S is the family of all subsets of S while $\binom{S}{p}$ is the family of all subsets of S of size p.

An efficient construction of separating collections is an algorithm that given n, p and q outputs the family \mathcal{F} of a separating collection (\mathcal{F}, χ) and then allows queries $\chi(A)$ for $A \in \binom{U}{p}$. We give constructions of separating collections of optimal (up to subexponential factors in p+q) size and degree, and construction and query time which is linear (up to subexponential factors in p+q) in the size of the output.

In the conference version of the paper [24], we only proved Theorem 2 for $x = \frac{p}{p+q}$. That is, let $S = \{S_1, \ldots, S_t\}$ be a family of sets of size p over a universe of size n. Then, for a given q, a q-representative family $\hat{S} \subseteq S$ for S with at most $\binom{p+q}{p} \cdot 2^{o(p+q)} \cdot \log n$ sets can be computed in time $\mathcal{O}((\frac{p+q}{q})^q \cdot 2^{o(p+q)} \cdot t \cdot \log n)$. Later we observed that our proof works for every 0 < x < 1and allows an interesting trade-off between the size of the computed representative families and the time taken to compute them [22], and that this trade-off can be exploited algorithmically to speed up "representative families based" algorithms. Theorem 2 improves over the one in [24] by shaving off a multiplicative factor of $\log n$ from the upper bound on the output family size. Independently, at the same time, Shachnai and Zehavi [53] also observed that our initial proof could be generalized in essentially the same way as what is stated in Theorem 2, and that this generalization used to speed up some of the algorithms given in the preliminary version of the paper [24]. In particular they obtain the same dependence on k in the running time bounds as in this paper for k-PATH and LONG DIRECTED CYCLE.

Applications.	Here we	provide t	the list	t of mair	1 applicat	tions	that	can b	e deriv	ed	from	our
algorithms that	$\operatorname{compute}$	represen	tative	families	together	with	a sh	ort ov	verview	of	previ	ious
work on each ap	plication.											

Reference	Randomized	Deterministic
Monien [44]	-	$\mathcal{O}(k!nm)$
Bodlaender [7]	-	$\mathcal{O}(k!2^kn)$
Alon et al. $[2]$	$\mathcal{O}(5.44^k n)$	$\mathcal{O}(c^k n \log n)$ for a large c
Kneis at al. [33]	$\mathcal{O}^*(4^k)$	$\mathcal{O}^*(16^k)$
Chen et al. $[12]$	$\mathcal{O}(4^k k^{2.7}m)$	$4^{k+\mathcal{O}(\log^3 k)}nm$
Koutis [34]	$\mathcal{O}^*(2.83^k)$	_
Williams [56]	$\mathcal{O}^*(2^k)$	-
Björklund et al. [5]	$\mathcal{O}^*(1.66^k)$	_
Conference version	-	$\mathcal{O}(2.851^k n \log^2 n)$
This paper	-	$\mathcal{O}(2.619^k n \log n)$

Table 1: Results for k-PATH. We use $\mathcal{O}^*()$ notation that hides factors polynomial in the number of vertices n and the parameter k in cases when the authors do not specify the power of polynomials.

k-Path. In the *k*-PATH problem we are given an undirected *n*-vertex graph *G* and integer *k*. The question is if *G* contains a path of length *k*. *k*-PATH was studied intensively within the parameterized complexity paradigm [18]. For *n*-vertex graphs the problem is trivially solvable in time $\mathcal{O}(n^k)$. Monien [44] and Bodlaender showed that the problem is fixed parameter tractable. Monien used representative families for set systems for his *k*-PATH algorithm [44] and Plehn and Voigt extended this algorithm to SUBGRAPH ISOMORPHISM in [51]. This led Papadimitriou and Yannakakis [49] to conjecture that the problem is solvable in polynomial time for $k = \log n$.

This conjecture was resolved in a seminal paper of Alon et al. [2], who introduced the method of color-coding and obtained the first single exponential algorithm for the problem. Actually, the method of Alon et al. can be applied for more general problems, like finding a k-path in directed graphs, or to solve the SUBGRAPH ISOMORPHISM problem in time $2^{\mathcal{O}(k)}n^{\mathcal{O}(t)}$, when the treewidth of the pattern graph is bounded by t. There has been a lot of efforts in parameterized algorithms to reduce the base of the exponent of both deterministic as well as the randomized algorithms for the k-PATH problem, see Table 1. After the work of Alon et al. [2], there were several breakthrough ideas leading to faster and faster randomized algorithms. Concerning deterministic algorithms, no improvements occurred since 2007, when Chen et al. [13] showed a clever way of applying universal sets to reduce the running time of color-coding algorithm to $\mathcal{O}^*(4^{k+o(k)})$.

k-PATH is a special case of the k-SUBGRAPH ISOMORPHISM problem, where for given n-vertex graph G and k-vertex graph F, the question is whether G contains a subgraph isomorphic to F. In addition to k-PATH, parameterized algorithms for two other variants of k-SUBGRAPH ISOMORPHISM, when F is a tree, and more generally, a graph of treewidth at most t, were studied in the literature. Alon et al. [2] showed that k-SUBGRAPH ISOMORPHISM, when the treewidth of the pattern graph is bounded by t, is solvable in time $2^{\mathcal{O}(k)}n^{\mathcal{O}(t)}$. Cohen et al. gave a randomized algorithm that for an input digraph D decides in time $5.704^k n^{\mathcal{O}(1)}$ if D contains a given out-tree with k vertices [14]. They also showed how to derandomize the algorithm in time $6.14^k n^{\mathcal{O}(1)}$. Amini et al. [3] introduced an inclusion-exclusion based approach in the classical color-coding and gave a randomized $5.4^k n^{\mathcal{O}(t)}$ time algorithm and a deterministic $5.4^{k+o(k)} n^{\mathcal{O}(t)}$ time algorithm for the case when F has treewidth at most t. Koutis and Williams [35] generalized their algebraic approach for k-PATH to k-TREE and obtained a randomized algorithm running in time $2^k n^{\mathcal{O}(1)}$ for k-TREE. A superset of the authors in [23], extended this result by providing a randomized algorithm for k-SUBGRAPH ISOMORPHISM running in time $2^k(nt)^{\mathcal{O}(t)}$, when the treewidth of F is at most t. However, the fastest known deterministic algorithm for this problem prior to this paper, was the time $5.4^{k+o(k)}n^{\mathcal{O}(t)}$ algorithm from [3]. In this paper we give deterministic algorithms for k-PATH and k-TREE that run in time $\mathcal{O}(2.619^k n \log n)$ and $\mathcal{O}(2.619^k n^{\mathcal{O}(1)})$. The algorithm for k-TREE can be generalized to k-SUBGRAPH ISOMORPHISM for the case when the pattern graph F has treewidth at most t. This algorithm will run in time $\mathcal{O}(2.619^k n^{\mathcal{O}(t)})$. Our approach can also be applied to find directed paths and cycles of length k in time $\mathcal{O}(2.619^k m \log n)$ and $\mathcal{O}(2.619^k n^{\mathcal{O}(1)})$ respectively.

Another interesting feature of our approach is that due to using weighted representative families, we can handle the weighted version of the problem as well. The weighted version of k-PATH is known as SHORT CHEAP TOUR. Let G be a graph with maximum edge cost W, then the problem is to find a path of length at least k where the total sum of costs on the edges is minimized. The algorithm of Björklund et al. [5] can be adapted to solve SHORT CHEAP TOUR in time $\mathcal{O}(1.66^k n^{\mathcal{O}(1)}W)$, however, their approach does not seem to be applicable to obtain algorithms with polylogarithmic dependence on W. Williams in [56] observed that a divide-and-color approach from [12] can be used to solve SHORT CHEAP TOUR in time $\mathcal{O}(4^k n^{\mathcal{O}(1)} \log W)$. No better algorithm for SHORT CHEAP TOUR was known prior to our work. As it was noted by Williams, the $\mathcal{O}(2^k n^{\mathcal{O}(1)})$ algorithm of his paper does not appear to extend to weighted graphs. Our approach provides deterministic $\mathcal{O}(2.619^k n^{\mathcal{O}(1)} \log W)$ time algorithm for SHORT CHEAP TOUR and partially resolves an open question asked by Williams.

Long Directed Cycle. In the LONG DIRECTED CYCLE problem we are interested in finding a cycle of length at least k in a directed graph. For this problem we give an algorithm of running time $\mathcal{O}(6.75^{k+o(k)}mn^2\log n)$.

While at the first glance the problem is similar to the problem of finding a cycle or a path of length exactly k, it is more tricky. The reason is that the problem of finding a cycle of

length $\geq k$ may entail finding a much longer, potentially even a Hamiltonian cycle. This is why color-coding, and other techniques applicable to k-PATH do not seem to work here. Even for undirected graphs color-coding alone is not sufficient, and one needs an additional clever trick to make it work. The first fixed-parameter tractable algorithm for LONG DIRECTED CYCLE is due to Gabow and Nie [26], who gave algorithms with expected running time $k^{2k}2^{\mathcal{O}(k)}nm$ and worstcase times $\mathcal{O}(k^{2k}2^{\mathcal{O}(k)}nm\log n)$ or $\mathcal{O}(k^{3k}nm)$. These running times allow them to find a directed cycle of length at least $\log n/\log\log n$ in expected polynomial time, if it exists. Let us note, that our algorithm implies that one can find in polynomial time a directed cycle of length at least $\log n$ if there is such a cycle. On the other hand, Björklund et al. [6] have shown that assuming Exponential Time Hypothesis (ETH) of Impagliazzo et al. [30], there is no polynomial time algorithm that finds a directed cycle of length $\Omega(f(n)\log n)$, for any nondecreasing, unbounded, polynomial time computable function f that tends to infinity. Thus, our work closes the gap between the upper and lower bounds for this problem.

Minimum Equivalent Graph. Our next application is from exact exponential time algorithms, we refer to [21] for an introduction to the area of exact algorithms. In the MINIMUM EQUIVALENT GRAPH (MEG) problem we are seeking a spanning subdigraph D' of a given digraph D with as few arcs as possible in which the reachability relation is the same as in the original digraph D. In other words, for every pair of vertices u, v, there is a path from u to v in D' if and only if the original digraph D has such a path. We show that this problem is solvable in time $\mathcal{O}(2^{4\omega n}mn)$, where n is the number of vertices and m is the number of arcs in D.

MEG is a classical NP-hard problem generalizing the HAMILTONIAN CYCLE problem, see Chapter 12 of the book [4] for an overview of combinatorial and algorithmic results on MEG. The algorithmic studies of MEG can be traced to the work of Moyles and Thompson [45] from 1969, who gave a (non-trivial) branching algorithm solving MEG in time $\mathcal{O}(n!)$. In 1975, Hsu in [29] discovered a mistake in the algorithm of Moyles and Thompson, and designed a different branching algorithm for this problem. Martello [39] and Martello and Toth [40] gave another branching based algorithm with running time $\mathcal{O}(2^m)$. No single-exponential exact algorithm, i.e. of running time $2^{\mathcal{O}(n)}$, for MEG was known prior to our work.

As it was already observed by Moyles and Thompson [45] the hardest instances of MEG are strong digraphs. A digraph is strong if for every pair of vertices $u \neq v$, there are directed paths from u to v and from v to u. MEG restricted to strong digraphs is known as the MINIMUM SCSS (strongly connected spanning subgraph) problem. It is known that the MEG problem reduces in linear time to MINIMUM SCSS, see e.g. [15].

Treewidth algorithms. We show that efficient computation of representative families can be used to obtain algorithms solving "connectivity" problems like HAMILTONIAN CYCLE or STEINER TREE in time $2^{\mathcal{O}(t)}n$, where t is the treewidth of the input n-vertex graph. It is well known that many intractable problems can be solved efficiently when the input graph has bounded treewidth. Moreover, many fundamental problems like MAXIMUM INDEPENDENT SET or MINIMUM DOMINATING SET can be solved in time $2^{\mathcal{O}(t)}n$. On the other hand, it was believed until very recently that for some "connectivity" problems such as HAMILTONIAN CYCLE or STEINER TREE no such algorithm exists. In their breakthrough paper, Cygan et al. [17] introduced a new algorithmic framework called Cut&Count and used it to obtain $2^{\mathcal{O}(t)}n^{\mathcal{O}(1)}$ time Monte Carlo algorithms for a number of connectivity problems. Very recently, Bodlaender et al. [8] obtained the first deterministic single exponential algorithms for these problems. Bodlaender et al. presented two approaches, one based on rank estimations in specific matrices and the second based on matrix-tree theorem and computation of determinants. Our approach, based on representative families in matroids, can be seen as an alternate path to obtain similar results. The main idea behind our approach is that all the relevant information about "partial solutions" in bags of the tree decomposition, can be encoded as an independent set of a specific matroid. Here efficient computation of representative families comes into play.

In all our applications we first define a specific matroid and then show a combinatorial relation between solution to the problem and independent sets of the matroid. Then we compute representative families using Theorem 1 or Theorem 2 and use them to obtain a solution to the problem. We believe that expressing graph problems in "matroid language" is a generic technique explaining why certain problems admit single-exponential parameterized and exact exponential algorithms. Finally, for completeness we would like to add that in the conference version of the paper, the running time for k-PATH and k-TREE were $\mathcal{O}(2.815^k n^{\mathcal{O}(1)})$; for k-SUBGRAPH ISOMORPHISM for the case when the pattern graph F has treewidth at most t was $\mathcal{O}(2.815^k n^{\mathcal{O}(t)})$ and for LONG DIRECTED CYCLE was $8^{k+o(k)} n^{\mathcal{O}(1)}$.

Organization of the paper. In Section 2 we give the necessary definitions and state some of the known results that we will use. In Section 3 we prove Theorem 1 by giving an efficient algorithm for the computation of representative families for linear matroids. In Section 4 we prove Theorem 2 by giving an efficient algorithm for the computation of representative families for uniform matroids. In Section 5 we give all our applications of Theorems 1 and 2. Concluding remarks and new developments can be found in Section 6. The proofs of Theorem 1 and Theorem 2 are independent of each other and may be read independently. All of our applications use Theorems 1 and 2 as black boxes, and thus may be read independently of the sections describing the efficient computation of representative families.

2 Preliminaries

In this section we give various definitions which we make use of in the paper.

Graphs. Let G be a graph with vertex set V(G) and edge set E(G). A graph G' is a subgraph of G if $V(G') \subseteq V(G)$ and $E(G') \subseteq E(G)$. The subgraph G' is called an *induced subgraph* of G if $E(G') = \{uv \in E(G) \mid u, v \in V(G')\}$, in this case, G' is also called the subgraph *induced* by V(G') and denoted by G[V(G')]. For a vertex set S, by $G \setminus S$ we denote $G[V(G) \setminus S]$. By N(u) we denote (open) neighborhood of u, that is, the set of all vertices adjacent to u. Similarly, by $N[u] = N(u) \cup \{u\}$ we define the closed neighborhood. The degree of a vertex v in G is $|N_G(v)|$ and is denoted by d(v). For a subset $S \subseteq V(G)$, we define $N[S] = \bigcup_{v \in S} N[v]$ and $N(S) = N[S] \setminus S$. By the length of the path we mean the number of edges in it.

Digraphs. Let D be a digraph. By V(D) and A(D) we represent the vertex set and arc set of D, respectively. Given a subset $V' \subseteq V(D)$ of a digraph D, let D[V'] denote the digraph induced by V'. A digraph D is strong if for every pair x, y of vertices there are directed paths from x to y and from y to x. A maximal strongly connected subdigraph of D is called a strong component. A vertex u of D is an *in-neighbor* (out-neighbor) of a vertex v if $uv \in A(D)$ ($vu \in A(D)$, respectively). The *in-degree* $d^-(v)$ (out-degree $d^+(v)$) of a vertex v is the number of its in-neighbors (out-neighbors). We denote the set of in-neighbors and out-neighbors of a vertex v by $N^-(v)$ and $N^+(v)$ correspondingly. A closed directed walk in a digraph D is a sequence $v_0v_1 \cdots v_\ell$ of vertices of D, not necessarily distinct, such that $v_0 = v_\ell$ and for every $0 \le i \le \ell - 1, v_iv_{i+1} \in A(D)$.

Sets, Functions and Constants. We use the following notations: $[n] = \{1, \ldots, n\}$ and $\binom{[n]}{i} = \{X \mid X \subseteq [n], |X| = i\}.$

We use the following operations on families of sets.

Definition 2.1. Given two families of sets \mathcal{A} and \mathcal{B} , we define

(•) $\mathcal{A} \bullet \mathcal{B} = \{X \cup Y \mid X \in \mathcal{A} \text{ and } Y \in \mathcal{B} \text{ and } X \cap Y = \emptyset\}$. Let $\mathcal{A}_1, \ldots, \mathcal{A}_r$ be r families. Then

$$\prod_{i\in[r]}^{\bullet}\mathcal{A}_i=\mathcal{A}_1\bullet\cdots\bullet\mathcal{A}_r.$$

- $(\circ) \ \mathcal{A} \circ \mathcal{B} = \{ A \cup B : A \in \mathcal{A} \text{ and } B \in \mathcal{B} \}.$
- (+) For a set X, we define $\mathcal{A} + X = \{A \cup X : A \in \mathcal{A}\}.$

The first and second derivatives of a function f(x) of a variable x is denoted by f'(x) and f''(x) respectively. Throughout the paper we use ω to denote the exponent in the running time of matrix multiplication, the current best known bound for which is $\omega < 2.373$ [57]. We use e to denote the base of natural logarithm.

2.1 Randomized Algorithms

We follow the same notion of randomized algorithms as described in [42, Section 2.3]. That is, some of the algorithms presented in this paper are randomized, which means that they can produce incorrect answer, but the probability of doing so is small. We assume that the algorithm has an integer parameter P given in unary, and the probability of incorrect answer is 2^{-P} .

2.2 Matroids

In the next few subsections we give definitions related to matroids. For a broader overview on matroids we refer to [48].

Definition 2.2. A pair $M = (E, \mathcal{I})$, where E is a ground set and \mathcal{I} is a family of subsets (called independent sets) of E, is a matroid if it satisfies the following conditions:

(I1)
$$\phi \in \mathcal{I}$$
.

(I2) If $A' \subseteq A$ and $A \in \mathcal{I}$ then $A' \in \mathcal{I}$.

(I3) If $A, B \in \mathcal{I}$ and |A| < |B|, then there is $e \in (B \setminus A)$ such that $A \cup \{e\} \in \mathcal{I}$.

The axiom (I2) is also called the hereditary property and a pair (E, \mathcal{I}) satisfying only (I2) is called hereditary family. An inclusion wise maximal set of \mathcal{I} is called a *basis* of the matroid. Using axiom (I3) it is easy to show that all the bases of a matroid have the same size. This size is called the *rank* of the matroid M, and is denoted by $\mathsf{rank}(M)$.

2.3 Linear Matroids and Representable Matroids

Let A be a matrix over an arbitrary field \mathbb{F} and let E be the set of columns of A. For A, we define matroid $M = (E, \mathcal{I})$ as follows. A set $X \subseteq E$ is independent (that is $X \in \mathcal{I}$) if the corresponding columns are linearly independent over \mathbb{F} . The matroids that can be defined by such a construction are called *linear matroids*, and if a matroid can be defined by a matrix A over a field \mathbb{F} , then we say that the matroid is representable over \mathbb{F} . That is, a matroid $M = (E, \mathcal{I})$ of rank d is representable over a field \mathbb{F} if there exist vectors in \mathbb{F}^d corresponding to the elements such that linearly independent sets of vectors correspond to independent sets of the matroid. A matroid $M = (E, \mathcal{I})$ is called *representable* or *linear* if it is representable over some field \mathbb{F} .

2.4 Direct Sum of Matroids.

Let $M_1 = (E_1, \mathcal{I}_1), M_2 = (E_2, \mathcal{I}_2), \ldots, M_t = (E_t, \mathcal{I}_t)$ be t matroids with $E_i \cap E_j = \emptyset$ for all $1 \leq i \neq j \leq t$. The direct sum $M_1 \oplus \cdots \oplus M_t$ is a matroid $M = (E, \mathcal{I})$ with $E := \bigcup_{i=1}^t E_i$ and $X \subseteq E$ is independent if and only if $X \cap E_i \in \mathcal{I}_i$ for all $i \leq t$. Let A_i be the representation matrix of $M_i = (E_i, \mathcal{I}_i)$. Then,

$$A_M = \begin{pmatrix} A_1 & 0 & 0 & \cdots & 0 \\ 0 & A_2 & 0 & \cdots & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & 0 & \cdots & A_t \end{pmatrix}$$

is a representation matrix of $M_1 \oplus \cdots \oplus M_t$. The correctness of this construction is proved in [42].

Proposition 2.1 ([42, Proposition 3.4]). Given representations of matroids M_1, \ldots, M_t over the same field \mathbb{F} , a representation of their direct sum can be found in polynomial time.

2.5 Uniform and Partition Matroids

A pair $M = (E, \mathcal{I})$ over an *n*-element ground set E, is called a uniform matroid if the family of independent sets is given by $\mathcal{I} = \{A \subseteq E \mid |A| \leq k\}$, where k is some constant. This matroid is also denoted as $U_{n,k}$. Every uniform matroid is linear and can be represented over a finite field by a $k \times n$ matrix A_M where the $A_M[i, j] = j^{i-1}$.

$$A_M = \begin{pmatrix} 1 & 1 & 1 & \cdots & 1 \\ 1 & 2 & 3 & \cdots & n \\ 1 & 2^2 & 3^2 & \cdots & n^2 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 1 & 2^{k-1} & 3^{k-1} & \cdots & n^{k-1} \end{pmatrix}$$

Matrix A_M is called Vandermonde matrix. Observe that for $U_{n,k}$ to be representable over a finite field \mathbb{F} , we need that the determinant of each $k \times k$ submatrix of A_M must not vanish over \mathbb{F} . Observe that any k columns corresponding to x_{i_1}, \ldots, x_{i_k} itself form a Vandermonde matrix, whose determinant is given by

$$\prod_{1 \le j < \ell \le k} (x_{i_j} - x_{i_\ell}).$$

Combining this with the fact that x_1, \ldots, x_n are *n* distinct elements of \mathbb{F} , we conclude that every subset of size at most *k* of the ground set is independent, while clearly each larger subset is dependent. Thus, choosing a field \mathbb{F} of size larger than *n* suffices. Note that this means that a representation of the uniform matroid $U_{n,k}$ can be stored using $\mathcal{O}(\log n)$ bits.

A partition matroid $M = (E, \mathcal{I})$ is defined by a ground set E being partitioned into (disjoint) sets E_1, \ldots, E_ℓ and by ℓ non-negative integers k_1, \ldots, k_ℓ . A set $X \subseteq E$ is independent if and only if $|X \cap E_i| \leq k_i$ for all $i \in \{1, \ldots, \ell\}$. Observe that a partition matroid is a direct sum of uniform matroids $U_{|E_1|,k_1}, \cdots, U_{|E_\ell|,k_\ell}$. Thus, by Proposition 2.1 and the fact that a uniform matroid $U_{n,k}$ is representable over a field \mathbb{F} of size larger than n, we have that.

Proposition 2.2 ([42, Proposition 3.5]). A representation over a field of size $\mathcal{O}(|E|)$ of a partition matroid can be constructed in polynomial time.

2.6 Graphic Matroids

Given a graph G, a graphic matroid $M = (E, \mathcal{I})$ is defined by taking elements as edge of G (that is E = E(G)) and $F \subseteq E(G)$ is in \mathcal{I} if it forms a spanning forest in the graph G. The graphic matroid is representable over any field of size at least 2. Consider the matrix A_M with a row for each vertex $i \in V(G)$ and a column for each edge $e = ij \in E(G)$. In the column corresponding to e = ij, all entries are 0, except for a 1 in i or j (arbitrarily) and a -1 in the other. This is a representation over reals. To obtain a representation over a field \mathbb{F} , one simply needs to take the representation given above over reals and simply replace all -1 by the additive inverse of 1

Proposition 2.3 ([48]). Graphic matroids are representable over any field of size at least 2.

2.7 Truncation of a Matroid.

The *t*-truncation of a matroid $M = (E, \mathcal{I})$ is a matroid $M' = (E, \mathcal{I}')$ such that $S \subseteq E$ is independent in M' if and only if $|S| \leq t$ and S is independent in M (that is $S \in \mathcal{I}$).

Proposition 2.4 ([42, Proposition 3.7]). Given a matroid M with a representation A over a finite field \mathbb{F} and an integer t, a representation of the t-truncation M' can be found in randomized polynomial time.

3 Fast Computation for Representative Sets for Linear Matroids

In this section we give an algorithm to find a q-representative family of a given family. We start with the definition of a q-representative family.

Definition 3.1 (*q*-Representative Family). Given a matroid $M = (E, \mathcal{I})$ and a family S of subsets of E, we say that a subfamily $\hat{S} \subseteq S$ is *q*-representative for S if the following holds: for every set $Y \subseteq E$ of size at most q, if there is a set $X \in S$ disjoint from Y with $X \cup Y \in \mathcal{I}$, then there is a set $\hat{X} \in \hat{S}$ disjoint from Y with $\hat{X} \cup Y \in \mathcal{I}$. If $\hat{S} \subseteq S$ is *q*-representative for S we write $\hat{S} \subseteq_{rep}^{q} S$.

In other words if some independent set in S can be extended to a larger independent set by q new elements, then there is a set in \hat{S} that can be extended by the same q elements. A weighted variant of q-representative families is defined as follows. It is useful for solving problems where we are looking for objects of maximum or minimum weight.

Definition 3.2 (Min/Max q-Representative Family). Given a matroid $M = (E, \mathcal{I})$, a family S of subsets of E and a non-negative weight function $w : S \to \mathbb{N}$, we say that a subfamily $\widehat{S} \subseteq S$ is min q-representative (max q-representative) for S if the following holds: for every set $Y \subseteq E$ of size at most q, if there is a set $X \in S$ disjoint from Y with $X \cup Y \in \mathcal{I}$, then there is a set $\widehat{X} \in \widehat{S}$ disjoint from Y with

- 1. $\widehat{X} \cup Y \in \mathcal{I}$; and
- 2. $w(\widehat{X}) \le w(X) \ (w(\widehat{X}) \ge w(X)).$

We use $\hat{S} \subseteq_{minrep}^{q} S$ ($\hat{S} \subseteq_{maxrep}^{q} S$) to denote a min q-representative (max q-representative) family for S.

We say that a family $S = \{S_1, \ldots, S_t\}$ of sets is a *p*-family if each set in S is of size p.

We start by three lemmata providing basic results about representative sets. These lemmata will be used in Section 5, where we provide algorithmic applications of representative families. We prove them for unweighted representative families but they can be easily modified to work for weighted variant.

Lemma 3.1. Let $M = (E, \mathcal{I})$ be a matroid and S be a family of subsets of E. If $S' \subseteq_{rep}^{q} S$ and $\widehat{S} \subseteq_{rep}^{q} S'$, then $\widehat{S} \subseteq_{rep}^{q} S$.

Proof. Let $Y \subseteq E$ of size at most q such that there is a set $X \in S$ disjoint from Y with $X \cup Y \in \mathcal{I}$. By the definition of q-representative family we have that there is a set $X' \in S'$ disjoint from Y with $X' \cup Y \in \mathcal{I}$. Now the fact that $\widehat{S} \subseteq_{rep}^{q} S'$ yields that there exists a $\widehat{X} \in \widehat{S}$ disjoint from Y with $\widehat{X} \cup Y \in \mathcal{I}$.

Lemma 3.2. Let $M = (E, \mathcal{I})$ be a matroid and S be a family of subsets of E. If $S = S_1 \cup \cdots \cup S_\ell$ and $\hat{S}_i \subseteq_{rep}^q S_i$, then $\cup_{i=1}^{\ell} \hat{S}_i \subseteq_{rep}^q S$.

Proof. Let $Y \subseteq E$ of size at most q such that there is a set $X \in \mathcal{S}$ disjoint from Y with $X \cup Y \in \mathcal{I}$. Since $\mathcal{S} = \mathcal{S}_1 \cup \cdots \cup \mathcal{S}_\ell$, there exists an i such that $X \in \mathcal{S}_i$. This implies that there exists a $\hat{X} \in \hat{\mathcal{S}}_i \subseteq \bigcup_{i=1}^\ell \hat{\mathcal{S}}_i$ disjoint from Y with $\hat{X} \cup Y \in \mathcal{I}$.

Lemma 3.3. Let $M = (E, \mathcal{I})$ be a matroid of rank k and \mathcal{S}_1 be a p_1 -family of independent sets, \mathcal{S}_2 be a p_2 -family of independent sets, $\widehat{\mathcal{S}}_1 \subseteq_{rep}^{k-p_1} \mathcal{S}_1$ and $\widehat{\mathcal{S}}_2 \subseteq_{rep}^{k-p_2} \mathcal{S}_2$. Then $\widehat{\mathcal{S}}_1 \bullet \widehat{\mathcal{S}}_2 \subseteq_{rep}^{k-p_1-p_2} \mathcal{S}_1 \bullet \mathcal{S}_2$.

Proof. Let $Y \subseteq E$ of size at most $q = k - p_1 - p_2$ such that there is a set $X \in S_1 \bullet S_2$ disjoint from Y with $X \cup Y \in \mathcal{I}$. This implies that there exist $X_1 \in S_1$ and $X_2 \in S_2$ such that $X_1 \cup X_2 = X$ and $X_1 \cap X_2 = \emptyset$. Since $\hat{S}_1 \subseteq_{rep}^{k-p_1} S_1$, we have that there exists a $\hat{X}_1 \in \hat{S}_1$ such that $\hat{X}_1 \cup X_2 \cup Y \in \mathcal{I}$ and $\hat{X}_1 \cap (X_2 \cup Y) = \emptyset$. Now since $\hat{S}_2 \subseteq_{rep}^{k-p_2} S_2$, we have that there exists a $\hat{X}_2 \in \hat{S}_2$ such that $\hat{X}_1 \cup \hat{X}_2 \cup Y \in \mathcal{I}$ and $\hat{X}_2 \cap (\hat{X}_1 \cup Y) = \emptyset$. This shows that $\hat{X}_1 \cup \hat{X}_2 \in \hat{S}_1 \bullet \hat{S}_2$ and $\hat{X}_1 \cup \hat{X}_2 \cup Y \in \mathcal{I}$ thus $\hat{S}_1 \bullet \hat{S}_2 \subseteq_{rep}^{k-p_1-p_2} S_1 \bullet S_2$. \Box

The main result of this section is that given a representable matroid $M = (E, \mathcal{I})$ of rank k = p + q with its representation matrix A_M , a *p*-family of independent sets S, and a nonnegative weight function $w : S \to \mathbb{N}$, we can compute $\widehat{S} \subseteq_{minrep}^{q} S$ and $\widehat{S} \subseteq_{maxrep}^{q} S$ of size $\binom{p+q}{p}$ deterministically in time $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega} + t\binom{p+q}{q}^{\omega-1}\right)$. The proof for this result is obtained by making the known exterior algebra based proof of Lovász [38, Theorem 4.8] algorithmic. Although our proof is based on exterior algebra and is essentially the same as the proof given in [38], we give a proof here which avoids the terminology from exterior algebra.

For our proof we also need the following well-known generalized Laplace expansion of determinants. For a matrix $A = (a_{ij})$, the row set and the column set are denoted by $\mathbf{R}(A)$ and $\mathbf{C}(A)$ respectively. For $I \subseteq \mathbf{R}(A)$ and $J \subseteq \mathbf{C}(A)$, $A[I, J] = (a_{ij} \mid i \in I, j \in J)$ means the submatrix (or minor) of A with the row set I and the column set J. For $I \subseteq [n]$ let $\overline{I} = [n] \setminus I$ and $\sum I = \sum_{i \in I} i$.

Proposition 3.1 (Generalized Laplace expansion). For an $n \times n$ matrix A and $J \subseteq \mathbf{C}(A) = [n]$, it holds that

$$\det(A) = \sum_{I \subseteq [n], |I| = |J|} (-1)^{\sum I + \sum J} \det(A[I, J]]) \det(A[\bar{I}, \bar{J}])$$

We refer to [46, Proposition 2.1.3] for a proof of the above identity. We always assume that the number of rows in the representation matrix A_M of M over a field \mathbb{F} is equal to $\mathsf{rank}(M) = \mathsf{rank}(A_M)$. Otherwise, using Gaussian elimination we can obtain a matrix of the desired kind in polynomial time. See [42, Proposition 3.1] for details. We do not give the proof for Theorem 1 but rather for the following generalization.

Theorem 3. Let $M = (E, \mathcal{I})$ be a linear matroid of rank p + q = k, $\mathcal{S} = \{S_1, \ldots, S_t\}$ be a p-family of independent sets and $w : \mathcal{S} \to \mathbb{N}$ be a non-negative weight function. Then there exists $\widehat{\mathcal{S}} \subseteq_{minrep}^q \mathcal{S}$ ($\widehat{\mathcal{S}} \subseteq_{maxrep}^q \mathcal{S}$) of size $\binom{p+q}{p}$. Moreover, given a representation A_M of M over a field \mathbb{F} , we can find $\widehat{\mathcal{S}} \subseteq_{minrep}^q \mathcal{S}$ ($\widehat{\mathcal{S}} \subseteq_{maxrep}^q \mathcal{S}$) of size at most $\binom{p+q}{p}$ in $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega}+t\binom{p+q}{q}^{\omega-1}\right)$ operations over \mathbb{F} .

Proof. We only show how to find $\widehat{S} \subseteq_{minrep}^{q} S$ in the claimed running time. The proof for $\widehat{S} \subseteq_{maxrep}^{q} S$ is analogous, and for that case we only point out the places where the proof differs. If $t \leq {k \choose p}$, then we can take $\widehat{S} = S$. Clearly, in this case $\widehat{S} \subseteq_{minrep}^{q} S$. So from now onwards we always assume that $t > {k \choose p}$. For the proof we view the representation matrix A_M as a vector space over \mathbb{F} and each set $S_i \in S$ as a subspace of this vector space. For every element $e \in E$, let x_e be the corresponding k-dimensional column in A_M . Observe that each $x_e \in \mathbb{F}^k$. For each subspace $S_i \in S$, $i \in \{1, \ldots, t\}$, we associate a vector $\vec{s}_i = \bigwedge_{j \in S_i} x_j$ in $\mathbb{F}^{\binom{k}{p}}$ as follows. In exterior algebra terminology, the vector \vec{s}_i is a wedge product of the vectors corresponding to elements in S_i . For a set $S \in S$ and $I \in \binom{[k]}{p}$, we define $s[I] = \det(A_M[I, S])$.

We also define

$$\vec{s}_i = \left(s_i[I]\right)_{I \in \binom{[k]}{n}}.$$

Thus the entries of the vector \vec{s}_i are the values of det $(A_M[I, S_i])$, where I runs through all the p sized subsets of rows of A_M .

Let $H_{\mathcal{S}} = (\vec{s}_1, \ldots, \vec{s}_t)$ be the $\binom{k}{p} \times t$ matrix obtained by taking \vec{s}_i as columns. Now we define a weight function $w' : \mathbf{C}(H_{\mathcal{S}}) \to \mathbb{R}^+$ on the set of columns of $H_{\mathcal{S}}$. For the column \vec{s}_i corresponding to $S_i \in \mathcal{S}$, we define $w'(\vec{s}_i) = w(S_i)$. Let \mathcal{W} be a set of columns of $H_{\mathcal{S}}$ that are linearly independent over \mathbb{F} , the size of \mathcal{W} is equal to the rank $(H_{\mathcal{S}})$ and is of minimum total weight with respect to the weight function w'. That is, \mathcal{W} is a minimum weight column basis of $H_{\mathcal{S}}$. Since the row-rank of a matrix is equal to the column-rank, we have that $|\mathcal{W}| = \operatorname{rank}(H_{\mathcal{S}}) \leq \binom{k}{p}$. We define $\widehat{\mathcal{S}} = \{S_\alpha \mid \vec{s}_\alpha \in \mathcal{W}\}$. Let $|\widehat{\mathcal{S}}| = \ell$. Because $|\mathcal{W}| = |\widehat{\mathcal{S}}|$, we have that $\ell \leq \binom{k}{p}$. Without loss of generality, let $\widehat{\mathcal{S}} = \{S_i \mid 1 \leq i \leq \ell\}$ (else we can rename these sets) and $\mathcal{W} = \{\vec{s}_1, \ldots, \vec{s}_\ell\}$. The only thing that remains to show is that indeed $\widehat{\mathcal{S}} \subseteq_{minrep}^q \mathcal{S}$.

Let $S_{\beta} \in \mathcal{S}$ be such that $S_{\beta} \notin \widehat{\mathcal{S}}$. We show that if there is a set $Y \subseteq E$ of size at most q such that $S_{\beta} \cap Y = \emptyset$ and $S_{\beta} \cup Y \in \mathcal{I}$, then there exists a set $\widehat{S}_{\beta} \in \widehat{\mathcal{S}}$ disjoint from Y with $\widehat{S}_{\beta} \cup Y \in \mathcal{I}$ and $w(\widehat{S}_{\beta}) \leq w(S_{\beta})$. Let us first consider the case |Y| = q. Since $S_{\beta} \cap Y = \emptyset$, it follows that $|S_{\beta} \cup Y| = p + q = k$. Furthermore, since $S_{\beta} \cup Y \in \mathcal{I}$, we have that the columns corresponding to $S_{\beta} \cup Y$ in A_M are linearly independent over \mathbb{F} ; that is, $\det(A_M[\mathbf{R}(A_M), S_{\beta} \cup Y]) \neq 0$.

Recall that, $\vec{s}_{\beta} = (s_{\beta}[I])_{I \in {\binom{[k]}{p}}}$, where $s_{\beta}[I] = \det(A_M[I, S_{\beta}])$. Similarly we define $y[L] = \det(A_M[L, Y])$ and

$$\vec{y} = (y[L])_{L \in \binom{[k]}{2}}$$

Let $\sum J = \sum_{i \in S_{\beta}} j$. Define

$$\gamma(\vec{s}_{\beta}, \vec{y}) = \sum_{I \in \binom{[k]}{p}} (-1)^{\sum I + \sum J} s_{\beta}[I] \cdot y[\bar{I}].$$

Since $\binom{k}{p} = \binom{k}{k-p} = \binom{k}{q}$ the above formula is well defined. Observe that by Proposition 3.1, we have that $\gamma(\vec{s}_{\beta}, \vec{y}) = \det(A_M[\mathbf{R}(A_M), S_{\beta} \cup Y]) \neq 0$. We also know that \vec{s}_{β} can be written as a linear combination of vectors in $\mathcal{W} = \{\vec{s}_1, \vec{s}_2, \dots, \vec{s}_\ell\}$. That is, $\vec{s}_{\beta} = \sum_{i=1}^{\ell} \lambda_i \vec{s}_i, \lambda_i \in \mathbb{F}$, and for some $i, \lambda_i \neq 0$. Thus,

$$\begin{aligned} \gamma(\vec{s}_{\beta}, \vec{y}) &= \sum_{I} (-1)^{\sum I + \sum J} s_{\beta}[I] \cdot y[\bar{I}] \\ &= \sum_{I} (-1)^{\sum I + \sum J} \left(\sum_{i=1}^{\ell} \lambda_{i} s_{i}[I] \right) y[\bar{I}] \\ &= \sum_{i=1}^{\ell} \lambda_{i} \left(\sum_{I} (-1)^{\sum I + \sum J} s_{i}[I] y[\bar{I}] \right) \\ &= \sum_{i=1}^{\ell} \lambda_{i} \det(A_{M}[\mathbf{R}(A_{M}), S_{i} \cup Y]) \quad \text{(by Proposition 3.1)} \end{aligned}$$

Define

$$\sup(S_{\beta}) = \left\{ S_i \mid S_i \in \widehat{\mathcal{S}}, \ \lambda_i \det(A_M[\mathbf{R}(A_M), S_i \cup Y])) \neq 0 \right\}.$$

Since $\gamma(\vec{s}_{\beta}, \vec{y}) \neq 0$, we have that $(\sum_{i=1}^{\ell} \lambda_i \det(A_M[\mathbf{R}(A_M), S_i \cup Y])) \neq 0$ and thus $\sup(S_{\beta}) \neq \emptyset$. Observe that for all $S \in \sup(S_{\beta})$ we have that $\det(A_M[\mathbf{R}(A_M), S \cup Y]) \neq 0$ and thus $S \cup Y \in \mathcal{I}$. We now show that $w(S) \leq w(S_{\beta})$ for all $S \in \sup(S_{\beta})$.

Claim 3.1. For all $S \in \sup(S_{\beta}), w(S) \leq w(S_{\beta})$.

Proof. For a contradiction assume that there exists a set $S_j \in \sup(S_\beta)$ such that $w(S_j) > w(S_\beta)$. Let $\vec{s_j}$ be the vector corresponding to S_j and $\mathcal{W}' = (\mathcal{W} \cup \{\vec{s_j}\}) \setminus \{\vec{s_\beta}\}$. Since $w(S_j) > w(S_\beta)$, we have that $w(\vec{s_j}) > w(\vec{s_\beta})$ and thus $w'(\mathcal{W}) > w'(\mathcal{W}')$. Now we show that \mathcal{W}' is also a column basis of H_S . This will contradict our assumption that \mathcal{W} is a minimum weight column basis of H_S . Recall that $\vec{s_\beta} = \sum_{i=1}^{\ell} \lambda_i \vec{s_i}, \lambda_i \in \mathbb{F}$. Since $S_j \in \sup(S_\beta)$, we have that $\lambda_j \neq 0$. Thus $\vec{s_j}$ can be written as linear combination of vectors in \mathcal{W}' . That is,

$$\vec{s}_j = \lambda_\beta \vec{s}_\beta + \sum_{i=1, i \neq j}^{\ell} \lambda'_i \vec{s}_i.$$
(1)

Also every vector $\vec{s}_{\gamma} \notin \mathcal{W}$ can be written as a linear combination of vectors in \mathcal{W}

$$\vec{s}_{\gamma} = \sum_{i=1}^{\ell} \delta_i \vec{s}_i, \quad \delta_i \in \mathbb{F}.$$
 (2)

By substituting (1) into (2), we conclude that every vector can be written as linear combination of vectors in \mathcal{W}' . This shows that \mathcal{W}' is also a column basis of $H_{\mathcal{S}}$, a contradiction proving the claim.

Claim 3.1 and the discussions preceding above it show that we could take any set $S \in \sup(S_{\beta})$ as the desired $\widehat{S}_{\beta} \in \widehat{S}$. Also, since det $(A_M[\mathbf{R}(A_M), S \cup Y]) \neq 0$, we have that $S \cap Y = \emptyset$. This shows that indeed $\widehat{S} \subseteq_{minrep}^q S$ for each Y of size q. This completes the proof for the case |Y| = q.

Suppose that |Y| = q' < q. Since M is a matroid of rank k = p + q, there exists a superset $Y' \in \mathcal{I}$ of Y of size q such that $S_{\beta} \cap Y' = \emptyset$ and $S_{\beta} \cup Y' \in \mathcal{I}$. This implies that there exists

a set $\widehat{S} \in \widehat{S}$ such that $\det(A_M[\mathbf{R}(A_M), \widehat{S} \cup Y']) \neq 0$ and $w(\widehat{S}) \leq w(S)$. Thus the columns corresponding to $\widehat{S} \cup Y$ are linearly independent.

We now consider the running time of the algorithm. To make the above proof algorithmic we need to

- (a) compute determinants and
- (b) apply fast Gaussian elimination to find a minimum weight column basis.

It is well known that one can compute the determinant of a $n \times n$ matrix in time $\mathcal{O}(n^{\omega})$ [11]. For a rectangular matrix A of size $d \times n$ (with $d \leq n$), Bodlaender et al. [8] outline an algorithm computing a minimum weight column basis in time $\mathcal{O}(nd^{\omega-1})$. Thus given a p-family of independent sets S we can construct the matrix H_S as follows. For every set S_i , we first compute \vec{s}_i . To do this we compute $\det(A_M[I, S_i])$ for every $I \in \binom{[k]}{p}$. This can be done in time $\mathcal{O}(\binom{p+q}{p}p^{\omega})$. Thus, we can obtain the matrix H_S in time $\mathcal{O}(\binom{p+q}{p}tp^{\omega})$. Given matrix H_S we can find a minimum weight column basis \mathcal{W} of H_S in time $\mathcal{O}(\binom{p+q}{p}tp^{\omega-1})$. Given \mathcal{W} , we can easily recover \hat{S} . Thus, we can compute $\hat{S} \subseteq_{minrep}^q S$ in $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega}+t\binom{p+q}{q}^{\omega-1}\right)$ field operations. This concludes the proof for finding $\hat{S} \subseteq_{minrep}^q S$. To find $\hat{S} \subseteq_{maxrep}^q S$, the only change we need to do in the algorithm for finding $\hat{S} \subseteq_{minrep}^q S$ is to find a maximum weight column basis \mathcal{W} of H_S . This concludes the proof.

In Theorem 3 we assumed that $\operatorname{rank}(M) = p + q$. However, one can obtain a similar result even when $\operatorname{rank}(M) > p + q$ in lieu of randomness. To do this we first need to compute the representation matrix of a k-restriction of $M = (E, \mathcal{I})$. For that we make use of Proposition 2.4. This step returns a representation of a k-restriction of $M = (E, \mathcal{I})$ with high probability. Given this matrix, we apply Theorem 3 and arrive at the following result.

Theorem 4. Let $M = (E, \mathcal{I})$ be a linear matroid, $S = \{S_1, \ldots, S_t\}$ be a p-family of independent sets and $w : S \to \mathbb{N}$ be a non-negative weight function. Then there exists $\widehat{S} \subseteq_{minrep}^q S$ $(\widehat{S} \subseteq_{maxrep}^q S)$ of size $\binom{p+q}{p}$. Furthermore, given a representation A_M of M over a field \mathbb{F} , there is a randomized algorithm computing $\widehat{S} \subseteq_{minrep}^q S$ $(\widehat{S} \subseteq_{maxrep}^q S)$ of size at most $\binom{p+q}{p}$ in $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega}+t\binom{p+q}{q}^{\omega-1}\right)$ operations over \mathbb{F} .

4 Fast Computation for Representative Sets for Uniform Matroids

In this section we show that for uniform matroids one can avoid matrix multiplication computations in order to compute representative families. The section is organized as follows. We start (Section 4.1, Theorem 5) from a relatively simple algorithm computating representative families over a uniform matroid. This algorithm is already faster than the algorithm of Theorem 1 for general matroids. In Section 4.2, Theorem 6, we give an even faster, but more complicated algorithm. Throughout this section a subfamily $\mathcal{A}' \subseteq \mathcal{A}$ of the family \mathcal{A} is said to *q*-represent \mathcal{A} if for every set B of size q such that there is an $A \in \mathcal{A}$ and $A \cap B = \emptyset$, there is a set $A' \in \mathcal{A}'$ such that $A' \cap B = \emptyset$.

4.1 Representative Sets using Lopsided Universal Sets

Our aim in this subsection is to prove the following theorem.

Theorem 5. There is an algorithm that given a family \mathcal{A} of *p*-sets over a universe *U* of size n and an integer q, computes in time $|\mathcal{A}| \cdot {\binom{p+q}{p}} \cdot 2^{o(p+q)} \cdot \log n$ a subfamily $\mathcal{A}' \subseteq A$ such that $|\mathcal{A}'| \leq {\binom{p+q}{p}} \cdot 2^{o(p+q)} \cdot \log n$ and \mathcal{A}' q-represents \mathcal{A} .

The main tool in our proof of Theorem 5 is a generalization of the notion of *n-k-universal* families. A family \mathcal{F} of sets over a universe U is an *n-k-universal* family if for every set $A \in \binom{U}{k}$ and every subset $A' \subseteq A$ there is some set $F \in \mathcal{F}$ whose intersection $F \cap A$ is exactly A'. Naor et al. [47] show that given n and k one can construct an *n-k*-universal family \mathcal{F} of size $2^{k+o(k)} \cdot \log n$ in time $2^{k+o(k)} \cdot n \log n$.

We tweak the notion of universal families as follows. We will say that a family \mathcal{F} of sets over a universe U of size n is an n-p-q-lopsided-universal family if for every $A \in \binom{U}{p}$ and $B \in \binom{U\setminus A}{q}$ there is an $F \in \mathcal{F}$ such that $A \subseteq F$ and $B \cap F = \emptyset$. An alternative definition that is easily seen to be equivalent is that \mathcal{F} is n-p-q-lopsided-universal if for every subset $A \in \binom{U}{p+q}$ and every subset $A' \in \binom{A}{p}$, there is an $F \in \mathcal{F}$ such that $F \cap A = A'$. From the second definition it follows that a n-(p+q)-universal family is also n-p-q-lopsided-universal. Thus the construction of Naor et al. [47] of universal set families also gives an construction of n-p-q-lopsided universal family of size $2^{p+q+o(p+q)} \cdot \log n$, running in time $2^{p+q+o(p+q)} \cdot n \log n$. It turns out that by slightly changing the construction of Naor et al. [47], one can prove the following result.

Lemma 4.1. There is an algorithm that given n, p and q constructs an n-p-q-lopsided-universal family \mathcal{F} of size $\binom{p+q}{p} \cdot 2^{o(p+q)} \cdot \log n$ in time $\mathcal{O}(\binom{p+q}{p} \cdot 2^{o(p+q)} \cdot n \log n)$.

We do not give a stand-alone proof of Lemma 4.1, however Lemma 4.1 is a direct corollary of Lemma 4.2 proved in Section 4.2. We will now show how to use the lemma to prove Theorem 5.

Proof of Theorem 5. The algorithm starts by constructing an *n*-*p*-*q*-lopsided universal family \mathcal{F} as guaranteed by Lemma 4.1. If $|\mathcal{A}| \leq |\mathcal{F}|$ the algorithm outputs \mathcal{A} and halts. Otherwise it builds the set \mathcal{A}' as follows. Initially \mathcal{A}' is equal to \emptyset and all sets in \mathcal{F} are marked as unused. The algorithm goes through every $A \in \mathcal{A}$ and unused sets $F \in \mathcal{F}$. If an unused set $F \in \mathcal{F}$ is found such that $A \subseteq F$, the algorithm marks F as used, inserts A into \mathcal{A}' and proceeds to the next set in \mathcal{A} . If no such set F is found the algorithm proceeds to the next set in \mathcal{A} without inserting A into \mathcal{A}' .

The size of \mathcal{A}' is upper bounded by $|\mathcal{F}| \leq {p+q \choose p} \cdot 2^{o(p+q)} \cdot \log n$ since every time a set is added to \mathcal{A}' an unused set in \mathcal{F} is marked as used. For the running time analysis, constructing \mathcal{F} takes time ${p+q \choose p} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot n \log n$. Then we run through all of \mathcal{F} for each set $A \in \mathcal{A}$, spending time $|\mathcal{A}| \cdot |\mathcal{F}| \cdot (p+q)^{\mathcal{O}(1)}$, which is at most $|\mathcal{A}| \cdot {p+q \choose p} \cdot 2^{o(p+q)} \cdot \log n$. Thus in total the running time is bounded by $|\mathcal{A}| \cdot {p+q \choose p} \cdot 2^{o(p+q)} \cdot \log n$.

Finally we need to argue that \mathcal{A}' q-represents \mathcal{A} . Consider any set $A \in \mathcal{A}$ and B such that |B| = q and $A \cap B = \emptyset$. If $A \in \mathcal{A}'$ we are done, so assume that $A \notin \mathcal{A}'$. Since \mathcal{F} is *n*-*p*-*q*-lopsided universal there is a set $F \in \mathcal{F}$ such that $A \subseteq F$ and $F \cap B = \emptyset$. Since $A \notin \mathcal{A}'$ we know that F was already marked as used when A was considered by the algorithm. When the algorithm marked F as used it also inserted a set A' into \mathcal{A}' . For the insertion to be made, F must satisfy $A' \subseteq F$. But then $A' \cap B = \emptyset$, completing the proof.

One of the factors that drive up the running time of the algorithm in Theorem 5 is that one needs to consider all of \mathcal{F} for each set $A \in \mathcal{A}$. Doing some computations it is possible to convince oneself that in an *n*-*p*-*q*-lopsided universal family \mathcal{F} the number of sets $F \in \mathcal{F}$ containing a fixed set A of size p should be approximately $|\mathcal{F}| \cdot \left(\frac{p}{p+q}\right)^p$. Thus, if we could only make sure that this estimation is in fact correct for every $A \in \mathcal{A}$, and we could make sure that for a given $A \in \mathcal{A}$ we can list all of the sets in \mathcal{F} that contain A without having to go through the sets that don't, then we could speed up our algorithm by a factor $\left(\frac{p+q}{p}\right)^p$. This is exactly the strategy behind the main theorem of Section 4.2.

4.2 Representative Sets using Separating Collections

In this section we design a faster algorithm to find q-representative family. Our main technical tool is a construction of n-p-q-separating collection. We start with the formal definition of n-p-q-separating collection.

Definition 4.1. An n-p-q-separating collection C is a tuple $(\mathcal{F}, \chi, \chi')$, where \mathcal{F} is a family of sets over a universe U of size n, χ is a function from $\bigcup_{p' \leq p} {U \choose p'}$ to $2^{\mathcal{F}}$ and χ' is a function from $\bigcup_{q' \leq q} {U \choose q'}$ to $2^{\mathcal{F}}$ such that the following properties are satisfied

- 1. for every $A \in \bigcup_{p' \leq p} {U \choose p'}$ and $F \in \chi(A), A \subseteq F$,
- 2. for every $B \in \bigcup_{q' \leq q} {U \choose q'}$ and $F \in \chi'(B), F \cap B = \emptyset$,
- 3. for every pairwise disjoint sets $A_1 \in \binom{U}{p_1}, A_2 \in \binom{U}{p_2}, \cdots, A_r \in \binom{U}{p_r}$ and $B \in \binom{U}{q}$ such that $p_1 + \cdots + p_r = p, \ \exists F \in \chi(A_1) \cap \chi(A_2) \dots \chi(A_r) \cap \chi'(B).$

The size of $(\mathcal{F}, \chi, \chi')$ is $|\mathcal{F}|$, the (χ, p') -degree of $(\mathcal{F}, \chi, \chi')$ for $p' \leq p$ is

$$\max_{A \in \binom{U}{p'}} |\chi(A)|$$

and the (χ',q') -degree of (\mathcal{F},χ,χ') for $q' \leq q$ is

$$\max_{B \in \binom{U}{q'}} |\chi'(B)|.$$

We must remark that the definition of an n-p-q-separating collection in the preliminary version of this paper [24] was slightly more restricted than the one given here. This new definition has already been used recently to obtain faster algorithms for computing representative sets for product families [22].

A construction of separating collections is a data structure, that given n, p and q initializes and outputs a family \mathcal{F} of sets over the universe U of size n. After the initialization one can query the data structure by giving it a set $A \in \bigcup_{p' \leq p} {U \choose p'}$ or $B \in \bigcup_{q' \leq q} {U \choose q'}$, the data structure then outputs a family $\chi(A) \subseteq 2^{\mathcal{F}}$ or $\chi'(B) \subseteq 2^{\mathcal{F}}$ respectively. Together the tuple $\mathcal{C} = (\mathcal{F}, \chi, \chi')$ computed by the data structure should form a *n-p-q-separating collection*.

We call the time the data structure takes to initialize and output \mathcal{F} the *initialization time*. The (χ, p') -query time, $p' \leq p$, of the data structure is the maximum time the data structure uses to compute $\chi(A)$ over all $A \in \binom{U}{p'}$. Similarly, the (χ', q') -query time, $q' \leq q$, of the data structure is the maximum time the data structure uses to compute $\chi'(B)$ over all $B \in \binom{U}{q'}$. The initialization time of the data structure and the size of \mathcal{C} are functions of n, p and q. The initialization time is denoted by $\tau_I(n, p, q)$, size of \mathcal{C} is denoted by $\zeta(n, p, q)$. The (χ, p') -query time and (χ, p') -degree of $\mathcal{C}, p' \leq p$, are functions of n, p', p, q and is denoted by $Q_{(\chi, p')}(n, p, q)$ and $\Delta_{(\chi, p')}(n, p, q)$ respectively. Similarly, the (χ', q') -query time and (χ', q') -degree of $\mathcal{C}, q' \leq q$, are functions of n, q', p, q and are denoted by $Q_{(\chi', q')}(n, p, q)$ and $\Delta_{(\chi', q')}(n, p, q)$ respectively. We are now ready to state the main technical tool of this subsection. **Lemma 4.2.** Given 0 < x < 1, there is a construction of n-p-q- separating collection with the following parameters

- size, $\zeta(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$
- initialization time, $\tau_I(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot n \log n$
- (χ, p') -degree, $\Delta_{(\chi, p')}(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$
- (χ, p') -query time, $Q_{(\chi, p')}(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$
- (χ',q') -degree, $\Delta_{(\chi',q')}(n,p,q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$
- (χ',q') -query time, $Q_{(\chi',q')}(n,p,q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$

We first give the road map that we take to prove Lemma 4.2. The proof of Lemma 4.2 uses three auxiliary lemmata.

- (a.) Existential Proof (Lemma 4.3). This lemma shows that there is indeed a n-p-q-separating collection with the required sizes, degrees and query time. Essentially, it shows that if we form a family $\mathcal{F} = \{F_1, \ldots, F_t\}$ of sets of U such that each F_i is a random subset of U where each element is inserted into F_i with probability x, then \mathcal{F} has the desired sizes, degrees and query time. Thus, this also gives a brute force algorithm to design the family \mathcal{F} by just guessing the family of desired size and then checking whether it is indeed a n-p-q-separating collection.
- (b.) Universe Reduction (Lemma 4.4). The construction obtained in Lemma 4.3 has only one drawback that the initialization time is much larger than claimed in Lemma 4.2. To overcome this lacuna, we do not apply the construction in Lemma 4.3 directly. We first prove a Lemma 4.4 which helps us in reducing the universe size to $(p+q)^2$. This is done using the known construction of k-perfect hash families of size $(p+q)^{\mathcal{O}(1)} \log n$. However, Lemma 4.4 alone can not reduce the universe size sufficiently, that we can apply the construction of Lemma 4.3.
- (c.) Splitting Lemma (Lemma 4.5). We give a splitter type construction in Lemma 4.5 that when applied with Lemma 4.4 makes the universe and other parameters small enough that we can apply the construction given in Lemma 4.3. In this construction we consider all the "consecutive partitions" of the universe into t parts, assume that the sets $A \cup B$, $A = \bigcup_{i=1}^{r} A_i$, are distributed uniformly into t parts and then use this information to obtain a construction of separating collections in each part and then take the product of these collections to obtain a collection for the original instance.

We start with the existential proof.

Lemma 4.3. Given 0 < x < 1, there is a construction of n-p-q-separating collections with

- size $\zeta(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p}(1-x)^{q}} \cdot (p^{2}+q^{2}+1)\log n\right)$
- initialization time $\tau_I(n, p, q) = \mathcal{O}(\binom{2^n}{\zeta(n, p, q)} \cdot \frac{1}{x^p(1-x)^q} \cdot n^{\mathcal{O}(p+q)})$
- (χ, p') -degree for $p' \le p$, $\Delta_{(\chi, p')}(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p-p'}} \cdot \frac{(p^2+q^2+1)}{(1-x)^q} \cdot \log n\right)$
- (χ, p') -query time $Q_{(\chi, p')}(n, p, q) = \mathcal{O}(\frac{1}{x^p(1-x)^q} \cdot n^{\mathcal{O}(1)})$
- (χ',q') -degree $\Delta_{(\chi',q')}(n,p,q) = \mathcal{O}\left(\frac{1}{x^p(1-x)^{q-q'}}\cdot(p^2+q^2+1)\cdot\log n\right)$

• (χ',q') -query time $Q_{(\chi',q')}(n,p,q) = \mathcal{O}(\frac{1}{x^p(1-x)^q} \cdot n^{\mathcal{O}(1)})$

Proof. We start by giving a randomized algorithm that with positive probability constructs a n-p-q-separating collection $\mathcal{C} = (\mathcal{F}, \chi, \chi')$ with the desired size and degree parameters. We will then discuss how to deterministically compute such a \mathcal{C} within the required time bound. Set $t = \frac{1}{x^p(1-x)^q} \cdot (p^2 + q^2 + 1) \log n$ and construct the family $\mathcal{F} = \{F_1, \ldots, F_t\}$ as follows. Each set F_i is a random subset of U, where each element of U is inserted into F_i with probability x. Distinct elements are inserted (or not) into F_i independently, and the construction of the different sets in \mathcal{F} is also independent. For each $A \in \bigcup_{p' \leq p} {U \choose p'}$ we set $\chi(A) = \{F \in \mathcal{F} : A \subseteq F\}$ and for each $B \in \bigcup_{q' \leq q} {U \choose q'}$ we set $\chi'(B) = \{F \in \mathcal{F} : F \cap B = \emptyset\}$.

The size of \mathcal{F} is within the required bound by construction. We now argue that with positive probability $(\mathcal{F}, \chi, \chi')$ is indeed a *n*-*p*-*q*-separating collection, and that the degrees of \mathcal{C} is within the required bounds as well. For fixed sets $A \in \binom{U}{p}$, $B \in \binom{U \setminus A}{q}$, and integer $i \leq t$, we consider the probability that $A \subseteq F_i$ and $B \cap F_i = \emptyset$. This probability is $x^p(1-x)^q$. Since each F_i is constructed independently from the other sets in \mathcal{F} , the probability that no F_i satisfies $A \subseteq F_i$ and $B \cap F_i = \emptyset$ is

$$(1 - x^p (1 - x)^q)^t \le e^{-(p^2 + q^2 + 1)\log n} = \frac{1}{n^{p^2 + q^2 + 1}}$$

For a fixed A_1, \ldots, A_r and B (choices in condition 3), the probability that no F_i in $\chi(A_1) \cap \chi(A_2) \cap \cdots \cap \chi(A_r) \cap \chi'(B)$ is equal to the probability that no F_i is in $\chi(A_1 \cup A_2 \cdots \cup A_r) \cap \chi'(B)$ (since $\chi(A')$ contains all the sets in \mathcal{F} that contains A' and $\chi'(B)$ contains all the sets in \mathcal{F} that are disjoint from B). Hence the probability that condition 3 fails is upper bounded by

$$Y \cdot \frac{1}{n^{p^2 + q^2 + 1}}$$

where Y is the number of choices for A_1, \ldots, A_r and B in condition 3. We upper bound Y as follows. There are $\binom{n}{p}$ choices for $A_1 \cup \cdots \cup A_r$ and $\binom{n}{q}$ choices for B. For each choice of $A_1 \cup \cdots \cup A_r$ there are at most r^p choices of making A_1, \ldots, A_r with some of them being empty as well. Note that $r \leq p$. Therefore the number of possible choices of sets A_1, A_2, \ldots, A_r and B in condition 3 is upper bounded by $\binom{n}{p}\binom{n}{q}p^p \leq n^{2p+q} \leq n^{p^2+q^2}$. Hence the probability that condition 3 in Definition 4.1 fails is at most $\frac{1}{n}$.

We also need to upper bound the maximum degree of \mathcal{C} . For every $A \in \binom{U}{p'}$, $|\chi(A)|$ is a random variable. For a fixed $A \in \binom{U}{p'}$ and $i \leq t$ the probability that $A \subseteq F_i$ is exactly $x^{p'}$. Hence $|\chi(A)|$ is the sum of t independent 0/1-random variables that each take value 1 with probability $x^{p'}$. Hence the expected value of $|\chi(A)|$ is

$$E[|\chi(A)|] = t \cdot x^{p'} = \frac{1}{x^{p-p'}(1-x)^q} \cdot (p^2 + q^2 + 1)\log n$$

For every $B \in \binom{U}{q'}$, $|\chi'(B)|$ is also a random variable. For a fixed $B \in \binom{U}{q'}$ and $i \leq t$ the probability that $A \cap F_i = \emptyset$ is exactly $(1-x)^{q'}$. Hence the expected value of $|\chi'(B)|$ is,

$$E[|\chi'(B)|] = t \cdot (1-x)^{q'} = \frac{1}{x^p(1-x)^{q-q'}} \cdot (p^2 + q^2 + 1)\log n$$

Standard Chernoff bounds [43, Theorem 4.4] show that the probability that for any $A \in \binom{U}{p'}$, $|\chi(A)|$ is at least $6E[|\chi(A)|]$ is upper bounded by $2^{-6E[|\chi(A)|]} \leq \frac{1}{n^{p^2+q^2+1}}$. Similarly the probability that for any $B \in \binom{U}{q'}$, $|\chi'(B)|$ is at least $6E[|\chi'(B)|]$ is upper bounded by $2^{-6E[|\chi'(B)|]} \leq 2^{-6E[|\chi'(B)|]}$.

 $\frac{1}{n^{p^2+q^2+1}}.$ There are $\sum_{p' \leq p} {n \choose p'} \leq n^{p^2}$ choices for $A \in \bigcup_{p' \leq p} {U \choose p'}$ and $\sum_{q' \leq q} {n \choose q'} \leq n^{q^2}$ choices for $B \in \bigcup_{q' \leq q} {U \choose q'}$. Hence the union bound yields that the probability that there exists an $A \in \bigcup_{p' \leq p} {U \choose p'}$ such that $|\chi(A)| > 6E[|\chi(A)|]$ or there exists $B \in \bigcup_{q' \leq q} {U \choose q'}$ such that $|\chi'(B)| > 6E[|\chi'(B)|]$ is upper bounded by $\frac{1}{n}$. Thus \mathcal{C} is a family of *n*-*p*-*q*-separating collections with the desired size and degree parameters with probability at least $1 - \frac{2}{n} > 0$. The degenerate case that $1 - \frac{2}{n} \leq 0$ is handled by the family \mathcal{F} containing all (at most four) subsets of U.

To construct \mathcal{F} within the stated initialization time bound, it is sufficient to try all families \mathcal{F} of size t and for each of the $\binom{2^n}{\zeta(n,p,q)}$ guesses, test whether it is indeed a family of n-p-q-separating collections in time $\mathcal{O}(t \cdot n^{\mathcal{O}(p+q)}) = \mathcal{O}(\frac{1}{x^p(1-x)^q} \cdot n^{\mathcal{O}(p+q)})$.

For the queries, we need to give an algorithm that given A, computes $\chi(A)$ (or $\chi'(A)$), under the assumption that \mathcal{F} has already has been computed in the initialization step. This is easily done within the stated running time bound by going through every set $F \in \mathcal{F}$, checking whether $A \subseteq F$ (or $A \cap F = \emptyset$), and if so, inserting F into $\chi(A)$ ($\chi'(A)$). This concludes the proof. \Box

We will now work towards improving the time bounds of Lemma 4.3. To that end we will need a construction of k-perfect hash functions by Alon et al. [2]

Definition 4.2. A family of functions f_1, \ldots, f_t from a universe U of size n to a universe of size r is a k-perfect family of hash functions if for every set $S \subseteq U$ such that |S| = k there exists an i such that the restriction of f_i to S is injective.

Alon et al. [2] give very efficient constructions of k-perfect families of hash functions from a universe of size n to a universe of size k^2 .

Proposition 4.1 ([2]). For any universe U of size n there is a k-perfect family f_1, \ldots, f_t of hash functions from U to $[k^2]$ with $t = \mathcal{O}(k^{\mathcal{O}(1)} \cdot \log n)$. Such a family of hash functions can be constructed in time $\mathcal{O}(k^{\mathcal{O}(1)} n \log n)$.

Lemma 4.4. If there is a construction of n-p-q-separating collections $(\hat{\mathcal{F}}, \hat{\chi}, \hat{\chi}')$ with initialization time $\tau_I(n, p, q)$, size $\zeta(n, p, q)$, $(\hat{\chi}, p')$ -query time $Q_{(\hat{\chi}, p')}(n, p, q)$, $(\hat{\chi}', q')$ -query time $Q_{(\hat{\chi}', q')}(n, p, q)$, $(\hat{\chi}, p')$ -degree $\Delta_{(\hat{\chi}, p')}(n, p, q)$, and $(\hat{\chi}', q')$ -degree $\Delta_{(\hat{\chi}', q')}(n, p, q)$ then there is a construction of n-p-q-separating collections with following parameters.

- $\zeta'(n, p, q) \leq \zeta \left((p+q)^2, p, q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n,$
- $\tau'_I(n, p, q) = \mathcal{O}\left(\tau_I\left((p+q)^2, p, q\right) + \zeta\left((p+q)^2, p, q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot n \log n\right),$
- $\Delta'_{(\chi,p')}(n,p,q) \leq \Delta_{(\hat{\chi},p')}\left((p+q)^2,p,q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n,$

•
$$Q'_{(\chi,p')}(n,p,q) = \mathcal{O}\left(\left(Q_{(\hat{\chi},p')}\left((p+q)^2, p, q\right) + \Delta_{(\hat{\chi},p')}\left((p+q)^2, p, q\right)\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right)$$

•
$$\Delta'_{(\chi',q')}(n,p,q) \le \Delta_{(\hat{\chi}',q')}((p+q)^2,p,q) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n,$$

•
$$Q'_{(\chi',q')}(n,p,q) = \mathcal{O}\left(\left(Q_{(\hat{\chi}',q')}\left((p+q)^2, p, q\right) + \Delta_{(\hat{\chi}',q')}\left((p+q)^2, p, q\right)\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right)$$

Proof. We give a construction of *n*-*p*-*q*-separating collections with initialization time, query time, size and degree τ'_I , Q', ζ' and Δ' respectively using the construction with initialization time, query time, size and degree τ_I , Q, ζ and Δ as a black box.

We first describe the initialization of the data structure. Given n, p, and q, we construct using Proposition 4.1 a (p+q)-perfect family $f_1, \ldots f_t$ of hash functions from the universe U to $[(p+q)^2]$. The construction takes time $\mathcal{O}((p+q)^{\mathcal{O}(1)}n\log n)$ and $t \leq (p+q)^{\mathcal{O}(1)} \cdot \log n$. We will store these hash functions in memory. We use the following notations.

- For a set $S \subseteq U$ and $T \subseteq [(p+q)^2]$, $f_i(S) = \{f_i(s) : s \in S\}$ and $f_i^{-1}(T) = \{s \in U : f(s) \in T\}$.
- For a family \mathcal{Z} of sets over U and family \mathcal{W} of sets over $[(p+q)^2]$, $f_i(\mathcal{Z}) = \{f_i(S) : S \in \mathcal{Z}\} \text{ and } f_i^{-1}(\mathcal{W}) = \{f_i^{-1}(T) : T \in \mathcal{W}\}.$

We first use the given black box construction for $(p+q)^2$ -p-q-separating collections $(\hat{\mathcal{F}}, \hat{\chi}, \hat{\chi}')$ over the universe $[(p+q)^2]$. We run the initialization algorithm of this construction and store the family $\hat{\mathcal{F}}$ in memory. We then set

$$\mathcal{F} = \bigcup_{i \le t} f_i^{-1}(\hat{\mathcal{F}}).$$

We spent $\mathcal{O}((p+q)^{\mathcal{O}(1)}n\log n)$ time to construct a (p+q)-perfect family of hash functions, $\mathcal{O}(\tau_I((p+q)^2, p, q))$ to construct $\hat{\mathcal{F}}$ of size $\zeta((p+q)^2, p, q)$, and $\mathcal{O}(\zeta((p+q)^2, p, q) \cdot (p+q)^{\mathcal{O}(1)} \cdot (p+q)^2)$ $n\log n$ time to construct \mathcal{F} from $\hat{\mathcal{F}}$ and the family of perfect hash functions. Thus the upper bound on $\tau'_I(n, p, q)$ follows. Furthermore, $|\mathcal{F}| \leq |\hat{\mathcal{F}}| \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$, yielding the claimed bound for ζ' .

We now define $\chi(A)$ for every $A \in \bigcup_{p' \leq p} {U \choose p'}$ and describe the query algorithm. For every $A \in \bigcup_{p' < p} {U \choose p'}$ we let

$$\chi(A) = \bigcup_{\substack{i \le t \\ |f_i(A)| = |A|}} f_i^{-1}(\hat{\chi}(f_i(A))).$$

Since for every $\hat{F} \in \hat{\chi}(f_i(A)), f_i(A) \subseteq \hat{F}$, it follows that $A \subseteq F$ for every $F \in \chi(A)$. Furthermore we can bound $|\chi(A)|$ for any $A \in \bigcup_{p' \leq p} {U \choose p'}$, as follows

$$|\chi(A)| \le \sum_{\substack{i \le t \\ |f_i(A)| = |A|}} |\hat{\chi}(f_i(A))| \le \Delta_{(\hat{\chi}, p')}((p+q)^2, p, q) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$$

Thus the claimed bound for $\Delta'_{(\chi,p')}$ follows. Similarly, way can define $\chi'(B)$ for every $B \in$ $\bigcup_{q' < q} {U \choose q'}$ as

$$\chi'(B) = \bigcup_{\substack{i \le t \\ |f_i(A)| = |A|}} f_i^{-1}(\hat{\chi}'(f_i(A))).$$

$$|\chi'(B)| \le \sum_{\substack{i \le t \\ |f_i(A)| = |A|}} |\hat{\chi}'(f_i(A))| \le \Delta_{(\hat{\chi}',q')}((p+q)^2, p, q) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$$

To compute $\chi(A)$ for any $A \in \bigcup_{p' < p} {U \choose p'}$, we go over every $i \leq t$ and check whether f_i is injective on A. This takes time $\mathcal{O}((p+q)^{\mathcal{O}(1)} \cdot \log n)$. For each *i* such that f_i is injective on A, we compute $f_i(A)$ and then $\hat{\chi}(f_i(A))$ in time $\mathcal{O}(Q_{(\hat{\chi},p')}((p+q)^2,p,q))$. Then we compute $f_i^{-1}(\hat{\chi}(f_i(A)))$ in time $\mathcal{O}(|\hat{\chi}(f_i(A))| \cdot (p+q)^{\mathcal{O}(1)}) = \mathcal{O}(\Delta_{(\hat{\chi},p')}((p+q)^2, p, q) \cdot (p+q)^{\mathcal{O}(1)})$ and add this set to $\chi(A)$. As we need to do this $\mathcal{O}((p+q)^{\mathcal{O}(1)} \cdot \log n)$ times, the total time to compute $\chi(A)$ is upper bounded by $\mathcal{O}((Q_{(\hat{\chi},p')}((p+q)^2,p,q) + \Delta_{(\hat{\chi},p')}((p+q)^2,p,q)) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n)$, yielding the claimed upper bound on $Q'_{(\chi,p')}$. Similar way we can bound $Q'_{(\chi',q')}$. It remains to argue that $(\mathcal{F}, \chi, \chi')$ is in fact a *n*-*p*-*q*-separating collection. For any *r*, consider pairwise disjoint sets $A_1 \in {U \choose p_1}, \ldots, A_r \in {U \choose p_r}$, and $B \in {U \choose q}$ such that $p_1 + \ldots + p_r = p$. We need

to show that there is $F \in \chi(A_1) \cap \cdots \cap \chi(A_r) \cap \chi'(B)$. Since f_1, \ldots, f_t is a (p+q)-perfect family of hash functions, there is an i such that f_i is injective on $A_1 \cup \cdots \cup A_r \cup B$. Since $(\hat{\mathcal{F}}, \hat{\chi}, \hat{\chi}')$ is a $(p+q)^2$ -p-q-separating collection, $\exists \hat{F} \in \hat{\chi}(f_i(A_1)) \cap \cdots \hat{\chi}(f_i(A_r)) \cap \hat{\chi}'(f_i(B))$. Since f_i is injective on A_1, \ldots, A_r and $B, f_i^{-1}(\hat{F}) \in \chi(A_1) \cap \cdots \chi(A_r) \cap \chi'(B)$. This concludes the proof. \Box

We now give a *splitting lemma*, which allows us to reduce the problem of finding n-p-q-separating collections to the same problem, but with much smaller values for p and q.

A partition of U is a family $\mathcal{U}_P = \{U_1, U_2, \ldots, U_t\}$ of sets over U such that $U_i \cap U_j = \emptyset$ for every $i \neq j$ and $U = \bigcup_{i \leq t} U_i$. Each of the sets U_i are called the *parts* of the partition. A consecutive partition of $\{1, \ldots, n\}$ is a partition $\mathcal{U}_P = \{U_1, U_2, \ldots, U_t\}$ of $\{1, \ldots, n\}$ such that for every integer $i \leq t$ and integers $1 \leq x \leq y \leq z$, if $x \in U_i$ and $z \in U_i$ then $y \in U_i$ as well. In other words, in a consecutive partition each part is a consecutive interval of integers. For every integer t, let \mathscr{P}_t^n denote the collection of all consecutive partitions of $\{1, \ldots, n\}$ with exactly t parts. We do not demand that all of the parts in a partition in \mathscr{P}_t are non-empty. Simple counting arguments show that for every t, $|\mathscr{P}_t^n| = \binom{n+t-1}{t-1}$.

We will denote by $\mathcal{Z}_{s,t}^p$ the set of all t-tuples (p_1, p_2, \ldots, p_t) of integers such that $\sum_{i \leq t} p_i = p$ and $0 \leq p_i \leq s$ for all *i*. Clearly $|\mathcal{Z}_{s,t}^p| \leq {p+t-1 \choose t-1}$, since this counts all the ways of writing p as a sum of t non-negative integers, without considering the upper bound on each one. For an ease of convenience we summarize the above in the next definition and the proposition.

Definition 4.3. A partition of U is a family $\mathcal{U}_P = \{U_1, U_2, \dots, U_t\}$ of sets over U such that $\forall i \neq j, U_i \cap U_j = \emptyset$ and $U = \bigcup_{i \leq t} U_i$. Each of the sets U_i are called the parts of the partition. A consecutive partition of $\{1, \dots, n\}$ is a partition $\mathcal{U}_P = \{U_1, U_2, \dots, U_t\}$ of $\{1, \dots, n\}$ such that for every integer $i \leq t$ and integers $1 \leq x \leq y \leq z$, if $x \in U_i$ and $z \in U_i$ then $y \in U_i$ as well.

Proposition 4.2. Let \mathscr{P}_t^n denote the collection of all consecutive partitions of $\{1, \ldots, n\}$ with exactly t parts. Let $\mathcal{Z}_{s,t}^p$ be the set of all t-tuples (p_1, p_2, \ldots, p_t) of integers such that $\sum_{i \leq t} p_i = p$ and $0 \leq p_i \leq s$ for all i. Then for every t, $|\mathscr{P}_t^n| = \binom{n+t-1}{t-1}$ and $|\mathcal{Z}_{s,t}^p| \leq \binom{p+t-1}{t-1}$.

Lemma 4.5. For any p, q let $s = \lfloor (\log(p+q))^2 \rfloor$ and $t = \lceil \frac{p+q}{s} \rceil$. If there is a construction of n-p-q-separating collections $(\mathcal{F}_p, \chi_p, \chi'_p)$

- with size $\zeta(n, p, q)$ and initialization time $\tau_I(n, p, q)$,
- (χ_p, p') -degree $\Delta_{(\chi_p, p')}(n, p, q)$ and (χ'_p, q') -degree $\Delta_{(\chi'_p, q')}(n, p, q)$, and
- query times $Q_{(\chi_p,p')}(n,p,q)$ and $Q_{(\chi'_p,q')}(n,p,q)$,

then there is a construction of n-p-q-separating collection with following parameters

•

$$\zeta'(n, p, q) \le |\mathscr{P}_t^n| \cdot \sum_{(p_1, \dots, p_t) \in \mathcal{Z}_{s,t}^p} \prod_{i \le t} \zeta(n, p_i, s - p_i),$$

$$\tau_I'(n, p, q) = \mathcal{O}\Big(\Big(\sum_{\substack{\hat{p} \le s, p\\ s - \hat{p} \le q}} \tau_I(n, \hat{p}, s - \hat{p})\Big) + \zeta'(n, p, q) \cdot n^{\mathcal{O}(1)}\Big),$$

$$\Delta'_{(\chi,p')}(n,p,q) \le \Delta^*_{(\chi,p')}(n,p,q) = |\mathscr{P}^n_t| \cdot |\mathcal{Z}^p_{s,t}| \cdot \max_{\substack{(p_1,\dots,p_t)\in\mathcal{Z}^p_{s,t}\\p'_1\le p_1,\dots,p'_t\le p_t\\p'_1+\dots+p'_t=p'}} \prod_{i\le t} \Delta_{(\chi_{p_i},p'_i)}(n,p_i,s-p_i),$$

$$Q'_{(\chi,p')}(n,p,q) = \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot \big(\max_{\substack{\hat{p}' \le \hat{p} \le s \\ \hat{p} - \hat{p}' \le p - p' \\ s - \hat{p} \le q}} Q_{(\chi_{\hat{p}},\hat{p}')}(n,\hat{p},s-\hat{p})\big)\Big),$$

$$\Delta'_{(\chi',q')}(n,p,q) \le \Delta^*_{(\chi',q')}(n,p,q) = |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot \max_{\substack{(p_1,\dots,p_t)\in\mathcal{Z}^p_{s,t}\\q_1'\le s-p_1,\dots,q_t'\le s-p_t\\q_1'+\dots+q_t'=q'}} \prod_{i\le t} \Delta_{(\chi'_{p_i},q_i')}(n,p_i,s-p_i),$$

$$Q'_{(\chi',q')}(n,p,q) = \mathcal{O}\Big(\Delta^*_{(\chi',q')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot \big(\max_{\substack{\hat{q}' \le \hat{q} \le s \\ \hat{q} - \hat{q}' \le q - q' \\ s - \hat{q} \le p}} Q_{(\chi'_{s-\hat{q}},\hat{q}')}(n,s-\hat{q},\hat{q})\big)\Big).$$

Proof. Set $s = \lfloor (\log(p+q))^2 \rfloor$ and $t = \lceil \frac{p+q}{s} \rceil$. We will give a construction of *n*-*p*-*q*-separating collections with initialization time, query time, size and degree within the claimed bounds above. In this construction we will use the given construction as a black box. We may assume without loss of generality that $U = \{1, \ldots, n\}$. Our algorithm first runs for every $\hat{p}, 0 \leq \hat{p} \leq s, \hat{p} \leq s$ $p, s - \hat{p} \leq q$, and initializes $n - \hat{p} - (s - \hat{p})$ -separating collections,

$$(\mathcal{F}_{\hat{p}}, \chi_{\hat{p}}, \chi'_{\hat{p}}).$$

These will be be the building blocks of our construction.

We need to define a few operations on families of sets. For families of sets \mathcal{A}, \mathcal{B} over U and subset $U' \subseteq U$ we define

$$\mathcal{A} \sqcap U' = \{A \cap U' : A \in \mathcal{A}\}$$
$$\mathcal{A} \circ \mathcal{B} = \{A \cup B : A \in \mathcal{A} \land B \in \mathcal{B}\}$$

We now define \mathcal{F} as follows.

$$\mathcal{F} = \bigcup_{\substack{\{U_1, \dots, U_t\} \in \mathscr{P}_t^n \\ (p_1, \dots, p_t) \in \mathcal{Z}_{s,t}^p \text{ such that} \\ \forall i : s - p_i \le q}} (\mathcal{F}_{p_1} \sqcap U_1) \circ (\mathcal{F}_{p_2} \sqcap U_2) \circ \dots \circ (\mathcal{F}_{p_t} \sqcap U_t)$$
(3)

It follows directly from the definition of \mathcal{F} that $|\mathcal{F}|$ is within the claimed bound for $\zeta'(n, p, q)$. For the initialization time, the algorithm spends $\mathcal{O}\left(\sum_{\substack{\hat{p} \leq s, p \\ s - \hat{p} \leq q}} \tau_I(n, \hat{p}, s - \hat{p})\right)$ time to initialize the constructions of the $n - \hat{p} - (s - \hat{p})$ -separating collections for all $\hat{p} \leq s$ such that $\hat{p} \leq p$ and $s - \hat{p} \leq q$ together. Now the algorithm can output the entries of \mathcal{F} one set at a time by using Equation (3), spending $n^{\mathcal{O}(1)}$ time per output set. Hence the time bound for $\tau'_I(n, p, q)$ follows. For every set $A \in \bigcup_{p' \leq p} {U \choose p'}$ we define $\chi(A)$ as follows.

$$\chi(A) = \bigcup_{\substack{\{U_1, \dots, U_t\} \in \mathscr{P}_t^n \\ (p_1, \dots, p_t) \in \mathscr{Z}_{s,t}^p \text{ such that} \\ \forall U_i : |U_i \cap A| \le p_i, s - p_i \le q}} \left[(\chi_{p_1}(A \cap U_1) \sqcap U_1) \circ (\chi_{p_2}(A \cap U_2) \sqcap U_2) \circ \dots (4) \right]$$

Now we show that $\chi(A) \subseteq \mathcal{F}$. From the definition of $n p_i (s - p_i)$ -separating collections $(\mathcal{F}_{p_i}, \chi_{p_i}, \chi'_{p_i})$, each family $\chi_{p_i}(A \cap U_i)$ in Equation (4) is a subset of \mathcal{F}_{p_i} . This implies that $\chi_{p_i}(A \cap U_i) \sqcap U_i \subseteq \mathcal{F}_{p_i} \sqcap U_i$. Hence $\chi(A) \subseteq \mathcal{F}$. Similarly we can define $\chi'(B)$ for any $B \in \bigcup_{q' \leq q} {U \choose q'}$ as

$$\chi'(B) = \bigcup_{\substack{\{U_1, \dots, U_t\} \in \mathscr{P}_t^n \\ (p_1, \dots, p_t) \in \mathscr{Z}_{s,t}^p \text{ such that} \\ \forall U_i : |U_i \cap B| \le s - p_i \le q}} \left[(\chi'_{p_1}(B \cap U_1) \sqcap U_1) \circ (\chi'_{p_2}(B \cap U_2) \sqcap U_2) \circ \cdots \right]$$
(5)

$$\cdots \circ (\chi'_{p_t}(B \cap U_t) \sqcap U_t)$$

Similar to the proof of $\chi(A) \subseteq \mathcal{F}$, we can show that $\chi'(B) \subseteq \mathcal{F}$. It follows directly from the definition of $\chi(A)$ and $\chi'(B)$ that $|\chi(A)|$ and $|\chi'(B)|$ is within the claimed bound for $\Delta'_{(\chi,p')}(n,p,q)$ and $\Delta'_{(\chi',q')}(n,p,q)$ respectively. We now describe how queries $\chi(A)$ can be answered, and analyze how much time it takes. Given A we will compute $\chi(A)$ using Equation (4). Let |A| = p'. For each $\{U_1, \ldots, U_t\} \in \mathscr{P}^n_t$ and $(p_1, \ldots, p_t) \in \mathcal{Z}^p_{s,t}$ such that $p'_i = |U_i \cap A| \leq p_i, s - p_i \leq q$ for all $i \leq t$, we proceed as follows. First we compute $\chi_{p_i}(A \cap U_i)$ for each $i \leq t$, spending in total $\mathcal{O}(\sum_{i \leq t} Q_{(\chi_{p_i}, p'_i)}(n, p_i, s - p_i))$ time. Now we add each set in

$$(\chi_{p_1}(A \cap U_1) \sqcap U_1) \circ (\chi_{p_2}(A \cap U_2) \sqcap U_2) \circ \ldots \circ (\chi_{p_t}(A \cap U_t) \sqcap U_t)$$

to $\chi(A)$, spending $n^{\mathcal{O}(1)}$ time per set, yielding the bound below,

$$\begin{aligned} Q'_{(\chi,p')}(n,p,q) &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + \sum_{\substack{\{U_1,\dots,U_t\} \in \mathscr{P}_t \\ (p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \text{ such that} \\ \forall U_i : p'_i = |U_i \cap A| \leq p_i, s - p_i \leq q} \left[\sum_{i \leq t} Q_{(\chi_{p_i},p'_i)}(n,p_i,s-p_i)\right] \right) \\ &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot \max_{\substack{(p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \\ p'_1 \leq p_1,\dots,p'_t \leq p_t \text{ such that} \\ p'_1 + \dots + p'_t = p', \forall i:s - p_i \leq q}} \left(\sum_{i \leq t} Q_{(\chi_{p_i},p'_i)}(n,p_i,s-p_i)\right) \right) \\ &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot \max_{\substack{(p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \\ p'_1 \leq p_1,\dots,p'_t \leq p_t \text{ such that} \\ p'_1 + \dots + p'_t = p', \forall i:s - p_i \leq q}} \left(Q_{(\chi_{p_i},p'_i)}(n,p_i,s-p_i)\right) \right) \\ &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot (\max_{\substack{(p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \\ p'_1 \leq p_1,\dots,p'_t \leq p_t \text{ such that} \\ p'_1 + \dots + p'_t = p', \forall i:s - p_i \leq q}} \\ &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot (\max_{\substack{(p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \\ p'_1 \leq p_1,\dots,p'_t \leq p_t \text{ such that} \\ p'_1 + \dots + p'_t = p', \forall i:s - p_i \leq q}} \\ &\leq \mathcal{O}\Big(\Delta^*_{(\chi,p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^n_t| \cdot |\mathscr{Z}^p_{s,t}| \cdot t \cdot (\max_{\substack{(p_1,\dots,p_t) \in \mathscr{Z}^p_{s,t} \\ p'_1 \leq p_1,\dots,p'_t \leq p_t \leq p_t \neq q}} Q_{(\chi_{\hat{p},\hat{p}')}(n,\hat{p},s-\hat{p})})\Big) \end{aligned}$$

For any $(p_1, \ldots, p_t) \in \mathbb{Z}_{s,t}^p$ and $p'_1 \leq p_1, \ldots, p'_t \leq p_t$ such that $\sum_{i=1}^t p'_i = p'$, we have that $\sum_{i=1}^t p_i - p'_i = p - p'$ and so $p_i - p'_i \leq p - p'$ for all *i*. This shows the correctness of the last inequality in the above query time analysis.

By doing similar analysis, we get required bound for $Q'_{(\chi',q')}$. We now need to argue that $(\mathcal{F}, \chi, \chi')$ is in fact a *n-p-q*-separating collection. For any *r*, consider pairwise disjoint sets $A_1 \in \binom{U}{b_1}, \ldots, A_r \in \binom{U}{b_r}$ and $B \in \binom{U}{q}$ such that $b_1 + \cdots + b_r = p$. Let $A = A_1 \cup \cdots \cup A_r$. There exists a consecutive partition $\{U_1, \ldots, U_t\} \in \mathscr{P}^n_t$ of *U* such that for every $i \leq t$ we have that $|(A \cup B) \cap U_i| \leq \lceil \frac{p+q}{t} \rceil = s$. For each $i \leq t$ set $p_i = |A \cap U_i|$ and $q_i = |B \cap U_i| = s - p_i$. Note that $p_i \leq p$ and $q_i \leq q$ for all *i*. For every $i \leq t$ the tuple $(\mathcal{F}_{p_i}, \chi_{p_i}, \chi'_{p_i})$ form a *n-p_i-q_i*-separating collection. Hence there exists a $F_i \in \chi_{p_i}(A_1 \cap U_i) \cap \cdots \cap \chi_{p_i}(A_r \cap U_i) \cap \chi'_{p_i}(B \cap U_i)$ because $|A_1 \cap U_i| + \cdots + |A_r \cap U_i| = p_i, |B \cap U_i| = q_i$ and $(\mathcal{F}_{p_i}, \chi_{p_i}, \chi'_{p_i})$ is a *n-p_i-q_i*-separating collection.

That is $F_i \in \chi_{p_i}(A_j \cap U_i)$ for all $j \leq r$ and $F_i \in \chi'_{p_i}(B \cap U_i)$. Let $F = \bigcup_{i \leq t} F_i \cap U_i$. By construction of χ and χ' , $F \in \chi(A_j)$ for all $j \leq r$ and $F \in \chi'(B)$. Hence $F \in \chi(A_1) \cap \cdots \cap \chi(A_r) \cap \chi'(B)$. This completes the proof

Now we are ready to prove Lemma 4.2. We restate the lemma for easiness of presentation.

Lemma 4.2 Given 0 < x < 1, there is a construction of n-p-q- separating collection with the following parameters

- size: $\zeta(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^q} \cdot (p+q)^{O(1)} \cdot \log n$
- initialization time: $\tau_I(n, p, q) \le 2^{O(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p(1-x)^q}} \cdot (p+q)^{O(1)} \cdot n \log n$
- (χ, p') -degree: $\Delta_{(\chi, p')}(n, p, q) \le 2^{O(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{O(1)} \cdot \log n$
- (χ, p') -query time: $Q_{(\chi, p')}(n, p, q) \le 2^{O(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{O(1)} \cdot \log n$
- (χ',q') -degree: $\Delta_{(\chi',q')}(n,p,q) \le 2^{O(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^{q-q'}} \cdot (p+q)^{O(1)} \cdot \log n$
- (χ',q') -query time: $Q_{(\chi',q')}(n,p,q) \le 2^{O(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^{q-q'}} \cdot (p+q)^{O(1)} \cdot \log n$

Proof. We first explain a brute force construction of n-p-q-separating collection when the value of x is close to 0 or close to 1. These are discussed in Cases 1 and 2 and the result for all other values of x is explained in Case 3. Let U be the universe.

Case 1: $x \leq \frac{1}{n}$. In this case the algorithm will output all subset of size p of the universe as the family \mathcal{F} of sets in the *n*-*p*-*q*- separating collection. That is $\mathcal{F} = \{F \subseteq U \mid |F| = p\}$. We define χ and χ' as follows. For any $A \in \bigcup_{p' \leq p} {U \choose p'}$, $\chi(A) = \{F \in \mathcal{F} \mid A \subseteq F\}$. For any $B \in \bigcup_{q' \leq q} {U \choose q'}$, $\chi'(B) = \{F \in \mathcal{F} \mid B \cap F = \emptyset\}$. It is easy to see that $(\mathcal{F}, \chi, \chi')$ is a *n*-*p*-*q*separating collection. Note that $|\mathcal{F}| = {n \choose p} \leq n^p$. Since $n \leq \frac{1}{x}$, the size of the *n*-*p*-*q*- separating collection is upperbound by the claimed bound. Since we can list all the elements in \mathcal{F} in n^p time, the initialization time is upper bounded by the claimed bound. For any $A \subseteq U$, |A| = p', the cardinality of $\chi(A)$ is exactly equal to ${n \choose p-p'}$ which is upper bounded by $\frac{1}{x^{p-p'}}$. Thus the (χ, p') -degree and (χ, p') -query time is bounded by the claimed bound. For any $B \subseteq U$, |B| = q', the cardinality of $\chi'(B)$ is at most $|\mathcal{F}|$, which is upper bounded by $\frac{1}{x^p}$. Thus the (χ', q') -degree and (χ', q') -query time is bounded by the claimed bound.

Case 2: $1-x \leq \frac{1}{n}$. In this case the algorithm will output all subset of size n-q of the universe as the family \mathcal{F} of sets in the *n*-*p*-*q*- separating collection. That is $\mathcal{F} = \{F \subseteq U \mid |F| = n - q\}$. We define χ and χ' as follows. For any $A \in \bigcup_{p' \leq p} {U \choose p'}$, $\chi(A) = \{F \in \mathcal{F} \mid A \subseteq F\}$. For any $B \in \bigcup_{q' \leq q} {U \choose q'}$, $\chi'(B) = \{F \in \mathcal{F} \mid B \cap F = \emptyset\}$. It is easy to see that $(\mathcal{F}, \chi, \chi')$ is a *n*-*p*-*q*-separating collection. Note that $|\mathcal{F}| = {n \choose n-q} \leq n^q$. Since $n \leq \frac{1}{1-x}$, the size of the *n*-*p*-*q*-separating collection is upperbound by the claimed bound. Since we can list all the elements in \mathcal{F} in n^q time, the initialization time is upper bounded by the claimed bound. For any $A \subseteq U$, |A| = p', the cardinality of $\chi(A)$ is is at most $|\mathcal{F}|$ which is upper bounded by $\frac{1}{(1-x)^q}$. Thus the (χ, p') -degree and (χ, p') -query time is bounded by the claimed bound. For any $B \subseteq U$, |B| = q', the cardinality of $\chi'(B)$ is exactly equal to $\binom{n}{q-q'}$, which is upper bounded by $\frac{1}{(1-x)^{q-q'}}$.

Case 3: $x, 1 - x > \frac{1}{n}$. The structure of the proof in this case is as follows. We first create a collection using Lemma 4.3. Then we apply Lemma 4.4 and obtain another construction.

From here onwards we keep applying Lemma 4.5 and Lemma 4.4 in phases until we achieve the required bounds on size, degree, query and intializitaion time.

We first apply Lemma 4.3 and get a construction of n-p-q-separating collections with the following parameters.

• size,
$$\zeta^1(n, p, q) = \mathcal{O}\left(\frac{1}{x^p(1-x)^q} \cdot (p^2 + q^2 + 1)\log n\right)$$

- initialization time, $\tau_I^1(n, p, q) = \mathcal{O}(\binom{2^n}{\zeta(n, p, q)} \cdot \frac{1}{x^{p(1-x)q}} \cdot n^{\mathcal{O}(p+q)}),$
- (χ_1, p') -degree for $p' \le p$, $\Delta^1_{(\chi_1, p')}(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p-p'}} \cdot \frac{(p^2 + q^2 + 1)}{(1-x)^q} \cdot \log n\right)$ (χ_1, p') -query time $Q^1_{(\chi_1, p')}(n, p, q) = \mathcal{O}(\frac{1}{x^{p(1-x)q}} \cdot n^{\mathcal{O}(1)}) = \mathcal{O}(2^n n^{\mathcal{O}(1)})$
- (χ'_1, q') -degree for $q' \le q$, $\Delta^1_{(\chi'_1, q')}(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p}(1-x)^{q-q'}} \cdot (p^2 + q^2 + 1) \cdot \log n\right)$
- (χ'_1, q') -query time, $Q^1_{(\chi'_1, q')}(n, p, q) = \mathcal{O}(\frac{1}{x^p(1-x)^q} \cdot n^{\mathcal{O}(1)}) = \mathcal{O}(2^n n^{\mathcal{O}(1)})$

We apply Lemma 4.4 to this construction to get a new construction with the following parameters.

- size, $\zeta^2(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p(1-x)q}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right)$
- initialization time,

$$\begin{aligned} \tau_I^2(n, p, q) &= \mathcal{O}\left(\tau_I^1\left((p+q)^2, p, q\right) + \zeta^1\left((p+q)^2, p, q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot n\log n\right) \\ &= \mathcal{O}\left(\frac{2^{2^{(p+q)^2}}}{x^p(1-x)^q} \cdot (p+q)^{\mathcal{O}(p+q)} + \left(\frac{1}{x^p(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot n\log n\right)\right) \\ &= \mathcal{O}\left(\frac{(p+q)^{\mathcal{O}(p+q)}}{x^p(1-x)^q} \left(2^{2^{(p+q)^2}} + n\log n\right)\right) \end{aligned}$$

•
$$(\chi_2, p')$$
-degree, $\Delta^2_{(\chi_2, p')}(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right)$

•
$$(\chi_2, p')$$
-query time, $Q^2_{(\chi_2, p')}(n, p, q) = \mathcal{O}\left(\left(2^{(p+q)^2} + \frac{1}{x^{p-p'}(1-x)^q}\right)(p+q)^{\mathcal{O}(1)} \cdot \log n\right)$

- (χ'_2, q') -degree, $\Delta^2_{(\chi'_2, q')}(n, p, q) = \mathcal{O}\left(\frac{1}{x^{p(1-x)q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right)$
- (χ_2, q') -query time, $Q^2_{(\chi'_2, q')}(n, p, q) = \mathcal{O}\left(\left(2^{(p+q)^2} + \frac{1}{x^{p}(1-x)^{q-q'}}\right)(p+q)^{\mathcal{O}(1)} \cdot \log n\right)$

We apply Lemma 4.5 to this construction. Recall that in Lemma 4.5 we set $s = \lfloor (\log(p+q))^2 \rfloor$ and $t = \left\lceil \frac{p+q}{s} \right\rceil$.

$$\begin{split} \zeta^{3}(n,p,q) &\leq |\mathscr{P}_{t}^{n}| \cdot \sum_{(p_{1},\ldots,p_{t})\in\mathcal{Z}_{s,t}^{p}} \prod_{i\leq t} \zeta^{2}(n,p_{i},s-p_{i}) \\ &\leq n^{\mathcal{O}(t)} \cdot |\mathcal{Z}_{s,t}^{p}| \cdot \max_{(p_{1},\ldots,p_{t})\in\mathcal{Z}_{s,t}^{p}} \prod_{i\leq t} \zeta^{2}(n,p_{i},s-p_{i}) \\ &\leq n^{\mathcal{O}(t)} \cdot (p+q)^{\mathcal{O}(t)} \cdot \frac{1}{x^{p}(1-x)^{q+s}} \cdot s^{\mathcal{O}(t)} \cdot (\log n)^{\mathcal{O}(t)} \\ &\leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q}} \qquad \left(\operatorname{Because}\left(\frac{1}{1-x}\right)^{s} \leq n^{s} \leq n^{\mathcal{O}(t)}\right) \end{split}$$

$$\begin{aligned} \tau_{I}^{3}(n,p,q) &= \mathcal{O}\left(\left(\sum_{\substack{\hat{p} \leq s,p \\ s-\hat{p} \leq q}} \tau_{I}^{2}(n,\hat{p},s-\hat{p})\right) + \zeta^{3}(n,p,q) \cdot n^{\mathcal{O}(1)}\right) \\ &= \mathcal{O}\left(\left(\sum_{\substack{\hat{p} \leq s,p \\ s-\hat{p} \leq q}} \frac{s^{\mathcal{O}(s)}}{x^{\hat{p}}(1-x)^{s-\hat{p}}} \left(2^{2^{s^{2}}} + n\log n\right)\right) + \zeta^{3}(n,p,q) \cdot n^{\mathcal{O}(1)}\right) \\ &= \mathcal{O}\left(\frac{(\log(p+q))^{\mathcal{O}(\log^{2}(p+q))}}{x^{p}(1-x)^{q}} \left(2^{2^{\log^{4}(p+q)}} + n\log n\right) + n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q}}\right) \end{aligned}$$

$$\begin{split} \Delta^{3}_{(\chi_{3},p')}(n,p,q) &\leq \Delta^{*3}_{(\chi_{3},p')}(n,p,q) \\ &= |\mathscr{P}^{n}_{t}| \cdot |\mathscr{Z}^{p}_{s,t}| \cdot \max_{\substack{(p_{1},\dots,p_{t}) \in \mathscr{Z}^{p}_{s,t} \ p'_{1} \leq p_{1},\dots,p'_{t} \leq p_{t} \ p'_{1} \leq p_{1},\dots,p'_{t} \leq p_{t} \ p'_{1} + \dots + p'_{t} = p'} \\ &\leq n^{\mathcal{O}(t)} \cdot (p+q)^{\mathcal{O}(t)} \cdot \frac{1}{x^{p-p'}(1-x)^{q+s}} \cdot s^{\mathcal{O}(t)} \cdot (\log n)^{\mathcal{O}(t)} \\ &\leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^{q}} \qquad \left(\text{Because}\left(\frac{1}{1-x}\right)^{s} \in n^{\mathcal{O}(t)}\right) \\ \Delta^{3}_{(\chi'_{3},q')}(n,p,q) &\leq \Delta^{*3}_{(\chi'_{3},q')}(n,p,q) \\ &= |\mathscr{P}^{n}_{t}| \cdot |\mathscr{Z}^{p}_{s,t}| \cdot \max_{\substack{(p_{1},\dots,p_{t}) \in \mathscr{Z}^{p}_{s,t} \\ q'_{1} \leq s-p_{1},\dots,q'_{t} \leq s-q_{t}} \ q'_{1} + \dots + q'_{t} = q'} \\ &\leq n^{\mathcal{O}(t)} \cdot (p+q)^{\mathcal{O}(t)} \cdot \frac{1}{1-q} \cdot s^{\mathcal{O}(t)} \cdot (\log n)^{\mathcal{O}(t)} \end{split}$$

$$\leq n^{\mathcal{O}(\frac{p+q}{\log^2(p+q)})} \cdot \frac{1}{x^p(1-x)^{q-q'}} \qquad \left(\text{Because}\left(\frac{1}{1-x}\right)^s \in n^{\mathcal{O}(t)} \right)$$

$$\begin{split} Q^{3}_{(\chi_{3},p')}(n,p,q) &\leq \mathcal{O}\left(\Delta^{*3}_{(\chi_{3},p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}^{n}_{t}| \cdot |\mathscr{Z}^{p}_{s,t}| \cdot t \cdot \max_{\substack{\hat{p}' \leq \hat{p} \leq s \\ \hat{p} - \hat{p}' \leq p - p' \\ s - \hat{p} \leq q}} Q^{2}_{(\chi_{2},\hat{p}')}(n,\hat{p},s-\hat{p})\right) \\ &\leq \mathcal{O}\left(\Delta^{*3}_{(\chi_{3},p')}(n,p,q) \cdot n^{\mathcal{O}(1)} + n^{\mathcal{O}(t)} \cdot \max_{\substack{\hat{p}' \leq \hat{p} \leq s \\ \hat{p} - \hat{p}' \leq p - p' \\ s - \hat{p} \leq q}} \left(2^{s^{2}} + \frac{1}{x^{\hat{p} - \hat{p}'}(1-x)^{s-\hat{p}}}\right) s^{\mathcal{O}(1)} \log n\right) \\ &\leq \mathcal{O}\left(\frac{n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})}}{x^{p-p'}(1-x)^{q}} + n^{\mathcal{O}(t)} \cdot s^{\mathcal{O}(1)} \cdot \log n \left(2^{s^{2}} + \frac{1}{x^{p-p'}(1-x)^{q}}\right)\right) \\ &\leq \mathcal{O}\left(\frac{n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})}}{x^{p-p'}(1-x)^{q}}\right) \end{split}$$

Similar way we can bound $Q^3_{(\chi'_3,q')}$ as,

$$Q^3_{(\chi'_3,q')}(n,p,q) \leq \mathcal{O}\left(rac{n^{\mathcal{O}(rac{p+q}{\log^2(p+q)})}}{x^p(1-x)^{q-q'}}
ight)$$

We apply Lemma 4.4 to this construction to get a new construction with the following parameters.

- size, $\zeta^4(n, p, q) \le 2^{\mathcal{O}(\frac{p+q}{\log(p+q)})} \cdot \frac{1}{x^p(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$,
- initialization time,

$$\begin{aligned} \tau_{I}^{4}(n,p,q) &\leq \mathcal{O}\left(\tau_{I}^{3}\left((p+q)^{2},p,q\right) + \zeta^{3}\left((p+q)^{2},p,q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot n\log n\right) \\ &\leq 2^{2^{\log^{4}(p+q)}} \cdot \frac{(\log(p+q))^{\mathcal{O}(\log^{2}(p+q))}}{x^{p}(1-x)^{q}} + \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p}(1-x)^{q}} \cdot (p+q)^{\mathcal{O}(1)}n\log n \end{aligned}$$

• (χ_4, p') -degree,

$$\begin{aligned} \Delta^4_{(\chi_4,p')}(n,p,q) &\leq \Delta^3_{(\chi_3,p')} \left((p+q)^2, p, q \right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \\ &\leq \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \end{aligned}$$

• (χ'_4, q') -degree,

$$\begin{aligned} \Delta^4_{(\chi'_4,q')}(n,p,q) &\leq & \Delta^3_{(\chi'_3,q')}\left((p+q)^2, p, q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \\ &\leq & \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^p(1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \end{aligned}$$

• (χ_4, p') -query time,

$$\begin{aligned} Q^4_{(\chi_4,p')}(n,p,q) &\leq & \mathcal{O}\left(\left(Q^3_{(\chi_3,p')}\left((p+q)^2, p, q\right) + \Delta^3_{(\chi_3,p')}\left((p+q)^2, p, q\right)\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \\ &\leq & \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \log n \end{aligned}$$

• (χ'_4, q') -query time,

$$Q^4_{(\chi'_4,q')}(n,p,q) \ \leq \ \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^p(1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)}\log n$$

We apply Lemma 4.5 to this construction by setting $s = \lfloor (\log(p+q))^2 \rfloor$ and $t = \lceil \frac{p+q}{s} \rceil$.

• size,

$$\begin{split} \zeta^{5}(n,p,q) &\leq |\mathscr{P}_{t}^{n}| \cdot \sum_{(p_{1},\dots,p_{t})\in\mathcal{Z}_{s,t}^{p}} \prod_{i\leq t} \zeta^{4}(n,p_{i},s-p_{i}) \\ &\leq n^{\mathcal{O}(t)} \cdot (p+q)^{\mathcal{O}(t)} \cdot s^{\mathcal{O}(t)} \cdot 2^{\mathcal{O}(\frac{st}{\log s})} \cdot (\log n)^{\mathcal{O}(t)} \cdot \frac{1}{x^{p}(1-x)^{q+s}} \\ &\leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \frac{1}{x^{p}(1-x)^{q}} \qquad \left(\text{Because } \left(\frac{1}{1-x}\right)^{s} \in n^{\mathcal{O}(t)} \right) \end{split}$$

• initialization time,

$$\begin{split} \tau_{I}^{5}(n,p,q) &\leq \mathcal{O}\left(\left(\sum_{\substack{\hat{p} \leq s,p \\ s-\hat{p} \leq q}} \tau_{I}^{4}(n,\hat{p},s-\hat{p})\right) + \zeta^{5}(n,p,q) \cdot n^{\mathcal{O}(1)}\right) \\ &\leq \mathcal{O}\left(s\frac{2^{2\log^{4}s} \cdot (\log s)^{\mathcal{O}(\log^{2}s)}}{x^{p}(1-x)^{q}} + \frac{2^{\mathcal{O}(\frac{s}{\log s})}}{x^{p}(1-x)^{q}} \cdot n\log n + n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(s\frac{2^{2\log^{4}s} \cdot (\log s)^{\mathcal{O}(\log^{2}s)}}{x^{p}(1-x)^{q}} + n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(\frac{2^{2\log^{4}s} \cdot (s)^{\mathcal{O}(s)}}{x^{p}(1-x)^{q}} + n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(\frac{2^{2(2\log\log(p+q))^{4}} \cdot (\log(p+q))^{\mathcal{O}(\log(p+q))^{2}}}{x^{p}(1-x)^{q}} + n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \\ &\leq \mathcal{O}\left(n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot \frac{2^{\mathcal{O}(\frac{p+q}{\log(p+q)})}}{x^{p}(1-x)^{q}}\right) \end{aligned}$$

• (χ_5, p') -degree,

$$\begin{split} \Delta^{5}_{(\chi_{5},p')}(n,p,q) &\leq \Delta^{*5}_{(\chi_{5},p')}(n,p,q) \\ &= |\mathscr{P}^{n}_{t}| \cdot |\mathscr{Z}^{p}_{s,t}| \cdot \max_{\substack{(p_{1},...,p_{t}) \in \mathscr{Z}^{p}_{s,t} \\ p'_{1} \leq p_{1},...,p'_{t} \leq p_{t} \\ p'_{1} + ... + p'_{t} = p'}} \prod_{i \leq t} \Delta^{4}_{(\chi_{4},p'_{i})}(n,p_{i},s-p_{i}) \\ &\leq n^{\mathcal{O}(t)} \cdot (p+q)^{\mathcal{O}(t)} \cdot \frac{2^{\mathcal{O}(\frac{st}{\log s})}}{x^{p-p'}(1-x)^{q+s}} \cdot s^{\mathcal{O}(t)} \cdot (\log n)^{\mathcal{O}(t)} \\ &\leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^{q}} \qquad \left(\text{Because } \left(\frac{1}{1-x}\right)^{s} \in n^{\mathcal{O}(t)} \right) \end{split}$$

• (χ'_5, q') -degree,

$$\begin{aligned} \Delta^{5}_{(\chi'_{5},q')}(n,p,q) &\leq & \Delta^{*5}_{(\chi'_{5},q')}(n,p,q) \\ &\leq & n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q-q'}} \end{aligned}$$

• (χ_5, p') -query time,

$$Q_{(\chi_{5},p')}^{5}(n,p,q) \leq \mathcal{O}\left(\Delta_{(\chi_{5},p')}^{*5}(n,p,q) \cdot n^{\mathcal{O}(1)} + |\mathscr{P}_{t}^{n}| \cdot |\mathcal{Z}_{s,t}^{p}| \cdot \max_{\substack{\hat{p}' \leq \hat{p} \leq s \\ \hat{p} - \hat{p}' \leq p - p' \\ s - \hat{p} \leq q}} Q_{(\chi_{4},\hat{p}')}^{4}(n,\hat{p},s-\hat{p})\right) \\ \leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^{q}}$$

• (χ'_5, q') -query time,

$$Q_{(\chi'_{5},q')}^{5}(n,p,q) \leq n^{\mathcal{O}(\frac{p+q}{\log^{2}(p+q)})} \cdot 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q-q'}}$$

We apply Lemma 4.4 to this construction to get a new construction with the following parameters.

• size,

$$\begin{aligned} \zeta(n,p,q) &\leq \zeta^5 \left((p+q)^2, p, q \right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \\ &\leq 2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p (1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \log n \end{aligned}$$

• initialization time,

$$\begin{aligned} \tau_I(n,p,q) &\leq \mathcal{O}\left(\tau_I^5\left((p+q)^2,p,q\right) + \zeta^5\left((p+q)^2,p,q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot n\log n\right) \\ &= \mathcal{O}\left(2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)}n\log n\right) \end{aligned}$$

• (χ, p') -degree,

$$\begin{aligned} \Delta_{(\chi,p')}(n,p,q) &\leq \Delta^5_{(\chi_5,p')}\left((p+q)^2,p,q\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \\ &\leq \mathcal{O}\left(2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^q} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \end{aligned}$$

• (χ, p') -query time,

$$\begin{aligned} Q_{(\chi,p')}(n,p,q) &\leq \mathcal{O}\left(\left(Q^{5}_{(\chi_{5},p')}\left((p+q)^{2},p,q\right) + \Delta^{5}_{(\chi_{5},p')}\left((p+q)^{2},p,q\right)\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \\ &\leq \mathcal{O}\left(2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p-p'}(1-x)^{q}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \end{aligned}$$

• (χ', q') -degree,

$$\begin{aligned} \Delta_{(\chi',q')}(n,p,q) &= \Delta_{(\chi'_5,q')}^5 \left((p+q)^2, p, q \right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \\ &\leq \mathcal{O}\left(2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^p (1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \right) \end{aligned}$$

• (χ', q') -query time,

$$\begin{aligned} Q_{(\chi',q')}(n,p,q) &= \mathcal{O}\left(\left(Q^{5}_{(\chi'_{5},q')}\left((p+q)^{2},p,q\right) + \Delta^{5}_{(\chi'_{5},q')}\left((p+q)^{2},p,q\right)\right) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \\ &\leq \mathcal{O}\left(2^{\mathcal{O}(\frac{p+q}{\log\log(p+q)})} \cdot \frac{1}{x^{p}(1-x)^{q-q'}} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n\right) \end{aligned}$$

The final construction satisfies all the claimed bounds. This concludes the proof.

Lemma 4.6. There is an algorithm that given a p-family \mathcal{A} of sets over a universe U of size n, an integer q, a 0 < x < 1, and a non-negative weight function $w : \mathcal{A} \to \mathbb{N}$ with maximum value at most W, computes in time

$$\mathcal{O}(x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot n\log n + |\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

a subfamily $\widehat{\mathcal{A}} \subseteq \mathcal{A}$ such that $|\widehat{\mathcal{A}}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$ and $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$ ($\widehat{\mathcal{A}} \subseteq_{maxrep}^{q} \mathcal{A}$).

Proof. The algorithm first checks whether $|\mathcal{A}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$. If yes then it outputs \mathcal{A} (as $\hat{\mathcal{A}}$) and halts. So we assume that $|\mathcal{A}| > x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$. The algorithm starts by constructing a generalized *n*-*p*-*q*-separating collection $(\mathcal{F}, \chi, \chi')$ as guaranteed by Lemma 4.2. If $|\mathcal{A}| \leq |\mathcal{F}|$ the algorithm outputs \mathcal{A} and halts. Otherwise it builds the set $\hat{\mathcal{A}}$ as follows. Initially $\hat{\mathcal{A}}$ is equal to \emptyset and all sets in \mathcal{F} are marked as unused. Now we sort the sets in \mathcal{A} in the increasing order of weights, given by $w : \mathcal{A} \to \mathbb{N}$. The algorithm goes through every $A \in \mathcal{A}$ in the sorted order and queries the separating collection to get the set $\chi(A)$. It then looks for a set $F \in \chi(A)$ that is not yet marked as used. The first time such a set F is found the algorithm marks F as used, inserts A into $\hat{\mathcal{A}}$ and proceeds to the next set in \mathcal{A} . If no such set F is found the algorithm proceeds to the next set in \mathcal{A} without inserting A into $\hat{\mathcal{A}}$.

The size of $\hat{\mathcal{A}}$ is upper bounded by $|\mathcal{F}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$ since every time a set is added to $\hat{\mathcal{A}}$ an unused set in \mathcal{F} is marked as used. For the running time analysis, the initialization of (\mathcal{F}, χ) takes time $x^{-p}(1-x)^{-q} \cdot (p+q)^{\mathcal{O}(1)} \cdot 2^{o(p+q)} \cdot n \log n$. Sorting \mathcal{A} takes $\mathcal{O}(|\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W)$ time. For each element $A \in \mathcal{A}$ the algorithm first queries $\chi(A)$, using time $(1-x)^{-q} \cdot 2^{o(p+q)} \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n$. Then it goes through all sets in $\chi(A)$ and checks whether they have already been marked as used, taking time $(1-x)^{-q} \cdot (p+q)^{\mathcal{O}(1)} \cdot 2^{o(p+q)} \cdot \log n$. Thus in total, the running time for these steps is bounded by $\mathcal{O}(|\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n + |\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W)$. Adding the initialization time to this gives the claimed running time.

Finally we need to argue that $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$. Consider any set $A \in \mathcal{A}$ and B such that |B| = q and $A \cap B = \emptyset$. If $A \in \widehat{\mathcal{A}}$ we are done, so assume that $A \notin \widehat{\mathcal{A}}$. Since $(\mathcal{F}, \chi, \chi')$ is a *n-p-q*-separating collection, we have that there exists $F \in \chi(A) \cap \chi'(B)$, i.e, $A \subseteq F$ and $F \cap B = \emptyset$. Since $A \notin \widehat{\mathcal{A}}$ we know that F was marked as used when A was considered by the algorithm. When the algorithm marked F as used it also inserted a set A' into $\widehat{\mathcal{A}}$, with the property that $F \in \chi(A')$. Thus $A' \subseteq F$ and hence $A' \cap B = \emptyset$. Furthermore, A' was considered before A and thus $w(A') \leq w(A)$. But $A' \in \widehat{\mathcal{A}}$, completing the proof. \Box

Next we prove a "faster version of Lemma 4.6", that speeds up the running time to compute the representative families.

Lemma 4.7. There is an algorithm that given a p-family \mathcal{A} of sets over a universe U of size n, an integer q, a 0 < x < 1, and a non-negative weight function $w : \mathcal{A} \to \mathbb{N}$ with maximum value at most W, computes in time

 $\mathcal{O}((p+q)^{\mathcal{O}(1)}n\log n + |\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$

a subfamily $\widehat{\mathcal{A}} \subseteq \mathcal{A}$ such that $|\widehat{\mathcal{A}}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$ and $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$ $(\widehat{\mathcal{A}} \subseteq_{maxrep}^{q} \mathcal{A})$.

Proof. The algorithm first checks whether $|\mathcal{A}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$. If yes then it outputs \mathcal{A} (as $\widehat{\mathcal{A}}$) and halts. So we assume that $|\mathcal{A}| > x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$.

We start by constructing a (p+q)-perfect family f_1, \ldots, f_t of hash functions from U to $[(p+q)^2]$ with $t = \mathcal{O}((p+q)^{\mathcal{O}(1)} \cdot \log n)$ in time $\mathcal{O}(k^{\mathcal{O}(1)}n \log n)$ using Proposition 4.1. Now we sort the sets in \mathcal{A} in the increasing order of weights, given by $w : \mathcal{A} \to \mathbb{N}$. For every f_j , $1 \leq j \leq t$, we construct a family $\hat{\mathcal{A}}_j$ as follows. The algorithm starts by constructing a generalized $[(p+q)^2]$ -p-q-separating collection $(\mathcal{F}_j, \chi_j, \chi'_j)$ as guaranteed by Lemma 4.2. It builds the set $\hat{\mathcal{A}}_j$ as follows. Initially $\hat{\mathcal{A}}_j$ is equal to \emptyset and all sets in \mathcal{F} are marked as unused. The algorithm goes through every $A \in \mathcal{A}$ in the sorted order and does as follows.

• It first check whether every element in A gets mapped to distinct integers by f_j . That is, $|\{f_j(a) \mid a \in A\}| = |A|$. If $|\{f_j(a) \mid a \in A\}| < |A|$ then the algorithm proceeds to the next set in A without inserting A into \hat{A} . Else, we move to the next step.

• It queries the separating collection to get the set $\chi(A)$. It looks for a set $F \in \chi_j(A)$ that is not yet marked as used. The first time such a set F is found the algorithm marks F as used, inserts A into $\hat{\mathcal{A}}_j$ and proceeds to the next set in \mathcal{A} . If no such set F is found the algorithm proceeds to the next set in \mathcal{A} without inserting A into $\hat{\mathcal{A}}_j$.

Finally, we return $\hat{\mathcal{A}} = \bigcup_{j=1}^t \hat{\mathcal{A}}_j$.

The size of $\hat{\mathcal{A}}_j$ is upper bounded by $|\mathcal{F}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log(p+q)$ since every time a set is added to $\hat{\mathcal{A}}$ an unused set in \mathcal{F} is marked as used. Thus, the size of $\hat{\mathcal{A}}$ is upper bounded by $|\mathcal{F}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log(p+q) \cdot (p+q)^{\mathcal{O}(1)} \cdot \log n \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n$. The running time analysis follows similar to the one given in Lemma 4.6.

Finally we need to argue that $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$. Consider any set $A \in \mathcal{A}$ and B such that |B| = qand $A \cap B = \emptyset$. If $A \in \widehat{\mathcal{A}}$ we are done, so assume that $A \notin \widehat{\mathcal{A}}$. By the properties of (p+q)-perfect family f_1, \ldots, f_t of hash functions from U to $[(p+q)^2]$, there exists an integer $j \in \{1, \ldots, t\}$ such that f_j is injective on $A \cup B$. We focus now on the construction of $\widehat{\mathcal{A}}_j$. Since $(\mathcal{F}_j, \chi_j, \chi'_j)$ is a $[(p+q)^2]$ -p-q-separating collection, we have that there exists $F \in \chi_j(A) \cap \chi'_j(B)$, i.e, $A \subseteq F$ and $F \cap B = \emptyset$. Since $A \notin \widehat{\mathcal{A}}_j$ (as $A \notin \widehat{\mathcal{A}}$) we know that F was marked as used when A was considered by the algorithm. When the algorithm marked F as used it also inserted a set A'into $\widehat{\mathcal{A}}$, with the property that $F \in \chi(A')$. Thus $A' \subseteq F$ and hence $A' \cap B = \emptyset$. Furthermore, A'was considered before A and thus $w(A') \leq w(A)$. But $A' \in \widehat{\mathcal{A}}_j \subseteq \widehat{\mathcal{A}}$, completing the proof. \Box

While applying Lemma 4.7 we can reduce the universe size to at most $|\mathcal{A}|p+q$. The next lemma formalizes this.

Lemma 4.8. There is an algorithm that given a p-family \mathcal{A} of sets over a universe U of size n, an integer q, a 0 < x < 1 and a non-negative weight function $w : \mathcal{A} \to \mathbb{N}$ with maximum value at most W, computes in time

$$\mathcal{O}(|\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

a subfamily $\widehat{\mathcal{A}} \subseteq \mathcal{A}$ such that $|\widehat{\mathcal{A}}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log |\mathcal{A}|$ and $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$ ($\widehat{\mathcal{A}} \subseteq_{maxrep}^{q} \mathcal{A}$).

Proof. We first construct a new universe U' as follows. If $n \leq |\mathcal{A}|p + q$, then we set U' = U, otherwise U' will consist of elements from U, which are part of any set in \mathcal{A} and q new elements. The universe U' can be constructed in $\mathcal{O}(|\mathcal{A}|p+q)$ time. Also note that $|U'| \leq |\mathcal{A}|p+q$ and $|U'| \leq n$. Now we claim that a q-representative family $\widehat{\mathcal{A}}$ of \mathcal{A} with respect to the universe U' is also the required representative family over U. Suppose $X \in \mathcal{A}$ and $Y \subseteq U$, $|Y| \leq q$ such that $X \cap Y = \emptyset$. Let $Y' = Y \setminus U'$ and let Y'' be an arbitrary subset of size |Y'| of $U' \setminus U$. Let $Z = (Y \setminus Y') \cup Y''$. It is easy to see that |Z| = |Y| and $X \cap Z = \emptyset$. By the definition of q-representative family, there exists $\widehat{X} \in \widehat{A}$ such that $\widehat{X} \cap Z = \emptyset$. Since $Y' \cap \widehat{X} = \emptyset$, we have that $\widehat{X} \cap Y = \emptyset$.

Thus we apply Lemma 4.7 to compute q-representative family $\hat{\mathcal{A}}$ of \mathcal{A} with respect to the universe U' and output it as the desired family. The claimed running time as well as the size bound on the output representative family follow by substituting the upper bound on |U'| in the bounds coming from Lemma 4.7.

Finally, we give our main theorem.

Theorem 6. There is an algorithm that given a p-family \mathcal{A} of sets over a universe U of size n, an integer q, a 0 < x < 1 and a non-negative weight function $w : \mathcal{A} \to \mathbb{N}$ with maximum value at most W, computes in time

$$\mathcal{O}(|\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

a subfamily $\widehat{\mathcal{A}} \subseteq \mathcal{A}$ such that $|\widehat{\mathcal{A}}| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)}$ and $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$ ($\widehat{\mathcal{A}} \subseteq_{maxrep}^{q} \mathcal{A}$).

Proof. Let $\mathcal{A} = \mathcal{A}_1$. We compute a sequence of representative families

$$\mathcal{A}_2 \subseteq_{minrep}^q \mathcal{A}_1, \cdots, \mathcal{A}_m \subseteq_{minrep}^q \mathcal{A}_{m-1}$$

using Corollary 4.8, such that m is the least integer with the property that $|\mathcal{A}_m| \ge |\mathcal{A}_{m-1}|/2$. In other words, for all i < m we have that $|\mathcal{A}_i| \le |\mathcal{A}_{i-1}|/2$ and $|\mathcal{A}_m| \ge |\mathcal{A}_{m-1}|/2$. We output \mathcal{A}_m as the q-representative family for \mathcal{A} . The correctness of this following from Lemma 3.1. By Corollary 4.8,

$$\begin{aligned} |\mathcal{A}_{m}| &\leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log |\mathcal{A}_{m-1}| \\ &\leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log 2|\mathcal{A}_{m}| \\ \\ \text{Thus,} \ \frac{|\mathcal{A}_{m}|}{\log |\mathcal{A}_{m}|} &\leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)}. \end{aligned}$$

We know that for some number a and b, if $a \leq b$ then $a \log^2 a \leq b \log^2 b$. Applying this identity we get the following.

$$\frac{|\mathcal{A}_m|}{\log|\mathcal{A}_m|}\log^2\left(\frac{|\mathcal{A}_m|}{\log|\mathcal{A}_m|}\right) \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)}$$

The above inequality implies that

$$|\mathcal{A}_m| \le \frac{|\mathcal{A}_m|}{\log|\mathcal{A}_m|} \log^2 \left(\frac{|\mathcal{A}_m|}{\log|\mathcal{A}_m|}\right) \le x^{-p} (1-x)^{-q} \cdot 2^{o(p+q)}$$

and thus $|\mathcal{A}_m| \leq x^{-p}(1-x)^{-q} \cdot 2^{o(p+q)}$. By Lemma 4.8, the total running time T to compute \mathcal{A}_m is,

$$T = \sum_{i=1}^{m-1} |\mathcal{A}_{i}| \cdot \log |\mathcal{A}_{i}| \cdot \log W + |\mathcal{A}_{i}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

$$= \sum_{i=1}^{m-1} \mathcal{O}\Big(\frac{|\mathcal{A}|}{2^{i-1}} \cdot \log |\mathcal{A}| \cdot \log W + \frac{|\mathcal{A}|}{2^{i-1}} \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n\Big) \quad (\text{since } |\mathcal{A}_{i}| \le \frac{|\mathcal{A}|}{2^{i-1}})$$

$$= \mathcal{O}(|\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

This concludes the proof.

The size of the output representative family in Theorem 6 is minimized when $x = \frac{p}{p+q}$. By substituting $x = \frac{p}{p+q}$ in Theorem 6 we get the following corollary.

Corollary 1. There is an algorithm that given a p-family \mathcal{A} of sets over a universe U of size n, an integer q, and a non-negative weight function $w : \mathcal{A} \to \mathbb{N}$ with maximum value at most W, computes in time

$$\mathcal{O}(|\mathcal{A}| \cdot \log |\mathcal{A}| \cdot \log W + |\mathcal{A}| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n)$$

a subfamily $\widehat{\mathcal{A}} \subseteq \mathcal{A}$ such that $|\widehat{\mathcal{A}}| \leq {p+q \choose p} \cdot 2^{o(p+q)}$ and $\widehat{\mathcal{A}} \subseteq_{minrep}^{q} \mathcal{A}$ $(\widehat{\mathcal{A}} \subseteq_{maxrep}^{q} \mathcal{A})$.

5 Applications

In this section we demonstrate how the efficient construction of representative families can be used to design single-exponential parameterized and exact exponential time algorithms. Our applications include best known deterministic algorithms for LONG DIRECTED CYCLE, MINIMUM EQUIVALENT GRAPH, k-PATH and k-TREE.

Let $M = (E, \mathcal{I})$ be a matroid with the ground set of size n and $\mathcal{S} = \{S_1, \ldots, S_t\}$ be a p-family of independent sets. Then for specific matroids we use the following notations to denote the time required to compute the following q-representative families of \mathcal{S} :

- $\mathcal{T}_{rm}(t, p, q)$ is the time required to compute a family $\widehat{\mathcal{S}} \subseteq_{rep}^{q} \mathcal{S}$ of size $\binom{p+q}{q}$, when M is a linear matroid.
- $\mathcal{T}_{\text{um}}(t, p, q)$ is the time required to compute a family $\widehat{\mathcal{S}} \subseteq_{rep}^{q} \mathcal{S}$ of size $\binom{p+q}{p} \cdot 2^{o(p+q)} \cdot \log n$, when M is a uniform matroid and x is chosen to be $\frac{p}{p+q}$.

Let us remind, that by Theorem 1, when rank of M is p + q, $\mathcal{T}_{rm}(t, p, q)$ is bounded by $\mathcal{O}\left(\binom{p+q}{p}tp^{\omega} + t\binom{p+q}{q}^{\omega-1}\right)$ multiplied by the time required to perform operations over \mathbb{F} . By Corollary 1, $\mathcal{T}_{um}(t, p, q) = \mathcal{O}(t \cdot (\frac{p+q}{q})^q \cdot \log n)$

5.1 Long Directed Cycle

In this section we give our first application of algorithms based on representative families. We study the following problem.

Long Directed Cycle	Parameter: k
Input: A <i>n</i> -vertex and <i>m</i> -arc directed graph D and a positive integer k .	
Question: Does there exist a directed cycle of length at least k in D ?	

Observe that the LONG DIRECTED CYCLE problem is different from the well-known problem of finding a directed cycle of length *exactly* k. It is quite possible that the only directed cycle that has length at least k is much longer than k, and possibly even is a Hamiltonian cycle. Let D be a directed graph, k be a positive integer, and $M = (E, \mathcal{I})$ be a uniform matroid $U_{n,2k}$ where E = V(D) and $\mathcal{I} = \{S \subseteq V(D) \mid |S| \leq 2k\}$. In this subsection whenever we talk about independent sets, these are independent sets of the uniform matroid $U_{n,2k}$. For a pair of vertices $u, v \in V(D)$, we define

 $\mathcal{P}_{uv}^i = \left\{ X \mid X \subseteq V(D), \ u, v \in X, \ |X| = i, \text{ and there is a directed } uv\text{-path in } D \right\}$

of length i - 1 with all the vertices belonging to X.

We start with a structural lemma providing the key insight to our algorithm.

Lemma 5.1. Let D be a directed graph. Then D has a directed cycle of length at least k if and only if there exists a pair of vertices $u, v \in V(D)$ and $X \in \widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$ such that D has a directed cycle C and in this cycle vertices of X induce a directed path (that is, vertices of Xform a consecutive segment in C).

Proof. The reverse direction of the proof is straightforward—if cycle C contains a path of length k, the length of C is at least k. We proceed with the proof of the forward direction. Let $C^* = v_1 v_2 \cdots v_r v_1$ be a smallest directed cycle in D of length at least k. That is, $r \geq k$ and there is no directed cycle of length r' where $k \leq r' < r$. We consider two cases.



Figure 1: Illustration to the proof of Lemma 5.1.

Case A: $r \leq 2k$. If $r \leq 2k$, then we take $u = v_1$ and $v = v_k$. We define paths $P = v_1 v_2 \cdots v_k$ and $Q = v_{k+1} \cdots v_r$. Because $|Q| \leq k$, by the definition of $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$, there exists a directed uv-path P' such that $X = V(P') \in \widehat{\mathcal{P}}_{uv}^k$ and $X \cap Q = \emptyset$. By replacing P with P' in C^* we obtain a directed cycle C of length at least k containing P' as a subpath.

Case B: $r \geq 2k + 1$. In this case we set $u = v_1$, $v = v_k$, and split C^* into three paths $P = v_1 \cdots v_k$, $Q = v_{k+1} \cdots v_{2k}$, and $R = v_{2k+1} \cdots v_r$. Since |Q| = k and $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$, it follows that there exists an *uv*-path P' such that $X = V(P') \in \widehat{\mathcal{P}}_{uv}^k$ and $X \cap Q = \emptyset$. However, P' is not necessarily disjoint with R and by replacing P with P' in C^* we can obtain a *closed walk* C' containing P' as a subpath. See Fig. 1 for an illustration.

If $X \cap R = \emptyset$, then C' is a simple cycle and we take C' as the desired C. We claim that this is the only possibility. Let us assume targeting towards a contradiction that $X \cap R \neq \emptyset$. We want to show that in this case there is a cycle of length at least k but shorter than C^* , contradicting the choice of C^* . Let v_{α} be the last vertex in $X \cap R$ when we walk from v_1 to v_k along P'. Let $P'[v_{\alpha}, v_k]$ be the subpath of P' starting at v_{α} and ending at v_k . If $v_{\alpha} = v_{2k+1}$, we set $R' = \emptyset$. Otherwise we put $R' = R[v_{2k+1}, v_{\alpha-1}]$ to be the subpath of R starting at v_{2k+1} and ending at $v_{\alpha-1}$. Observe that since the arc $v_{\alpha-1}v_{\alpha}$ is present in D (in fact it is an arc of the cycle C^*), we have that $\overline{C} = P'[v_{\alpha}, v_k]QR'$ is a simple cycle in D. Clearly, $|\overline{C}| \ge |Q| \ge k$. Furthermore, since v_1 is not present in $P'[v_{\alpha}, v_k]$ we have that $|P'[v_{\alpha}, v_k]| < |P'| = |P|$. Similarly since v_{α} is not present in R', we have that |R'| < |R|. Thus we have

$$k \le |\overline{C}| = |P'[v_{\alpha}, v_k]| + |Q| + |R'| < |P| + |Q| + |R| = |C^*|.$$

This implies that \overline{C} is a directed simple cycle of length at least k and strictly smaller than r. This is a contradiction. Hence by replacing P with P' in C^* we obtain a directed cycle C containing P' as a subpath. This concludes the proof.

Next lemma provides an efficient computation of family $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$. The next lemma is provided to give a simple exposition of representative families based dynamic programming algorithm.

Lemma 5.2. Let D be a directed/unidrected graph with n vertices and m edges, $u \in V(D)$ and $M = (E, \mathcal{I})$ be an uniform matroid $U_{n,\ell}$ where E = V(D) and $\mathcal{I} = \{S \subseteq V(D) \mid |S| \leq \ell\}$. Then

for every $p \leq \ell$ and $v \in V(D) \setminus \{u\}$, a family $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^{\ell-p} \mathcal{P}_{uv}^p$ of size at most

$$\binom{\ell}{p} \cdot 2^{o(\ell)}$$

can be found in time

$$\mathcal{O}\left(2^{o(\ell)}m\log n\max_{i\in[p]}\left\{\binom{\ell}{i-1}\left(\frac{\ell}{\ell-i}\right)^{\ell-i}\right\}\right).$$

Furthermore, within the same running time every set in $\widehat{\mathcal{P}}_{uv}^p$ can be ordered in a way that it corresponds to a directed (undirected) path in D.

Proof. We prove the lemma only for digraphs. The proof for undirected graphs is analogous and we only point out the differences with the proof for the directed case. We describe a dynamic programming based algorithm. Let $V(D) = \{u, v_1, \ldots, v_{n-1}\}$ and \mathcal{D} be a $(p-1) \times (n-1)$ matrix where the rows are indexed from integers in $\{2, \ldots, p\}$ and the columns are indexed from vertices in $\{v_1, \ldots, v_{n-1}\}$. The entry $\mathcal{D}[i, v]$ will store the family $\widehat{\mathcal{P}}_{uv}^i \subseteq_{rep}^{\ell-i} \mathcal{P}_{uv}^i$. We fill the entries in the matrix \mathcal{D} in the increasing order of rows. For i = 2, $\mathcal{D}[2, v] = \{\{u, v\}\}$ if $uv \in A(D)$ (for an undirected graph we check whether u and v are adjacent). Assume that we have filled all the entries until the row i. Let

$$\mathcal{N}_{uv}^{i+1} = \bigcup_{w \in N^-(v)} \widehat{\mathcal{P}}_{uw}^i \bullet \{v\}.$$

For undirected graphs we use the following definition

$$\mathcal{N}_{uv}^{i+1} = \bigcup_{w \in N(v)} \widehat{\mathcal{P}}_{uw}^i \bullet \{v\}.$$

Claim 5.1. $\mathcal{N}_{uv}^{i+1} \subseteq_{rep}^{\ell-(i+1)} \mathcal{P}_{uv}^{i+1}$.

Proof. Let $S \in \mathcal{P}_{uv}^{i+1}$ and Y be a set of size $\ell - (i+1)$ (which is essentially an independent set of $U_{n,\ell}$) such that $S \cap Y = \emptyset$. We will show that there exists a set $S' \in \mathcal{N}_{uv}^{i+1}$ such that $S' \cap Y = \emptyset$. This will imply the desired result. Since $S \in \mathcal{P}_{uv}^{i+1}$ there exists a directed path $P = ua_1 \cdots a_{i-1}v$ in D such that $S = \{u, a_1, \dots, a_{i-1}, v\}$ and $a_{i-1} \in N^-(v)$. The existence of path $P[u, a_{i-1}]$, the subpath of P between u and a_{i-1} , implies that $X^* = S \setminus \{v\} \in \mathcal{P}_{ua_{i-1}}^i$. Take $Y^* = Y \cup \{v\}$. Observe that $X^* \cap Y^* = \emptyset$ and $|Y^*| = \ell - i$. Since $\widehat{\mathcal{P}}_{ua_{i-1}}^i \subseteq_{rep}^{\ell - i} \mathcal{P}_{ua_{i-1}}^i$ there exists a set $\widehat{X}^* \in \widehat{\mathcal{P}}_{ua_{i-1}}^i$ such that $\widehat{X}^* \cap Y^* = \emptyset$. However, since $a_{i-1} \in N^-(v)$ and $\widehat{X}^* \cap \{v\} = \emptyset$ (as $\widehat{X}^* \cap Y^* = \emptyset$), we have $\widehat{X}^* \bullet \{v\} = \widehat{X}^* \cup \{v\}$ and $\widehat{X}^* \cup \{v\} \in \mathcal{N}_v^{i+1}$. Taking $S' = \widehat{X}^* \cup \{v\}$ suffices for our purpose. This completes the proof of the lemma.

We fill the entry for $\mathcal{D}[i+1, v]$ as follows. Observe that

$$\mathcal{N}_{uv}^{i+1} = \bigcup_{w \in N^-(v)} \mathcal{D}[i, w] \bullet \{v\}.$$

We already have computed the family corresponding to $\mathcal{D}[i, w]$ for $w \in N^-(v)$. By Corollary 1, $|\hat{\mathcal{P}}_{uw}^i| \leq {\ell \choose i} 2^{o(\ell)}$ and thus $|\mathcal{N}_{uv}^{i+1}| \leq d^-(v) {\ell \choose i} 2^{o(\ell)}$. Furthermore, we can compute \mathcal{N}_{uv}^{i+1} in time $\mathcal{O}\left(d^-(v) {\ell \choose i} 2^{o(\ell)}\right)$. Now using Corollary 1, we compute $\widehat{\mathcal{N}}_{uv}^{i+1} \subseteq_{rep}^{\ell-i-1} \mathcal{N}_{uv}^{i+1}$ in time $\mathcal{T}_{um}(t, i+1, \ell-i-1)$, where $t = d(v) {\ell \choose i} 2^{o(\ell)}$. By Claim 5.1, we know that $\mathcal{N}_{uv}^{i+1} \subseteq_{rep}^{\ell-i-1} \mathcal{P}_{uv}^{i+1}$.

Thus Lemma 3.1 implies that $\widehat{\mathcal{N}}_{uv}^{i+1} = \widehat{\mathcal{P}}_{uv}^{i+1} \subseteq_{rep}^{\ell-i-1} \mathcal{P}_{uv}^{i+1}$. We assign this family to $\mathcal{D}[i+1,v]$. This completes the description and the correctness of the algorithm. We give ordering to the vertices of the sets in $\widehat{\mathcal{P}}_{uv}^p$ in the following way so that it corresponds to a directed (undirected) path in D. We keep the sets in the order in which they are built using the \bullet operation. That is, we can view these sets as strings and \bullet operation as concatenation. Then every ordered set in our family represents a path in the graph. The running time of the algorithm is bounded by

$$\mathcal{O}\left(\sum_{i=2}^{p}\sum_{j=1}^{n-1}\mathcal{T}_{um}\left(d^{-}(v_{j})\binom{\ell}{i-1}2^{o(\ell)}, i, \ell-i\right)\right)$$

$$= \mathcal{O}\left(\sum_{i=2}^{p}\sum_{j=1}^{n-1}d^{-}(v_{j})\binom{\ell}{i-1}\left(\frac{\ell}{\ell-i}\right)^{\ell-i}2^{o(\ell)}\log n\right)$$

$$= \mathcal{O}\left(2^{o(\ell)}\log n\sum_{i=2}^{p}\sum_{j=1}^{n-1}d^{-}(v_{j})\binom{\ell}{i-1}\left(\frac{\ell}{\ell-i}\right)^{\ell-i}\right)$$

$$= \mathcal{O}\left(2^{o(\ell)}m\log n\max_{i\in[p]}\left\{\binom{\ell}{i-1}\left(\frac{\ell}{\ell-i}\right)^{\ell-i}\right\}\right)$$

This completes the proof

Finally, we are ready to state the main result of this section.

Theorem 7. LONG DIRECTED CYCLE can be solved in time $\mathcal{O}(8^{k+o(k)}mn^2)$.

Proof. Let D be a directed graph. We solve the problem by applying the structural characterization proved in Lemma 5.1. By Lemma 5.1, D has a directed cycle of length at least k if and only if there exists a pair of vertices $u, v \in V(D)$ and a path P' with $V(P') \in \widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$ such that D has a directed cycle C containing P' as a subpath.

We first compute $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$ for all $u, v \in V(D)$. For that we apply Lemma 5.2 for each vertex $u \in V(D)$ with $\ell = 2k$ and p = k. Thus, we can compute $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^k$ for all $u, v \in V(D)$ in time $\mathcal{O}\left(8^{k+o(k)}mn\log n\right)$. Moreover, for every $X \in \widehat{\mathcal{P}}_{uv}^k$ we also compute a directed *uv*-path \mathcal{P}_X using vertices of X. Let

$$\mathcal{Q} = \bigcup_{u,v \in V(D)} \widehat{\mathcal{P}}_{uv}^k.$$

Now for every set $X \in \mathcal{Q}$ and the corresponding uv-path P_X with endpoint, we check if there is a uv-path in D avoiding all vertices of X but u and v. This check can be done by a standard graph traversal algorithm like BFS/DFS in time $\mathcal{O}(m+n)$. If we succeed in finding a path for at least one $X \in \mathcal{Q}$, we answer YES and return the corresponding directed cycle obtained by merging P_X and another path. Otherwise, if we did not succeed to find such a path for any of the sets $X \in \mathcal{Q}$, this means that there is no directed cycle of length at least k in D. The correctness of the algorithm follows from Lemma 5.1. By Corollary 1, the size of \mathcal{Q} is upper bounded by $n^2 \binom{2k}{k} 2^{o(k)} \leq n^2 4^{k+o(k)}$. Thus the overall running time of the algorithm is upper bounded by

$$\mathcal{O}(8^{k+o(k)}mn\log n + 4^{k+o(k)}(n^2m + n^3)).$$

This concludes the proof.

36

5.2 Faster Long Directed Cycle

In this subsection we design a faster algorithm for LONG DIRECTED CYCLE. In Subsection 5.1 we have seen an algorithm for LONG DIRECTED CYCLE where the running time mainly depend on the computation of representative families $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^q \mathcal{P}_{uv}^p$ for $2 \leq p \leq k$ and q = 2k - p. We used Theorem 4.6 with $x = \frac{p}{p+q}$ (i.e, Corollary 1) to compute representative families. The choice $x = \frac{p}{p+q}$ minimizes the size of representative family. But in fact, we can choose x that minimizes the running time instead.

Now we find out the choice of x which minimizes the computation of $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^q \mathcal{P}_{uv}^p$ for $2 \leq p \leq k$ and q = 2k - p. Let $s_{p,q}$ denote the size of $\widehat{\mathcal{P}}_{uv}^p$. We know that the computation of $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^q \mathcal{N}_{uv}^p \subseteq_{rep}^q \mathcal{P}_{uv}^p$ depends on $|\mathcal{N}_{uv}^p|$, which depends on the size of the representative families $\widehat{\mathcal{P}}_{uv}^{p-1}$. That is $|\mathcal{N}_{uv}^p| \leq s_{p-1,q+1} \cdot n$. Thus the value of $s_{p-1,q+1}$ and $s_{p,q}$ are "almost equal" and we denote it by $s_{p-1,q+1} \approx s_{p,q}$. By Theorem 6, the running time to compute $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^q \mathcal{N}_{uv}^p \subseteq_{rep}^q \mathcal{P}_{uv}^p$ is,

$$\mathcal{O}\left(|\mathcal{N}_{uv}^p| \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot \log n\right)$$

= $\mathcal{O}\left(s_{p,q} \cdot (1-x)^{-q} \cdot 2^{o(p+q)} \cdot n \log n\right)$
= $\mathcal{O}\left(x^{-p} \cdot (1-x)^{-2q} \cdot 2^{o(p+q)} \cdot n \log n\right)$

To minimize the above running time it is enough to minimize the function $f(x) = x^{-p} \cdot (1-x)^{-2q}$. Using methods from calculus we know that the value x^* of x for which $f'(x^*) = 0$ corresponds to a minimum value of the function f(x) if $f''(x^*) > 0$. The derivative of f(x) is, $f'(x) = -px^{-p-1}(1-x)^{-2q} + 2q \cdot x^{-p}(1-x)^{-2q-1}$. Now consider the value of x for which f'(x) = 0.

$$-px^{-p-1}(1-x)^{-2q} + 2q \cdot x^{-p}(1-x)^{-2q-1} = 0$$

$$-p(1-x) + 2q \cdot x = 0$$

$$x = \frac{p}{p+2q}$$

Set $x^* = \frac{p}{p+2q}$. To prove f(x) is minimized at x^* , it is enough to show that $f''(x^*) > 0$.

$$\begin{aligned} f'(x) &= -px^{-p-1}(1-x)^{-2q} + 2q \cdot x^{-p}(1-x)^{-2q-1} \\ &= x^{-p}(1-x)^{-2q}(-p \cdot x^{-1} + 2q \cdot (1-x)^{-1}) \\ &= f(x) \cdot (-p \cdot x^{-1} + 2q \cdot (1-x)^{-1}) \\ f''(x) &= f(x) \cdot (p \cdot x^{-2} + 2q \cdot (1-x)^{-2}) + f'(x) \cdot (-p \cdot x^{-1} + 2q \cdot (1-x)^{-1}) \\ f''(x^*) &= f(x^*) \cdot (p \cdot (x^*)^{-2} + 2q \cdot (1-(x^*))^{-2}) > 0 \end{aligned}$$

Hence the run time to compute $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^q \mathcal{P}_{uv}^p$ is minimized when $x = \frac{p}{p+2q}$.

Lemma 5.3. Let D be a directed graph with n vertices and m edges, $u \in V(D)$ and $M = (E, \mathcal{I})$ be an uniform matroid $U_{n,\ell}$ where E = V(D) and $\mathcal{I} = \{S \subseteq V(D) \mid |S| \leq \ell\}$. Then for every $v \in V(D) \setminus \{u\}$ and integer $2 \leq p \leq \ell$ there is an algorithm that computes a family $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^{\ell-p} \mathcal{P}_{uv}^p$ of size $\left(\frac{2\ell-p}{p}\right)^p \left(\frac{2\ell-p}{2\ell-2p}\right)^{\ell-p} \cdot 2^{o(\ell)}$ in time $\mathcal{O}\left(2^{o(\ell)} \cdot m \log n \cdot \max_{i \in [p]} \left\{ \left(\frac{2\ell-i}{i}\right)^i \left(\frac{2\ell-i}{2\ell-2i}\right)^{2\ell-2i} \right\} \right)$

Proof. The proof is same as the proof of Lemma 5.2, except the choice of x while applying Theorem 4.6 (instead of Corollary 1). As in the proof of Lemma 5.2, we have a dynamic programming table \mathcal{D} where the rows are indexed from integers in $\{2, \ldots, p\}$ and the columns

are indexed from vertices in $\{v_1, \ldots, v_{n-1}\}$. The entry $\mathcal{D}[i, v]$ will store the family $\widehat{\mathcal{P}}_{uv}^i \subseteq_{rep}^{\ell-i} \mathcal{P}_{uv}^i$. We fill the entries in the matrix \mathcal{D} in the increasing order of rows. For i = 2, $\mathcal{D}[2, v] = \{\{u, v\}\}$ if $uv \in A(D)$. Assume that we have filled all the entries until the row i. Let

$$\mathcal{N}_{uv}^{i+1} = \bigcup_{w \in N^-(v)} \widehat{\mathcal{P}}_{uw}^i \bullet \{v\}.$$

Due to Claim 5.1, we have that $\mathcal{N}_{uv}^{i+1} \subseteq_{rep}^{\ell-(i+1)} \mathcal{P}_{uv}^{i+1}$. Lemma 3.1 implies that $\widehat{\mathcal{N}}_{uv}^{i+1} = \widehat{\mathcal{P}}_{uv}^{i+1} \subseteq_{rep}^{\ell-i-1} \mathcal{P}_{uv}^{i+1}$. We assign this family to $\mathcal{D}[i+1,v]$.

Now we explain the computation of $\widehat{\mathcal{N}}_{uv}^{i+1} = \widehat{\mathcal{P}}_{uv}^{i+1}$. For any j, to compute $\widehat{\mathcal{N}}_{uv}^j = \widehat{\mathcal{P}}_{uv}^j$, we apply Theorem 6 with the value x_j for x, where

$$x_j = \frac{j}{j+2(\ell-j)} = \frac{j}{2\ell-j}$$

Let $s_{j,\ell-j}$ be the size of the representative family $\widehat{\mathcal{N}}_{uv}^j = \widehat{\mathcal{P}}_{uv}^j$ when we apply Theorem 6 with the value x_j . That is $s_{j,\ell-j} = (x_j)^{-j}(1-x_j)^{\ell-j} \cdot 2^{o(\ell)}$. Assume that we have computed $\widehat{\mathcal{P}}_{uw}^j$ of size $s_{j,\ell-j}$ and stored it in $\mathcal{D}[j,w]$ for all $j \leq i$ and $w \in \{v_1,\ldots,v_{n-1}\}$. Now consider the computation of $\widehat{\mathcal{N}}_{uv}^{i+1} = \widehat{\mathcal{P}}_{uv}^{i+1}$. We apply Theorem 6 with value x_{i+1} for x to compute $\widehat{\mathcal{N}}_{uv}^{i+1} \subseteq_{rep}^{\ell-(i+1)} \mathcal{N}_{uv}^{i+1}$. Since $\mathcal{N}_{uv}^{i+1} = \bigcup_{w \in N^-(v)} \widehat{\mathcal{P}}_{uw}^i \bullet \{v\}$, we have that

$$\begin{array}{rcl} \mathcal{N}_{uv}^{i+1} | &\leq & s_{i,\ell-i} \cdot d^{-}(v) \\ &\leq & (x_i)^{-i} (1-x_i)^{\ell-i} \cdot 2^{o(\ell)} d^{-}(v) \end{array}$$

By Theorem 6, the running time to compute $\widehat{\mathcal{N}}_{uv}^{i+1}$ is,

$$s_{i,\ell-i} \cdot (1 - x_{i+1})^{\ell - (i+1)} \cdot 2^{o(\ell)} \cdot d^{-}(v) \cdot \log n$$
(6)

To analyze the running time further we need the following claim.

Claim 5.2. For any 3 < i < p, $s_{i,\ell-i} \le e^2 \cdot (i+1) \cdot s_{i+1,\ell-i-1}$.

Proof. By applying the definition of s_i and x_{i+1} we get he following inequality.

$$\begin{aligned} \frac{s_{i,\ell-i}}{s_{i+1,\ell-i-1}} &= \frac{x_i^{-i}(1-x_i)^{-\ell+i}}{x_{i+1}^{-(i+1)}(1-x_{i+1})^{-\ell+(i+1)}} \\ &= \left(\frac{2\ell-i}{i}\right)^i \left(\frac{2\ell-i}{2\ell-2i}\right)^{\ell-i} \left(\frac{i+1}{2\ell-(i+1)}\right)^{i+1} \left(\frac{2\ell-2(i+1)}{2\ell-(i+1)}\right)^{\ell-(i+1)} \\ &= \left(\frac{2\ell-i}{2\ell-(i+1)}\right)^\ell \cdot \frac{(i+1)^{i+1}}{i^i} \cdot \frac{(2\ell-2(i+1))^{\ell-(i+1)}}{2\ell-2i)^{\ell-i}} \\ &\leq \left(1+\frac{1}{2\ell-(i+1)}\right)^{2\ell-(i+1)} \cdot (i+1) \cdot \left(1+\frac{1}{i}\right)^i \\ &\leq e^2 \cdot (i+1). \end{aligned}$$

In the last transition we used that $(1 + 1/x)^x < e$ for every x > 0.

From Equation 6 and Claim 5.2 we have that the running time for computing $\widehat{\mathcal{P}}_{uv}^p$ is bounded by

$$\mathcal{O}\left(\sum_{i=2}^{p}\sum_{j=1}^{n-1}s_{i,\ell-i}\cdot d^{-}(v_{j})\cdot (1-x_{i})^{-\ell+i}\cdot 2^{o(\ell)}\cdot \log n\right)$$
$$=\mathcal{O}\left(2^{o(\ell)}\cdot m\log n\cdot \max_{i\in[p]}\left\{\left(\frac{2\ell-i}{i}\right)^{i}\left(\frac{2\ell-i}{2\ell-2i}\right)^{2\ell-2i}\right\}\right)$$

The size of the family $\widehat{\mathcal{P}}_{uv}^p \subseteq_{rep}^{\ell-p} \mathcal{N}_{uv}^p \subseteq_{rep}^{\ell-p} \mathcal{P}_{uv}^p$ is,

$$s_{p,\ell-p} = (x_p)^{-p} (1-x_p)^{-\ell+p} \cdot 2^{o(\ell)} = \left(\frac{2\ell-p}{p}\right)^p \left(\frac{2\ell-p}{2\ell-2p}\right)^{\ell-p} \cdot 2^{o(\ell)}.$$

es the proof.

This completes the proof.

We now have a faster algorithm to compute the representative family $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^p$. Using Lemma 5.3, we can compute $\widehat{\mathcal{P}}_{uv}^k$, for all $v \in V(D) \setminus \{u\}$ in time

$$\mathcal{O}\left(2^{o(k)} \cdot m \log n \cdot \max_{i \in [p]} \left\{ \left(\frac{4k-i}{i}\right)^i \left(\frac{4k-i}{4k-2i}\right)^{4k-2i} \right\} \right).$$

Simple calculus shows that the maximum is attained for i = k. Hence the running time to compute $\widehat{\mathcal{P}}_{uv}^k$ for all $u, v \in V(D)$ is upper bounded by $\mathcal{O}(6.75^{k+o(k)}nm\log n)$. This yields an improved bound for the running time of our algorithm for LONG DIRECTED CYCLE.

We apply Lemma 5.3 for each $u \in V(D)$ with $\ell = 2k$ and p = k. Thus, we can compute $\widehat{\mathcal{P}}_{uv}^k \subseteq_{rep}^k \mathcal{P}_{uv}^p$ for all $u, v \in V(D)$ in time $\mathcal{O}(6.75^{k+o(k)}nm\log n)$. The size of the family $\widehat{\mathcal{P}}_{uv}^k$ for any $u, v \in V(D)$ is upper bounded by $\mathcal{O}(4.5^{k+o(k)})$. Thus, if we now loop over every set in the representative families and run a breadth first search, just as in the proof of Theorem 7, this will take at most $\mathcal{O}(6.75^{k+o(k)}nm\log^n + 4.5^{k+o(k)}(n^3 + n^2m))$ time. Hence we arrive at the following theorem.

Theorem 8. There is a $\mathcal{O}(6.75^{k+o(k)}mn^2)$ time algorithm for LONG DIRECTED CYCLE

5.3 Minimum Equivalent Graph

For a given digraph D, a subdigraph D' of D is said to be an *equivalent* subdigraph of D if for any pair of vertices $u, v \in V(D)$ if there is a directed path in D from u to v then there is also a directed path from u to v in D'. That is, reachability of vertices in D and D' is same. In this section we study a problem where given a digraph D the objective is to find an equivalent subdigraph of D' of D with as few arcs as possible. Equivalently, the objective is to remove the maximum number of arcs from a digraph D without affecting its reachability. More precisely the problem we study is as follows.

MINIMUM EQUIVALENT GRAPH (MEG) Input: A directed graph DTask: Find an equivalent subdigraph of D with the minimum number of arcs.

The following proposition is due to Moyles and Thompson [45], see also [4, Sections 2.3], reduces the problem of finding a minimum equivalent subdigraph of an arbitrary D to a strong digraph.

Proposition 5.1. Let D be a digraph on n vertices with strongly connected components C_1, \ldots, C_r . Given a minimum equivalent subdigraph C'_i for each C_i , $i \in [r]$, one can obtain a minimum equivalent subdigraph D' of D containing each of C'_i in $\mathcal{O}(n^{\omega})$ time.

Observe that for a strong digraph D any equivalent subdigraph is also strong. By Proposition 5.1, MEG reduces to the following problem.

MINIMUM STRONGLY CONNECTED SPANNING SUBGRAPH (MINIMUM SCSS) Input: A strongly connected directed graph DTask: Find a strong spanning subdigraph of D with the minimum number of arcs. It seems to be no established agreement in the literature on how to call these problems. MEG sometimes is also referred as MINIMUM EQUIVALENT DIGRAPH and MINIMUM EQUIVALENT SUBDIGRAPH, while MINIMUM SCSS is also called MINIMUM SPANNING STRONG SUBDIGRAPH (MSSS).

A digraph T is an *out-tree* (an *in-tree*) if T is an oriented tree with just one vertex s of in-degree zero (out-degree zero). The vertex s is the root of T. If an out-tree (in-tree) T is a spanning subdigraph of D, T is called an *out-branching* (an *in-branching*). We use the notation B_s^+ (B_s^-) to denote an out-branching (in-branching) rooted at s of the digraph.

It is known that a digraph is strong if and only if it contain an out-branching and an in-branching rooted at some vertex $v \in V(D)$ [4, Proposition 12.1.1].

Proposition 5.2. Let D be a strong digraph on n vertices, let v be an arbitrary vertex of V(D), and $\ell \leq n-2$ be a natural number. Then there exists a strong spanning subdigraph of D with at most $2n-2-\ell$ arcs if and only if D contains an in-branching B_v^- and an out-branching B_v^+ with root v so that $|A(B_v^+) \cap A(B_v^-)| \geq \ell$ (that is, they have at least ℓ common arcs).

Proposition 5.2 implies that the MINIMUM SCSS problem is equivalent to finding, for an arbitrary vertex $v \in V(D)$, an out-branching B_v^+ and an in-branching B_v^- that maximizes $|A(B_v^+) \cap A(B_v^-)|$. For our exact algorithm for MINIMUM SCSS we implement this equivalent version using representative sets.

Let D be a strong digraph and $s \in V(D)$ be a fixed vertex. For $v \in V(D)$ we use $\ln(v)$ and $\operatorname{Out}(v)$ to denote the sets of in-coming and out-going arcs incident with v. By D_s^- we denote the digraph obtained from D by deleting the arcs in $\operatorname{Out}(s)$. Similarly, by D_s^+ we denote the digraph obtained from D by deleting the arcs in $\ln(s)$.

We take two copies E_1, E_2 of A(D) (that is $E_i = \{e_i \mid e \in A(D)\}$), a copy E_3 of $A(D_s^+)$ and a copy E_4 of $A(D_s^-)$ and construct four matroids as follows. Let U(D) denote the underlying undirected graph of D. The first two matroids $M_1 = (E_1, \mathcal{I}_1), M_2 = (E_2, \mathcal{I}_2)$ are the graphic matroids on U(D). Observe that

$$A(D_s^+) = \biguplus_{v \in V(D_s^+)} \mathsf{In}(v) \text{ and } A(D_s^-) = \biguplus_{v \in V(D_s^-)} \mathsf{Out}(v).$$

Thus the arcs of D_s^+ can be partitioned into sets of in-arcs and similarly the arcs of D_s^- into sets of out-arcs. The other two matroids are the following partition matroids $M_3 = (E_3, \mathcal{I}_3)$, $M_4 = (E_4, \mathcal{I}_4)$, where

$$\mathcal{I}_3 = \{ I \mid I \subseteq A(D_s^+), \text{ for every } v \in V(D_s^+) = V(D), |I \cap \mathsf{ln}(v)| \le 1 \},\$$

and

$$\mathcal{I}_4 = \{ I \mid I \subseteq A(D_s^-), \text{ for every } v \in V(D_s^-) = V(D), |I \cap \mathsf{Out}(v)| \le 1 \}$$

We define the matroid $M = (E, \mathcal{I})$ as the direct sum $M = M_1 \oplus M_2 \oplus M_3 \oplus M_4$. Since each of M_i is a representable matroids over the same field (by Propositions 2.2 and 2.3), we have that M is also representable (Proposition 2.1). The reason we say that M_i is representable over the same field \mathbb{F} is that the graphic matroid is representable over any field and the partition matroids defined here are representable over a finite field of size $n^{\mathcal{O}(1)}$. So if we take \mathbb{F} as a finite field of size $n^{\mathcal{O}(1)}$ then M is representable over \mathbb{F} . The rank of this matroid is 4n - 4.

Let us note that for each arc $e \in A(D)$ which is not incident with s, we have four elements in the matroid M, corresponding to the copies of e in M_i , $i \in \{1, \ldots, 4\}$. We denote these elements by e_i , $i \in \{1, \ldots, 4\}$. For every edge $e \in A(D)$ incident with s, we have three corresponding elements. We denote them by e_1, e_2, e_3 , or e_1, e_2, e_4 , depending on the case when e is in- or out-arc for s. For $i \in \{1, \ldots, n-1\}$, we define

$$\mathcal{B}^{4i} = \Big\{ W \mid W \in \mathcal{I}, \ |W| = 4i, \ \forall \ e \in A(D) \text{ either } W \cap \{e_1, e_2, e_3, e_4\} = \emptyset \text{ or } \{e_1, e_2, e_3, e_4\} \subseteq W \Big\}.$$

For $W \in \mathcal{I}$, by A_W we denote the set of arcs $e \in A(D)$ such that $\{e_1, e_2, e_3, e_4\} \cap W \neq \emptyset$. Now we are ready to state the lemma that relates representative sets and the MINIMUM SCSS problem.

Lemma 5.4. Let D be a strong digraph on n vertices and $\ell \leq n-2$ be a natural number. Then there exists a strong spanning subdigraph D' of D with at most $2n - 2 - \ell$ arcs if and only if there exists a set $\hat{F} \in \hat{\mathcal{B}}^{4\ell} \subseteq_{rep}^{n'-4\ell} \mathcal{B}^{4\ell}$ such that D has a strong spanning subdigraph \bar{D} with $A_{\widehat{F}} \subseteq A(\bar{D})$. Here, n' = 4n - 4.

Proof. We only show the forward direction of the proof, the reverse direction is straightforward. Let D' be a strong spanning subdigraph of D with at most $2n - 2 - \ell$ arcs. Thus, by Proposition 5.2 we have that for any vertex $v \in V(D')$, there exists an out-branching B_v^+ and an in-branching B_v^- in D' such that $|A(B_v^+) \cap A(B_v^-)| \ge \ell$. Observe that the arcs in $A(B_v^+) \cap A(B_v^-)$ form an out-forest (in-forest). Let F' be an arbitrary subset of $A(B_v^+) \cap A(B_v^-)$ containing exactly ℓ arcs. Take $X = A(B_v^+) \setminus F'$ and $Y = A(B_v^-) \setminus F'$. Observe that X and Y need not be disjoint. Clearly, $|X| = |Y| = n - 1 - \ell$.

In matroid M, one can associate with D' an independent set $I_{D'}$ of size 4n - 4 as follows:

$$I_{D'} = \bigcup_{e \in F'} \{e_1, e_2, e_3, e_4\} \bigcup_{e \in X} \{e_1, e_3\} \bigcup_{e \in Y} \{e_2, e_4\}.$$

By our construction, we have that $I_{D'}$ is an independent set in \mathcal{I} and $|I_{D'}| = 4\ell + 4(n-1-\ell) = n'$. Let $F = \bigcup_{e \in F'} \{e_1, e_2, e_3, e_4\}$, $\bar{X} = \bigcup_{e \in X} \{e_1, e_3\}$ and $\bar{Y} = \bigcup_{e \in Y} \{e_2, e_4\}$. Then notice that $F \in \mathcal{B}^{4\ell}$ and $F \subset I_{D'}$. This implies that there exists a set $\hat{F} \in \hat{\mathcal{B}}^{4\ell} \subseteq_{rep}^{n'-4\ell} \mathcal{B}^{4\ell}$ such that $I_{\bar{D}} = \hat{F} \cup \bar{X} \cup \bar{Y} \in \mathcal{I}$. We show that D has a strong spanning subdigraph \bar{D} with $A_{\widehat{F}} \subseteq A(\bar{D})$. Let \bar{D} be the digraph with the vertex set V(D) and the arc set $A(\bar{D}) = X \cup Y \cup A_{\widehat{F}}$. Consider the following four sets.

- 1. Let $W_1 = \{e_1 \mid e \in X \cup A_{\widehat{F}}\}$ then we have that $W_1 \subseteq I_{\overline{D}}$ and thus $W_1 \in \mathcal{I}_1$. This together with the fact that $|W_1| = n 1$ implies that $X \cup A_{\widehat{F}}$ forms a spanning tree in U(D).
- 2. Let $W_2 = \{e_2 \mid e \in Y \cup A_{\widehat{F}}\}$. Similar to the first case, then $Y \cup A_{\widehat{F}}$ forms a spanning tree in U(D).
- 3. Let $W_3 = \{e_3 \mid e \in X \cup A_{\widehat{F}}\}$ then we have that $W_3 \subseteq I_{\overline{D}}$ and thus $W_3 \in \mathcal{I}_3$. This together with the fact that $|W_1| = |W_3| = n - 1$ and that $X \cup A_{\widehat{F}}$ is a spanning tree in U(D)implies that $X \cup A_{\widehat{F}}$ forms an out-branching rooted at s in D_s^+ .
- 4. Let $W_4 = \{e_3 \mid e \in Y \cup A_{\widehat{F}}\}$. Similar to the previous case, then $Y \cup A_{\widehat{F}}$ forms an in-branching rooted at s in D_s^- .

We have shown that D contains $A_{\widehat{F}}$ and has an out-branching and in-branching rooted at s. This implies that \overline{D} is the desired strong spanning subdigraph of D containing a set from $\widehat{\mathcal{B}}^{4\ell}$. This concludes the proof of the lemma.

Lemma 5.5. Let D be a strong digraph on n vertices and $\ell \leq n-2$ be a natural number. Then in time $\mathcal{O}\left(\max_{i \in [\ell]} {\binom{n'}{4i}}^{\omega} mn^2 \log n\right)$ we can compute $\widehat{\mathcal{B}}^{4\ell} \subseteq_{rep}^{n'-4\ell} \mathcal{B}^{4\ell}$ of size ${\binom{n'}{4\ell}}$. Here, n' = 4n - 4. Proof. We describe a dynamic programming based algorithm. Let \mathcal{D} be an array of size ℓ . The entry $\mathcal{D}[i]$ will store the family $\widehat{\mathcal{B}}^{4i} \subseteq_{rep}^{n'-4i} \mathcal{B}^{4\ell}$. We fill the entries in the array \mathcal{D} in the increasing order of its index, that is, from $0, \ldots, \ell$. For the base case define $\widehat{\mathcal{B}}^0 = \{\emptyset\}$ and let $W = \{\{e_1, e_2, e_3, e_4\} | e \in A(D)\}$. Given that $\mathcal{D}[i]$ is filled for all $i' \leq i$, we fill $\mathcal{D}[i+1]$ as follows. Define $\mathcal{N}^{4(i+1)} = (\widehat{\mathcal{B}}^{4i} \bullet W) \cap \mathcal{I}$.

Claim 5.3. For all $0 \le i \le \ell - 1$, $\mathcal{N}^{4(i+1)} \subseteq_{rep}^{n'-4(i+1)} \mathcal{B}^{4(i+1)}$.

Proof. Let $S \in \mathcal{B}^{4(i+1)}$ and Y be a set of size n' - 4(i+1) such that $S \cap Y = \emptyset$ and $S \cup Y \in \mathcal{I}$. We will show that there exists a set $\hat{S} \in \mathcal{N}^{4(i+1)}$ such that $\hat{S} \cap Y = \emptyset$ and $\hat{S} \cup Y \in \mathcal{I}$. This will imply the desired result.

Let $e \in A(D)$ such that $\{e_1, e_2, e_3, e_4\} \subseteq S$. Define $S^* = S \setminus \{e_1, e_2, e_3, e_4\}$ and $Y^* = Y \cup \{e_1, e_2, e_3, e_4\}$. Since $S \cup Y \in \mathcal{I}$ we have that $S^* \in \mathcal{I}$ and $Y^* \in \mathcal{I}$. Observe that $S^* \in \mathcal{B}^{4i}$, $S^* \cup Y^* \in \mathcal{I}$ and the size of Y^* is n' - 4i. This implies that there exists \widehat{S}^* in $\widehat{\mathcal{B}}^{4i} \subseteq_{rep}^{n'-4i} \mathcal{B}^{4\ell}$ such that $\widehat{S}^* \cup Y^* \in \mathcal{I}$. Thus $\widehat{S}^* \cup \{e_1, e_2, e_3, e_4\} \in \mathcal{I}$ and also in $\widehat{\mathcal{B}}^{4i} \bullet W$ and thus in $\mathcal{N}^{4(i+1)}$. Taking $\widehat{S} = \widehat{S}^* \cup \{e_1, e_2, e_3, e_4\}$ suffices for our purpose. This completes the proof of the claim. \Box

We fill the entry for $\mathcal{D}[i+1]$ as follows. Observe that $\mathcal{N}_{uv}^{4(i+1)} = (\mathcal{D}[i,w] \bullet W) \cap \mathcal{I}$. We already have computed the family corresponding to $\mathcal{D}[i]$. By Theorem 1, $|\widehat{\mathcal{B}}^{4i}| \leq \binom{n'}{4i}$ and thus $|\mathcal{N}^{4(i+1)}| \leq 4m\binom{n'}{4i}$. Furthermore, we can compute $\mathcal{N}^{4(i+1)}$ in time $\mathcal{O}\left(mn\binom{n'}{4i}\right)$. Now using Theorem 1, we can compute $\widehat{\mathcal{N}}^{4(i+1)} \subseteq_{rep}^{n'-4(i+1)} \mathcal{N}^{4(i+1)}$ in time $\mathcal{T}_{rm}(t, 4i+4, n'-4(i+1))$, where $t = 4m\binom{n'}{4i}$.

By Claim 5.3 we know that $\mathcal{N}^{4(i+1)} \subseteq_{rep}^{n'-4(i+1)} \mathcal{B}^{4(i+1)}$. Thus Lemma 3.1 implies that $\widehat{\mathcal{N}}^{4(i+1)} = \widehat{\mathcal{B}}^{4(i+1)} \subseteq_{rep}^{n'-4(i+1)} \mathcal{B}^{4(i+1)}$. We assign this family to $\mathcal{D}[i+1]$. This completes the description and the correctness of the dynamic programming. The field size for uniform matroids are upper bounded by $n^{\mathcal{O}(1)}$ and thus we can perform all the field operations in time $\mathcal{O}(\log n)$. Thus, the running time of this algorithm is upper bounded by

$$\mathcal{O}\left(\sum_{i=1}^{\ell} \mathcal{T}_{rm}\left(4m\binom{n'}{4(i-1)}, 4i, n'-4i\right)\right) = \mathcal{O}\left(\max_{i\in[\ell]}\binom{n'}{4i}^{\omega} m\log n\right).$$

This completes the proof.

Lemma 5.6. MINIMUM SCSS can be solved in time $\mathcal{O}(2^{4\omega n}mn)$.

Proof. Let us fix n' = 4n - 4. Proposition 5.2 implies that the MINIMUM SCSS problem is equivalent to finding, for an arbitrary vertex $s \in V(D)$, an out-branching B_v^+ and an inbranching B_v^- that maximizes $|A(B_v^+) \cap A(B_v^-)|$. We guess the value of $|A(B_v^+) \cap A(B_v^-)|$ and let this be ℓ . By Lemma 5.4, there exists a strong spanning subdigraph D' of D with at most $2n - 2 - \ell$ arcs if and only if there exists a set $\hat{F} \in \hat{\mathcal{B}}^{4\ell} \subseteq_{rep}^{n'-4\ell} \mathcal{B}^{4\ell}$ such that D has a strong spanning subdigraph \bar{D} with $A_{\widehat{F}} \subseteq A(\bar{D})$. Recall that for $X \in \mathcal{I}$, by A_X we denote the set of arcs $e \in A(D)$ such that $\{e_1, e_2, e_3, e_4\} \cap X \neq \emptyset$. Now using Lemma 5.5 we compute $\hat{\mathcal{B}}^{4\ell} \subseteq_{rep}^{n'-4\ell} \mathcal{B}^{4\ell}$ in time $\mathcal{O}\left(\max_{i \in [\ell]} {n' \choose 4i}^{\omega} m \log n\right)$.

For every $\widehat{F} \in \widehat{\mathcal{B}}^{4\ell}$ we test whether $A_{\widehat{F}}$ can be extended to an out-branching in D_s^+ and to an in-branching in D_s^- . We can do it in $\mathcal{O}(n(n+m))$ -time by putting weights 0 to the arcs of $A_{\widehat{F}}$ and weights 1 to all remaining arcs and then by running the classical algorithm of Edmonds [19]. Since $\ell \leq n-2$, the running time of this algorithm is upper bounded by $\mathcal{O}(2^{4\omega n}mn)$. This concludes the proof. Finally, we are ready to prove the main result of this section

Theorem 9. MINIMUM EQUIVALENT GRAPH can be solved in time $\mathcal{O}(2^{4\omega n}mn)$.

Proof. Given an arbitrary digraph D we first find its strongly connected components C_1, \ldots, C_s . Now on each C_i , we apply Lemma 5.6 and obtain a minimum equivalent subdigraph C'_i . After this we apply Proposition 5.1 and obtain a minimum equivalent subdigraph of D. Since all the steps except Lemma 5.6 takes polynomial time we get the desired running time. This completes the proof.

A weighted variant of MINIMUM EQUIVALENT GRAPH has also been studied in literature. More precisely the problem is defined as follows.

MINIMUM WEIGHT EQUIVALENT GRAPH (MWEG) **Input**: A directed graph D and a weight function $w : A(D) \to \mathbb{N}$. **Task**: Find a minimum weight equivalent subdigraph of D.

MWEG can be solved along the same line as MEG but to do this we need to use the notion of min q-representative family and use Theorem 3 instead of Theorem 1. These changes give us the following theorem.

Theorem 10. MINIMUM WEIGHT EQUIVALENT GRAPH can be solved in time $\mathcal{O}(2^{4\omega n}mn\log W)$. Here, W is the maximum value assigned by the weight function $w : A(D) \to \mathbb{N}$.

5.4 Dynamic Programming over graphs of bounded treewidth

In this section we discuss deterministic algorithms for "connectivity problems" such as HAMIL-TONIAN PATH, STEINER TREE, FEEDBACK VERTEX SET parameterized by the treewidth of the input graph. The algorithms are based on Theorem 1 and use graphic matroids to take care of connectivity constraints. The approach is generic and can be used whenever all the relevant information about a "partial solution" can be encoded as an independent set of a specific linear matroid. We exemplify the approach on the STEINER TREE problem.

STEINER TREE **Input**: An undirected graph G with a set of terminals $T \subseteq V(G)$, and a weight function $w : E(G) \to \mathbb{N}$. **Task**: Find a subtree in G of minimum weight spanning all vertices of T.

5.4.1 Treewidth

Let G be a graph. A tree-decomposition of a graph G is a pair $(\mathbb{T}, \mathcal{X} = \{X_t\}_{t \in V(\mathbb{T})})$ such that

- $\cup_{t \in V(\mathbb{T})} X_t = V(G),$
- for every edge $xy \in E(G)$ there is a $t \in V(\mathbb{T})$ such that $\{x, y\} \subseteq X_t$, and
- for every vertex $v \in V(G)$ the subgraph of \mathbb{T} induced by the set $\{t \mid v \in X_t\}$ is connected.

The width of a tree decomposition is $\max_{t \in V(\mathbb{T})} |X_t| - 1$ and the treewidth of G is the minimum width over all tree decompositions of G and is denoted by $\mathbf{tw}(G)$.

A tree decomposition $(\mathbb{T}, \mathcal{X})$ is called a *nice tree decomposition* if \mathbb{T} is a tree rooted at some node r where $X_r = \emptyset$, each node of \mathbb{T} has at most two children, and each node is of one of the following kinds:

- 1. Introduce node: a node t that has only one child t' where $X_t \supset X_{t'}$ and $|X_t| = |X_{t'}| + 1$.
- 2. Forget node: a node t that has only one child t' where $X_t \subset X_{t'}$ and $|X_t| = |X_{t'}| 1$.
- 3. Join node: a node t with two children t_1 and t_2 such that $X_t = X_{t_1} = X_{t_2}$.
- 4. **Base node**: a node t that is a leaf of \mathbb{T} , is different than the root, and $X_t = \emptyset$.

Notice that, according to the above definition, the root r of \mathbb{T} is either a forget node or a join node. It is well known that any tree decomposition of G can be transformed into a nice tree decomposition maintaining the same width in linear time [32]. We use G_t to denote the graph induced by the vertex set $\bigcup_{t'} X_{t'}$, where t' ranges over all descendants of t, including t. By $E(X_t)$ we denote the edges present in $G[X_t]$. We use H_t to denote the graph on vertex set $V(G_t)$ and the edge set $E(G_t) \setminus E(X_t)$. For clarity of presentation we use the term nodes to refer to the vertices of the tree \mathbb{T} .

5.4.2 Steiner Tree parameterized by treewidth

Let G be an input graph of the STEINER TREE problem. Throughout this section, we say that $E' \subseteq E(G)$ is a *solution* if the subgraph induced on this edge set is connected and it contains all the terminal vertices. We call $E' \subseteq E(G)$ an *optimal solution* if E' is a solution of the minimum weight. Let \mathscr{S} be the family of edge subsets such that every edge subset corresponds to an optimal solution. That is,

 $\mathscr{S} = \{ E' \subseteq E(G) \mid E' \text{ is an optimal solution} \}.$

We start with few definitions that will be useful in explaining the algorithm. Let $(\mathbb{T}, \mathcal{X})$ be a tree decomposition of G of width **tw**. Let t be a node of $V(\mathbb{T})$. By \mathcal{S}_t we denote the family of edge subsets of $E(H_t)$, $\{E' \subseteq E(H_t)\}$, that satisfies the following properties.

- Either E' is a solution (that is, the subgraph formed by this edge set is connected and contains all the terminal vertices); or
- every vertex of $(T \cap V(G_t)) \setminus X_t$ is incident with some edge from E', and every connected component of the graph induced by E' contains a vertex from X_t .

We call S_t a family of partial solutions for t. We denote by K^t a complete graph on the vertex set X_t . For an edge subset $E^* \subseteq E(G)$ and a bag X_t corresponding to a node t, we define the following.

- 1. Set $\partial^t(E^*) = X_t \cap V(E^*)$, the set of endpoints of E^* in X_t .
- 2. Let G^* be the subgraph of G on the vertex set V(G) and the edge set E^* . Let C'_1, \ldots, C'_{ℓ} be the connected components of G^* such that for all $i \in [\ell], C'_i \cap X_t \neq \emptyset$. Let $C_i = C'_i \cap X_t$. Observe that C_1, \ldots, C_{ℓ} is a partition of $\partial^t(E^*)$. By $F(E^*)$ we denote a forest $\{Q_1, \ldots, Q_{\ell}\}$ where each Q_i is an arbitrary spanning tree of $K^t[C_i]$. For an example, since $K^t[C_i]$ is a complete graph we could take Q_i as a star. The purpose of $F(E^*)$ is to keep track for the vertices in C_i whether they are in the same connected component of G^* .
- 3. We define $w(F(E^*)) = w(E^*)$.

Our description of the algorithm slightly deviates from the usual table look-up based expositions of dynamic programming algorithms on graphs of bounded treewidth. With every node t of \mathbb{T} , we associate a subgraph of G. In our case it will be H_t . For every node t, rather than keeping a table, we keep a family of partial solutions for the graph H_t . That is, for every optimal solution $L \in \mathscr{S}$ and its intersection $L_t = E(H_t) \cap L$ with the graph H_t , we have some partial solution in the family that is "as good as L_t ". More precisely, we have some partial solution, say \hat{L}_t in our family such that $\hat{L}_t \cup L_R$ is also an optimum solution for the whole graph. Here, $L_R = L \setminus L_t$. As we move from one node t in the decomposition tree to the next node t' the graph H_t changes to $H_{t'}$, and so does the set of partial solutions. The algorithm updates its set of partial solutions accordingly. Here matroids come into play: in order to bound the size of the family of partial solutions that the algorithm stores at each node we employ Theorem 3 for graphic matroids. More details are given in the proof of the following theorem, which is the main result of this section.

Theorem 11. Let G be an n-vertex graph given together with its tree decomposition of width **tw**. Then STEINER TREE on G can be solved in time $\mathcal{O}((1+2^{\omega+1})^{\mathbf{tw}}\mathbf{tw}^{\mathcal{O}(1)}n)$.

Proof. We first outline an algorithm with running time $\mathcal{O}((1+2^{\omega+1})^{\mathbf{tw}}\mathbf{tw}^{\mathcal{O}(1)}n^2)$ for a simple exposition. Later we point out how we can remove the extra factor of n at the cost of a factor polynomial in \mathbf{tw} .

For every node t of \mathbb{T} and subset $Z \subseteq X_t$, we store a family of edge subsets $\widehat{\mathcal{S}}_t[Z]$ of H_t satisfying the following correctness invariant.

Correctness Invariant: For every $L \in \mathscr{S}$ we have the following. Let $L_t = E(H_t) \cap L$, $L_R = L \setminus L_t$, and $Z = \partial^t(L)$. Then there exists $\hat{L}_t \in \hat{\mathcal{S}}_t[Z]$ such that $w(\hat{L}_t) \leq w(L_t)$, $\hat{L} = \hat{L}_t \cup L_R$ is a solution, and $\partial^t(\hat{L}) = Z$. Observe that since $w(\hat{L}_t) \leq w(L_t)$ and $L \in \mathscr{S}$, we have that $\hat{L} \in \mathscr{S}$.

We process the nodes of the tree \mathbb{T} from base nodes to the root node while doing the dynamic programming. Throughout the process we maintain the correctness invariant, which will prove the correctness of the algorithm. However, our main idea is to use representative sets to obtain $\hat{\mathcal{S}}_t[Z]$ of small size. That is, given the set $\hat{\mathcal{S}}_t[Z]$ that satisfies the correctness invariant, we use Theorem 3 to obtain a subset $\hat{\mathcal{S}}'_t[Z]$ of $\hat{\mathcal{S}}_t[Z]$ that also satisfies the correctness invariant and has size upper bounded by $2^{|Z|}$. Thus, we maintain the following size invariant.

Size Invariant: After node t of \mathbb{T} is processed by the algorithm, for every $Z \subseteq X_t$ we have that $|\widehat{\mathcal{S}}_t[Z]| \leq 2^{|Z|}$.

The new ingredient of the dynamic programming algorithm for STEINER TREE is the use of Theorem 3 to compute $\hat{S}_t[Z]$ maintaining the size invariant. The next lemma shows how to implement it.

Lemma 5.7 (Shrinking Lemma). Let t be a node of \mathbb{T} , and let $Z \subseteq X_t$ be a set of size k. Furthermore, let $\widehat{\mathcal{S}}_t[Z]$ be a family of edge subsets of H_t satisfying the correctness invariant. If $|\widehat{\mathcal{S}}_t[Z]| = \ell$, then in time $\mathcal{O}\left(2^{k(\omega-1)}k^{\mathcal{O}(1)}\ell \cdot n\right)$ we can compute $\widehat{\mathcal{S}}'_t[Z] \subseteq \widehat{\mathcal{S}}_t[Z]$ satisfying correctness and size invariants.

Proof. We start by associating a matroid with node t and the set $Z \subseteq X_t$ as follows. We consider a graphic matroid $M = (E, \mathcal{I})$ on $K^t[Z]$. Here, the element set E of the matroid is the edge set $E(K^t[Z])$ and the family of independent sets \mathcal{I} consists of spanning forests of $K^t[Z]$.

Let $\widehat{\mathcal{S}}_t[Z] = \{E_1^t, \ldots, E_\ell^t\}$ and let $\mathcal{N} = \{F(E_1^t), \ldots, F(E_\ell^t)\}$ be the set of forests in $K^t[Z]$ corresponding to the edge subsets in $\widehat{\mathcal{S}}_t[Z]$. For $i \in \{1, \ldots, k-1\}$, let \mathcal{N}_i be the family of forests of \mathcal{N} with *i* edges. For each family \mathcal{N}_i we apply Theorem 3 and compute its min (k-1-i)-representative. That is,

$$\mathcal{N}_i \subseteq_{minrep}^{k-1-i} \mathcal{N}_i$$

Let $\widehat{\mathcal{S}}'_t[Z] \subseteq \widehat{\mathcal{S}}_t[Z]$ be such that for every $E_j^t \in \widehat{\mathcal{S}}'_t[Z]$ we have that $F(E_j^t) \in \bigcup_{i=1}^{k-1} \widehat{\mathcal{N}}_i$. By Theorem 3, $|\widehat{\mathcal{S}}'_t[Z]| \leq \sum_{i=1}^{k-1} {k \choose i} \leq 2^k$. Now we show that $\widehat{\mathcal{S}}'_t[Z]$ maintains the correctness invariant.

Let $L \in \mathscr{S}$ and let $L_t = E(H_t) \cap L$, $L_R = L \setminus L_t$ and $Z = \partial^t(L)$. Then there exists $E_j^t \in \widehat{\mathcal{S}}_t[Z]$ such that $w(E_j^t) \leq w(L_t)$, $\widehat{L} = E_j^t \cup L_R$ is an optimal solution and $\partial^t(\widehat{L}) = Z$. Consider the forest $F(E_j^t)$. Suppose its size is *i*, then $F(E_j^t) \in \mathcal{N}_i$. Now let $F(L_R)$ be the forest corresponding to L_R with respect to the bag X_t . Since \widehat{L} is a solution, we have that $F(E_j^t) \cup F(L_R)$ is a spanning tree in $K^t[Z]$. Since $\widehat{\mathcal{N}}_i \subseteq_{minrep}^{k-1-i} \mathcal{N}_i$, we have that there exists a forest $F(E_h^t) \in \widehat{\mathcal{N}}_i$ such that $w(F(E_h^t)) \leq w(F(E_i^t))$ and $F(E_h^t) \cup F(L_R)$ is a spanning tree in $K^t[Z]$. Thus, we know that $E_h^t \cup L_R$ is an optimum solution and $E_h^t \in \widehat{\mathcal{S}}_t'[Z]$. This proves that $\widehat{\mathcal{S}}_t'[Z]$ maintains the invariant.

The running time to compute $\widehat{\mathcal{S}}_t[Z]$ is dominated by:

$$\mathcal{O}\left(\sum_{i=1}^{k-1} \binom{k-1}{i}^{\omega-1} k^{\mathcal{O}(1)} \ell\right) = \mathcal{O}\left(2^{k(\omega-1)} k^{\mathcal{O}(1)} \ell\right).$$

For a given edge set we also need to compute the forest and that can take $\mathcal{O}(n)$ time.

In our algorithm the size of $\hat{\mathcal{S}}_t[Z]$ can grow larger than $2^{|Z|}$ in intermediate steps but it will be at most $4^{|Z|}$ and thus we can use Shrinking Lemma (Lemma 5.7) to reduce its size efficiently.

We now return to the dynamic programming algorithm over the tree-decomposition $(\mathbb{T}, \mathcal{X})$ of G and prove that it maintains the correctness invariant. We assume that $(\mathbb{T}, \mathcal{X})$ is a nice tree-decomposition of G. By $\hat{\mathcal{S}}_t$ we denote $\bigcup_{Z \subseteq X_t} \hat{\mathcal{S}}_t[Z]$ (also called a *representative family of partial solutions*). We show how $\hat{\mathcal{S}}_t$ is obtained by doing dynamic programming from base node to the root node.

Base node t. Here the graph H_t is empty and thus we take $\hat{S}_t = \emptyset$.

Introduce node t with child t'. Here, we know that $X_t \supset X_{t'}$ and $|X_t| = |X_{t'}| + 1$. Let v be the vertex in $X_t \setminus X_{t'}$. Furthermore observe that $E(H_t) = E(H_{t'})$ and v is degree zero vertex in H_t . Thus the graph H_t only differs from $H_{t'}$ at a isolated vertex v. Since we have not added any edge to the new graph, the family of solutions, which contains edge-subsets, does not change. Thus, we take $\hat{S}_t = \hat{S}_{t'}$. Formally, we take $\hat{S}_t[Z] = \hat{S}_{t'}[Z \setminus \{v\}]$. Since, H_t and $H_{t'}$ have same set of edges the invariant is vacuously maintained.

Forget node t with child t'. Here we know $X_t \subset X_{t'}$ and $|X_t| = |X_{t'}| - 1$. Let v be the vertex in $X_{t'} \setminus X_t$. Let $\mathcal{E}_v[Z]$ denote the set of edges between v and the vertices in $Z \subseteq X_t$. Let $\mathcal{P}_v[Z] = \{Y \mid \emptyset \neq Y \subseteq \mathcal{E}_v[Z]\}$. Observe that $E(H_t) = E(H_{t'}) \cup \mathcal{E}_v[X_t]$. Before we define things formally, observe that in this step the graphs H_t and $H_{t'}$ differ by at most tw edges - the edges with one endpoint in v and the other in X_t . We go through every possible way an optimal solution can intersect with these newly added edges. The idea is that for every edge subset in our family of partial solutions we make several new partial solutions, one each for every subset of newly added edges. More formally the new set of partial solutions is defined as follows.

$$\widehat{\mathcal{S}}_{t}[Z] = \begin{cases} \left(\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_{v}[Z]\right) \cup \left\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_{t}\right\} & \text{if } v \in T \\ \left(\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_{v}[Z]\right) \cup \left\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_{t}\right\} \cup \widehat{\mathcal{S}}_{t'}[Z] & \text{if } v \notin T \end{cases} \end{cases}$$

Recall that for two families \mathcal{A} and \mathcal{B} , we defined $\mathcal{A} \circ \mathcal{B} = \{A \cup B : A \in \mathcal{A} \land B \in \mathcal{B}\}$. Now we claim that $\widehat{\mathcal{S}}_t[Z] \subseteq \mathcal{S}_t$. Towards the proof we first show that $\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_v[Z] \subseteq \mathcal{S}_t$. Let $E' \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_v[Z]$. Note that $E' \cap \mathcal{E}_v[Z] \neq \emptyset$. If E' is a solution tree then $E' \in \mathcal{S}_t$ and we are done. Since $E' \setminus \mathcal{E}_v[Z] \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \subseteq \mathcal{S}_{t'}$, every vertex of $(T \cap V(G_t)) \setminus (X_t \cup \{v\})$ is incident with some edge from E'. Since $E' \cap \mathcal{E}_v[Z] \neq \emptyset$, there exists an edge in E' which is incident to v. This implies that every vertex of $(T \cap V(G_t)) \setminus X_t$ is incident with some edge from E'. Now consider any connected component C in G[E']. If $v \notin V(C)$, then C contains a vertex from $X_{t'} \setminus \{v\} = X_t$, because $E' \setminus \mathcal{E}_v[Z] \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \subseteq \mathcal{S}_{t'}$. If $v \in V(C)$, then Ccontains a vertex from X_t because $E' \cap \mathcal{E}_v[Z] \neq \emptyset$. Thus we have shown that $E' \in \mathcal{S}_t$. It is easy to see that $\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_t\} \subseteq \mathcal{S}_t$. If $v \notin T$ then $\widehat{\mathcal{S}}_{t'}[Z] \subseteq \mathcal{S}_t$, because $\widehat{\mathcal{S}}_{t'}[Z] \subseteq \mathcal{S}_{t'}$ and $X_t = X_{t'} \setminus \{v\}$.

Now we show that $\widehat{\mathcal{S}}_t$ maintains the invariant of the algorithm. Let $L \in \mathscr{S}$.

- 1. Let $L_t = E(H_t) \cap L$ and $L_R = L \setminus L_t$. Furthermore, edges of L_t can be partitioned into $L_{t'} = E(H_{t'}) \cap L$ and $L_v = L_t \setminus L_{t'}$. That is, $L_t = L_{t'} \uplus L_v$.
- 2. Let $Z = \partial^t(L)$ and $Z' = \partial^{t'}(L)$.

By the property of $\widehat{\mathcal{S}}_{t'}$, there exists a $\widehat{L}_{t'} \in \widehat{\mathcal{S}}_{t'}[Z']$ such that

$$L \in \mathscr{S} \iff L_{t'} \uplus L_v \uplus L_R \in \mathscr{S}$$
$$\iff \hat{L}_{t'} \uplus L_v \uplus L_R \in \mathscr{S}$$
(7)

and $\partial^{t'}(L) = \partial^{t'}(\hat{L}_{t'} \uplus L_v \uplus L_R) = Z'.$

We put $\hat{L}_t = \hat{L}_{t'} \cup L_v$ and $\hat{L} = \hat{L}_t \cup L_R$. We know show that $\hat{L}_t \in \hat{\mathcal{S}}_t[Z]$. Towards this just note that since Z' = Z or $Z' = Z \cup \{v\}$, we have that $\hat{\mathcal{S}}_t[Z]$ contains $\hat{\mathcal{S}}_{t'}[Z'] \circ \{L_v\}$. By (7), $\hat{L} \in \mathscr{S}$. Finally, we need to show that $\partial^t(\hat{L}) = Z$. Towards this just note that $\partial^t(\hat{L}) = Z' \setminus \{v\} = Z$. This concludes the proof for the fact that $\hat{\mathcal{S}}_t$ maintains the correctness invariant.

Join node t with two children t_1 and t_2 . Here, we know that $X_t = X_{t_1} = X_{t_2}$. Also we know that the edges of H_t is obtained by the union of edges of H_{t_1} and H_{t_2} which are disjoint. Of course they are separated by the vertices in X_t . A natural way to obtain a family of partial solutions for H_t is that we take the union of edges subsets of the families stored at nodes t_1 and t_2 . This is exactly what we do. Let

$$\widehat{\mathcal{S}}_t[Z] = \widehat{\mathcal{S}}_{t_1}[Z] \circ \widehat{\mathcal{S}}_{t_2}[Z].$$

Now we show that $\widehat{\mathcal{S}}_t$ maintains the invariant. Let $L \in \mathscr{S}$.

1. Let $L_t = E(H_t) \cap L$ and $L_R = L \setminus L_t$. Furthermore edges of L_t can be partitioned into those belonging to H_{t_1} and those belonging to H_{t_2} . Let $L_{t_1} = E(H_{t_1}) \cap L$ and $L_{t_2} = E(H_{t_2}) \cap L$. Observe that since $E(H_{t_1}) \cap E(H_{t_2}) = \emptyset$, we have that $L_{t_1} \cap L_{t_2} = \emptyset$. Also observe that $L_t = L_{t_1} \uplus L_{t_2}$.

2. Let
$$Z = \partial^t(L)$$
. Since $X_t = X_{t_1} = X_{t_2}$ this implies that $Z = \partial^t(L) = \partial^{t_1}(L) = \partial^{t_2}(L)$.

Now observe that

$$\begin{array}{lll} L \in \mathscr{S} & \Longleftrightarrow & L_{t_1} \uplus L_{t_2} \uplus L_R \in \mathscr{S} \\ & \Leftrightarrow & \hat{L}_{t_1} \uplus L_{t_2} \uplus L_R \in \mathscr{S} & (\text{by the property of } \widehat{\mathcal{S}}_{t_1} \text{ we have that } \hat{L}_{t_1} \in \widehat{\mathcal{S}}_{t_1}[Z]) \\ & \Leftrightarrow & \hat{L}_{t_1} \uplus \hat{L}_{t_2} \uplus L_R \in \mathscr{S} & (\text{by the property of } \widehat{\mathcal{S}}_{t_2} \text{ we have that } \hat{L}_{t_2} \in \widehat{\mathcal{S}}_{t_2}[Z]) \end{array}$$

We put $\hat{L}_t = \hat{L}_{t_1} \cup \hat{L}_{t_2}$. By the definition of $\hat{\mathcal{S}}_t[Z]$, we have that $\hat{L}_{t_1} \cup \hat{L}_{t_2} \in \hat{\mathcal{S}}[Z]$. The above inequalities also show that $\hat{L} = \hat{L}_t \cup L_R \in \mathscr{S}$. It remains to show that $\partial^t(\hat{L}) = Z$. Since $\partial^{t_1}(L) = Z$, we have that $\partial^{t_1}(\hat{L}_{t_1} \uplus L_{t_2} \uplus L_R) = Z$. Now since $X_{t_1} = X_{t_2}$ we have that $\partial^{t_2}(\hat{L}_{t_1} \uplus L_{t_2} \uplus L_R) = Z$. Now since $X_{t_2} = X_t$, we conclude that $\partial^t(\hat{L}_{t_1} \uplus \hat{L}_{t_2} \uplus L_R) = Z$. This concludes the proof of correctness invariant.

Root node r. Here, $X_r = \emptyset$. We go through all the solution in $\widehat{S}_r[\emptyset]$ and output the one with the minimum weight. This concludes the description of the dynamic programming algorithm.

Computation of \widehat{S}_t . Now we show how to implement the algorithm described above in the desired running time by making use of Lemma 5.7. For our discussion let us fix a node t and $Z \subseteq X_t$ of size k. While doing dynamic programming algorithm from the base nodes to the root node we always maintain the size invariant. That is, $\widehat{S}_t[Z]| \leq 2^k$.

Base node t. Trivially, in this case we have $|\widehat{S}_t[Z]| \leq 2^k$.

Introduce node t with child t'. Here, we have that $\widehat{\mathcal{S}}_t[Z] = \widehat{\mathcal{S}}_{t'}[Z \setminus \{v\}]$ and thus $|\widehat{\mathcal{S}}_t[Z]| = |\widehat{\mathcal{S}}_{t'}[Z \setminus \{v\}]| \le 2^{k-1} \le 2^k$.

Forget node t with child t'. In this case,

$$\widehat{\mathcal{S}}_{t}[Z] = \begin{cases} \left(\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_{v}[Z]\right) \cup \left\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_{t}\right\} & \text{if } v \in T \\ \left(\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_{v}[Z]\right) \cup \left\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_{t}\right\} \cup \widehat{\mathcal{S}}_{t'}[Z] & \text{if } v \notin T \end{cases} \end{cases}$$

Observe that,

$$\begin{aligned} \left|\widehat{\mathcal{S}}_{t}[Z]\right| &\leq \left|\widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] \circ \mathcal{P}_{v}[Z]\right| + \left|\left\{A \in \widehat{\mathcal{S}}_{t'}[Z \cup \{v\}] : A \in \mathcal{S}_{t}\right\}\right| + \left|\widehat{\mathcal{S}}_{t'}[Z]\right| \\ &\leq \left(\sum_{i=1}^{k} \binom{k}{i} 2^{k+1}\right) + 2^{k+1} + 2^{k} = \mathcal{O}(4^{k}). \end{aligned}$$

It can happen in this case that the size of $\widehat{\mathcal{S}}_t[Z]$ is larger than 2^k and thus we need to reduce the size of family. We apply Lemma 5.7 and obtain $\widehat{\mathcal{S}}'_t[Z]$ that maintains the correctness and size invariants. We update $\widehat{\mathcal{S}}_t[Z] = \widehat{\mathcal{S}}'_t[Z]$.

The running time to compute $\widehat{\mathcal{S}}_t$ (that is, across all subsets of X_t) is

$$\mathcal{O}\left(\sum_{i=1}^{\mathbf{tw}+1} {\mathbf{tw}+1 \choose i} 2^{i(\omega-1)} 4^i \cdot \mathbf{tw}^{\mathcal{O}(1)} n\right) = \mathcal{O}\left((1+2^{\omega+1})^{\mathbf{tw}} \cdot \mathbf{tw}^{\mathcal{O}(1)} n\right).$$

Join node t with two children t_1 and t_2 . Here we defined

$$\widehat{\mathcal{S}}_t[Z] = \widehat{\mathcal{S}}_{t_1}[Z] \circ \widehat{\mathcal{S}}_{t_2}[Z].$$

The size of $\widehat{\mathcal{S}}_t[Z]$ is $2^k \cdot 2^k = 4^k$. Now, we apply Lemma 5.7 and obtain $\widehat{\mathcal{S}}'_t[Z]$ that maintains the correctness invariant and has size at most 2^k . We put $\widehat{\mathcal{S}}_t[Z] = \widehat{\mathcal{S}}'_t[Z]$.

The running time to compute $\widehat{\mathcal{S}}_t$ is

$$\mathcal{O}\left(\sum_{i=1}^{\mathbf{tw}+1} {\mathbf{tw}+1 \choose i} 4^{i} 2^{i(\omega-1)} \cdot \mathbf{tw}^{\mathcal{O}(1)} n\right) = \mathcal{O}\left((1+2^{\omega+1})^{\mathbf{tw}} \cdot \mathbf{tw}^{\mathcal{O}(1)} n\right).$$

Thus the whole algorithm takes time $\mathcal{O}\left((1+2^{\omega+1})^{\mathbf{tw}}\cdot\mathbf{tw}^{\mathcal{O}(1)}\cdot n^2\right)$ as the number of nodes in a nice tree-decomposition is upper bounded by $\mathcal{O}(n)$. However, observe that we do not need to compute the forests and the associated weight at every step of the algorithm. The size of the forest is at most $\mathbf{tw} + 1$ and we can maintain these forests across the bags during dynamic programming in time $\mathbf{tw}^{\mathcal{O}(1)}$. This will lead to an algorithm with the claimed running time. The last remark we would like to make is that one can do better at **forget node** by forgetting a single edge at a time. However, we did not try to optimize this, as the running time to compute the family of partial solutions at **join node** is the most expensive operation. This completes the proof.

The approach of Theorem 11 can be used to obtain single-exponential algorithms parameterized by the treewidth of an input graph for several other connectivity problems such as HAMILTONIAN CYCLE, FEEDBACK VERTEX SET, and CONNECTED DOMINATED SET. For all these problems, checking whether two partial solutions can be glued together to form a global solution can be checked by testing independence in a specific graphic matroid. We believe that there exist interesting problems where this check corresponds to testing independence in a different class of linear matroids.

5.5 Path, Trees and Subgraph Isomorphism

In this section we outline algorithms for k-PATH, k-TREE and k-SUBGRAPH ISOMORPHISM using representative families. All results in this section are based on computing representative families with respect to uniform matroids.

5.5.1 *k*-Path

The problem we study in this section is as follows.

k-Path	Parameter: k
Input: An undirected n -vertex and m -edge graph G and a positive integration of G and a positive integration of G and G an	ger k .
Question: Does there exist a simple path of length k in G ?	

We start by modifying the graph slightly. We add a new vertex, say s not present in V(G), to G by making it adjacent to every vertex in V(G). Let the modified graph be called G'. It is clear that G has a path of length k if and only if G' has a path of length k + 1 starting from s. For ease of presentation we rename G' to G and the objective is to find a path of length k + 1 starting from s. Let $M = (E, \mathcal{I})$ be an uniform matroid $U_{n,k+2}$ where E = V(G) and $\mathcal{I} = \{S \subseteq V(G) \mid |S| \leq k+2\}$. In this section whenever we speak about independent sets we mean independence with respect to the uniform matroid $U_{n,k+2}$ defined above. For a given pair of vertices $s, v \in V(G)$, recall that we defined

$$\mathcal{P}_{sv}^{i} = \left\{ X \mid X \subseteq V(G), \ v, s \in X, \ |X| = i \text{ and there is a path from } s \text{ to } v \text{ of length } i \text{ in } G \text{ with all the vertices belonging to } X. \right\}$$

The problem can be reformulated to asking whether there exists $v \in V(G)$ such that \mathcal{P}_{sv}^{k+2} is non-empty. Our algorithm will check whether \mathcal{P}_{uv}^{k+2} is non-empty by computing $\widehat{\mathcal{P}}_{sv}^{k+2} \subseteq_{rep}^{0} \mathcal{P}_{sv}^{k+2}$ and checking whether $\widehat{\mathcal{P}}_{sv}^{k+2}$ is non-empty. The correctness of this algorithm is as follows. If \mathcal{P}_{sv}^{k+2} is non-empty then \mathcal{P}_{sv}^{k+2} contains some set A which does not intersect the empty set \emptyset . But then $\widehat{\mathcal{P}}_{sv}^{k+2} \subseteq_{rep}^{0} \mathcal{P}_{sv}^{k+2}$ must also contain a set which does not intersect with \emptyset , and hence $\widehat{\mathcal{P}}_{sv}^{k+2}$ must be non-empty as well. Thus, having computed the representative familes $\widehat{\mathcal{P}}_{sv}^{k+2}$ all we need to do is to check whether there is a vertex v such that $\widehat{\mathcal{P}}_{sv}^{k+2}$ is non-empty. All that remains is an algorithm that computes the representative families $\widehat{\mathcal{P}}_{sv}^{k+2} \subseteq_{rep}^{0} \mathcal{P}_{sv}^{k+2}$ for all $v \in V(G) \setminus \{s\}$. Now using Lemma 5.3 (by setting $\ell = p = k + 2$) we compute $\widehat{\mathcal{P}}_{sv}^{k+2} \subseteq_{rep}^{0} \mathcal{P}_{sv}^{k+2}$ for all

 $v \in V(G) \setminus \{s\}$ in time

$$2^{o(k)} \cdot m \log n \cdot \max_{i \in [k+2]} \left\{ \left(\frac{2(k+2)-i}{i}\right)^i \left(\frac{2(k+2)-i}{2(k+2)-2i}\right)^{2(k+2)-2i} \right\}.$$

Simple calculus shows that the running time is maximized for $i = (1 - \frac{1}{\sqrt{5}})(k+2)$, and thus the running time to compute $\widehat{\mathcal{P}}_{sv}^{k+2} \subseteq_{rep}^{0} \mathcal{P}_{sv}^{k+2}$ for all $v \in V(G) \setminus \{s\}$ together is upper bounded by $\phi^{2k+o(k)}m\log^2 n = \mathcal{O}(2.619^k m\log n)$, where where ϕ is the golden ratio $\frac{1+\sqrt{5}}{2}$. Furthermore, in the same time every set in $\hat{\mathcal{P}}_{sv}^p$ can be ordered in a way that it corresponds to an undirected path in G. A graph G has a path of length k + 1 starting from s if and only if for some $v \in V(G) \setminus \{s\}$, we have that $\widehat{\mathcal{P}}_{sv}^{k+2} \neq \emptyset$. Thus the running time of this algorithm is upper bounded by $\mathcal{O}(2.619^k m \log n)$. Let us remark that almost the same arguments show that the version of the problem on directed graphs is solvable within the same running time. However on undirected graphs we can speed up the algorithm slightly by using the following standard trick. We need the following result.

Proposition 5.3 ([7]). There exists an algorithm, that given a graph G and an integer k, in time $\mathcal{O}(k^2n)$ either finds a simple path of length $\geq k$ or computes a DFS (depth first search) tree rooted at some vertex of G of depth at most k.

We first apply Proposition 5.3 and in time $\mathcal{O}(k^2 n)$ either find a simple path of length > kin G or compute a DFS tree of G of depth at most k. In the former case we simply output the same path. In the later case since all the root to leaf paths are upper bounded by k and there are no cross edges in a DFS tree, we have that the number of edges in G is upper bounded by $\mathcal{O}(k^2n)$. Now on this G we apply the representative set based algorithm described above. This results in the following theorem.

Theorem 12. k-PATH can be solved in time $\mathcal{O}(2.619^k n \log n)$.

Our algorithm for k-PATH can be used to solve the weighted version of the problem, i.e. SHORT CHEAP TOUR. In this problem a graph G with maximum edge cost W is given, and the objective is to find a path of length at least k where the total sum of costs on the edges is minimized.

Theorem 13. SHORT CHEAP TOUR can be solved in time $\mathcal{O}(2.619^k n^{\mathcal{O}(1)} \log W)$.

k-Tree and k-Subgraph Isomorphism 5.5.2

In this section we consider the following problem.

k-Tree **Parameter:** k**Input:** An undirected *n*-vertex, *m*-edge graph G and a tree T on k vertices. **Question:** Does G contains a subgraph isomorphic to T?

We design an algorithm for k-TREE using the method of representative sets. The algorithm for k-TREE is more involved than for k-PATH. The reason to that is due to the fact that paths poses perfectly balanced separators of size one while trees not. We select a leaf r of T and root the tree at r. For vertices $x, y \in V(T)$ we say that $y \leq x$ if x lies on the path from y to r in T (if x = r we also say that $y \leq x$). For a set C of vertices in T we will say that $x \leq_C y$ if $x \leq y$ and there is no $z \in C$ such that $x \leq z$ and $z \leq y$. For a pair x, y of vertices such that $y \leq x$ in T we define

$$C^{xy} = \begin{cases} \emptyset & \text{if } xy \in E(T), \\ \text{The unique component } C \text{ of } T \setminus \{x, y\} \text{ such that } N(C) = \{x, y\} & \text{otherwise.} \end{cases}$$

We also define $T^{uv} = T[C^{uv} \cup \{u, v\}]$. We start by making a few simple observations about sets of vertices in trees.

Lemma 5.8. For any tree T, a pair $\{x, y\}$ of vertices in V(T) and integer $c \ge 1$ there exists a set W of vertices such that $\{x, y\} \subseteq W$, $|W| = \mathcal{O}(c)$ and every connected component U of $T \setminus W$ satisfies $|U| \le \frac{|V(T)|}{c}$ and $|N(U)| \le 2$.

Proof. We first find a set W_1 of size at most c such that every connected component U of $T \setminus W_1$ satisfies $|U| \leq \frac{|V(T)|}{c}$. Start with $W_1 = \emptyset$ and select a lowermost vertex $u \in V(T)$ such that the subtree rooted at u has at least $\frac{|V(T)|}{c}$ vertices. Add u to W_1 and remove the subtree rooted at u from T. The process must stop after c iterations since each iteration removes $\frac{|V(T)|}{c}$ vertices of T. Each component U of $T \setminus W_1$ satisfies $|U| \leq \frac{|V(T)|}{c}$ because (a) whenever a vertex u is added to W_1 , all components below u have size strictly less than $\frac{|V(T)|}{c}$ and (b) when the process ends the subtree rooted at r has size at most $|U| \leq \frac{|V(T)|}{c}$. Now, insert x and y into W_1 as well.

We build W from W_1 by taking the *least common ancestor closure* of W_1 ; start with $W = W_1$ and as long as there exist two vertices u and v in W such that their least common ancestor wis not in W, add w to W. Standard counting arguments on trees imply that this process will never increase the size of W by more than a factor 2, hence $|W| \leq 2|W_1| = O(c)$.

We claim that every connected component U of $T \setminus W$ satisfies $N(U) \leq 2$. Suppose not and let u be the vertex of u closest to the root. Since N(U) > 2 at least two vertices v and w in N(U) are descendants of u. Since U is connected v and w can't be descendants of each other, but then the least common ancestor of v and w is in U, contradicting the construction of W.

Observation 5.1. For any tree T, set $W \subseteq V(T)$ and component U of $T \setminus W$ such that |N(U)| = 1, U contains a leaf of T.

Proof. $T[U \cup N(U)]$ is a tree on at least two vertices and hence it has at least two leaves. At most one of these leaves is in N(U), the other one is also a leaf of T.

Lemma 5.9. Let $W \subseteq V(T)$ be a set of vertices such that for every pair of vertices in W their least common ancestor is also in W. Let X be a set containing one leaf of T from each connected component U of $T \setminus W$ such that |N(U)| = 1. Then, for every connected component U such that |N(U)| = 1 there exist $x \in W$, $y \in X$ such that $U = C^{xy} \cup \{y\}$. For every other connected component U there exist $x, y \in W$ such that $U = C^{xy}$.

Proof. It follows from the argument at the end of the proof of Lemma 5.8 that every component U of $T \setminus W$ satisfies $|N(U)| \leq 2$. If |N(U)| = 2, let $N(U) = \{x, y\}$. We have that $x \leq y$ or $y \leq x$ since least common ancestor of x and y can not be in U and would therefore be in N(U), contradicting |N(U)| = 2. Without loss of generality $y \leq x$. But then $U = C^{xy}$. If N(U) = 1, let $N(U) = \{x\}$. By Observation 5.1 U contains a leaf y of T. Then $U = C^{xy} \cup \{y\}$. \Box

Given two graphs F and H, a graph homomorphism from F to H is a map f from V(F) to V(H), that is $f: V(F) \to V(H)$, such that if $uv \in E(F)$, then $f(u)f(v) \in E(H)$. Furthermore,

when the map f is injective, f is called a subgraph isomorphism. For every $x, y \in V(T)$ such that $y \leq x$, and every u, v in V(G) we define

$$\mathcal{F}_{uv}^{xy} = \left\{ F \in \begin{pmatrix} V(G) \setminus \{u, v\} \\ |C^{xy}| \end{pmatrix} : \exists \text{ subgraph isomorphism } f \\ \text{from } T^{xy} \text{ to } G[F \cup \{u, v\}] \text{ such that } f(x) = u \text{ and } f(y) = v \right\}$$

Let us remind that for a set X and a family \mathcal{A} , we use $\mathcal{A} + X$ to denote $\{A \cup X : A \in \mathcal{A}\}$. For every $x, y \in V(T)$ such that $y \leq x$, and every u in V(G) we define

$$\mathcal{F}_{u*}^{xy} = \bigcup_{v \in V(G) \setminus \{u\}} \mathcal{F}_{uv}^{xy} + \{v\}$$
(8)

In order to solve the problem it is sufficient to select an arbitrary leaf ℓ of T and determine whether there exists a $u \in V(G)$ such that the family $\mathcal{F}_{u*}^{r\ell}$ is non-empty. We show that the collections of families $\{\mathcal{F}_{uv}^{xy}\}$ and $\{\mathcal{F}_{u*}^{xy}\}$ satisfy a recurrence relation. We will then exploit this recurrence relation to get a fast algorithm for k-TREE.

Lemma 5.10. For every $x, y \in V(T)$ such that $y \leq x$, every $\widehat{W} = W \cup \{x, y\}$ where $W \subseteq C^{xy}$, such that for every pair of vertices in \widehat{W} their least common ancestor is also in \widehat{W} , every $X \subseteq C^{xy} \setminus W$ such that X contains exactly one leaf of T in each connected component U of $T^{xy} \setminus \widehat{W}$ with |N(U)| = 1, the following recurrence holds.

$$\mathcal{F}_{uv}^{xy} = \bigcup_{\substack{g:\widehat{W} \to V(G)\\g(x) = u \land g(y) = v}} \left[\begin{pmatrix} \mathbf{n} \\ \prod_{\substack{x',y' \in \widehat{W}\\y' \preceq \widehat{W}}}^{\bullet} \mathcal{F}_{g(x')g(y')}^{x'y'} \bullet \prod_{\substack{x' \in \widehat{W}\\y' \preceq \widehat{W}}}^{\bullet} \mathcal{F}_{g(x')g(y')}^{x'y'} \end{pmatrix} + g(W) \right]$$
(9)

Here the union goes over all $O(n^{|W|})$ injective maps g from \widehat{W} to V(G) such that g(x) = u and g(y) = v, and by g(W) we mean $\{g(c) : c \in W\}$.

Proof. For the \subseteq direction of the equality consider any subgraph isomorphism f from T^{xy} to V(G) such that f(x) = u and f(y) = v. Let g be the restriction of f to W. The map f can be considered as a collection of subgraph isomorphisms with one isomorphism for each $x', y' \in \widehat{W}$ such that $y' \preceq_{\widehat{W}} x$ from $T^{x'y'}$ to G such that f(x') = g(x') and f(y') = g(y'), and one isomorphism for each $x' \in \widehat{W}, y' \in X$ such that $y' \preceq_{\widehat{W}} x$ from $T^{x'y'}$ to G such that f(x') = g(x'). Taking the union of the ranges of each of the small subgraph isomorphisms clearly give the range of f. Here we used Lemma 5.9 to argue that for every connected component U of $T^{xy} \setminus \widehat{W}$ we have that $T[U \cup N(U)]$ is in fact on the form $T^{x'y'}$ for some x', y'.

For the reverse direction take any collection of subgraph isomorphisms with one isomorphism f for each $x', y' \in \widehat{W}$ such that $y' \preceq_{\widehat{W}} x$ from $T^{x'y'}$ to G such that f(x') = g(x') and f(y') = g(y'), and one isomorphism for each $x' \in \widehat{W}, y' \in X$ such that $y' \preceq_{\widehat{W}} x$ from $T^{x'y'}$ to G such that f(x') = g(x'), such that the range of all of these subgraph isomorphisms are pairwise disjoint (except on vertices in \widehat{W}). Since all of these subgraph isomorphisms agree on the set W they can be glued together to a subgraph isomorphism from T^{xy} to G.

Our goal is to compute for every $x, y \in V(T)$ such that $y \leq x$ and $u, v \in V(G)$ a family $\hat{\mathcal{F}}_{uv}^{xy}$ such that $\hat{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \mathcal{F}_{uv}^{xy}$ and for every $x, y \in V(T)$ such that $y \leq x$ and $u \in V(G)$ a family $\hat{\mathcal{F}}_{u*}^{xy}$ such that $\hat{\mathcal{F}}_{u*}^{xy} \subseteq_{rep}^{k-|C^{xy}|-1} \mathcal{F}_{uv}^{xy}$. We will also maintain the following size invariants.

$$|\hat{\mathcal{F}}_{uv}^{xy}| \le \left(\frac{2k - |C^{xy}|}{|C^{xy}|}\right)^{|C^{xy}|} \left(\frac{2k - |C^{xy}|}{2k - 2|C^{xy}|}\right)^{k - |C^{xy}|} 2^{o(k)} \tag{10}$$

$$|\hat{\mathcal{F}}_{u*}^{xy}| \le \left(\frac{2k - |C^{xy}| - 1}{|C^{xy}| + 1}\right)^{|C^{xy}| + 1} \left(\frac{2k - |C^{xy}| - 1}{2k - 2|C^{xy}| - 2}\right)^{k - |C^{xy}| - 1} 2^{o(k)} \tag{11}$$

Let the right hand side of equation 10 be s_{xy} and the right had side of equation 11 be s_{xy}^* . We first compute such families $\hat{\mathcal{F}}_{uv}^{xy}$ for all $x, y \in V(T)$ such that $y \leq x$ and $xy \in E(T)$. Observe that in this case we have

$$\mathcal{F}_{uv}^{xy} = \begin{cases} \{\emptyset\} & \text{if } uv \in E(G), \\ \emptyset & \text{if } uv \notin E(G). \end{cases}$$

For each $x, y \in V(T)$ such that $y \leq x$ and $xy \in E(T)$ and every $u, v \in V(G)$ we set $\hat{\mathcal{F}}_{uv}^{xy} = \mathcal{F}_{uv}^{xy}$. We can now for compute $\hat{\mathcal{F}}_{u*}^{xy}$ for every $x, y \in V(T)$ such that $y \leq x$ and $xy \in E(T)$ and every $u \in V(G)$ by applying Equation 8. Clearly the computed families are within the required size bounds.

We now show how to compute a family $\hat{\mathcal{F}}_{uv}^{xy}$ of size s_{xy} for every $x, y \in V(T)$ such that $y \leq x$ and $u, v \in V(G)$ and $|C^{xy}| = t$, assuming that the families $\hat{\mathcal{F}}_{uv}^{xy}$ and $\hat{\mathcal{F}}_{u*}^{xy}$ have been computed for every $x, y \in V(T)$ such that $y \leq x$ and $u, v \in V(G)$ and $|C^{xy}| < t$. We also assume that for each family $\hat{\mathcal{F}}_{uv}^{xy}$ that has been computed, $|\hat{\mathcal{F}}_{uv}^{xy}| \leq s_{xy}$. Similarly we assume that for each family $\hat{\mathcal{F}}_{u*}^{xy}$ that has been computed, $|\hat{\mathcal{F}}_{u*}^{xy}| \leq s_{xy}$.

We fix a constant c whose value will be decided later. First apply Lemma 5.8 on T^{xy} , vertex pair $\{x, y\}$ and constant c and obtain a set \widehat{W} such that $\{x, y\} \subseteq \widehat{W}$ and every connected component U of $T \setminus \widehat{W}$ satisfies $|U| \leq \frac{|V(T)|}{c}$ and $|N(U)| \leq 2$. Select a set $X \subseteq V(T^{x,y}) \setminus \widehat{W}$ such that each connected component U of $T \setminus \widehat{W}$ with |N(U)| = 1 contains exactly one leaf which is in X. Now, set $W = \widehat{W} \setminus \{x, y\}$ and consider Equation 9 for $\widehat{\mathcal{F}}_{uv}^{xy}$ for this choice of x, y, W and X. Define

$$\tilde{\mathcal{F}}_{uv}^{xy} = \bigcup_{\substack{g:\widehat{W}\to V(G)\\g(x)=u\wedge g(y)=v}} \left[\begin{pmatrix} \mathbf{n} & \hat{\mathcal{F}}_{g(x')g(y')}^{x'y'} \bullet & \mathbf{n} \\ x',y'\in\widehat{W} & x'\in\widehat{W}, y'\in X\\ y'\preceq_{\widehat{W}}x' & y'\preceq_{\widehat{W}}x' \end{pmatrix} + g(W) \right]$$
(12)

Lemma 5.10 together with Lemmata 3.2 and 3.3 directly imply that $\tilde{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \mathcal{F}_{uv}^{xy}$. Furthermore, each family on the right hand side of Equation 12 has already been computed, since $C^{x'y'} \subset C^{xy}$ and so $|C^{x'y'}| < t$. For a fixed injective map $g: W \to V(G)$ we define

$$\tilde{\mathcal{F}}_{g}^{xy} = \begin{pmatrix} \prod_{\substack{x',y'\in\widehat{W}\\y'\leq\widehat{W}x'}}^{\bullet} \hat{\mathcal{F}}_{g(x')g(y')}^{x'y'} \bullet \prod_{\substack{x'\in\widehat{W}\\y'\leq\widehat{W}x'}}^{\bullet} \hat{\mathcal{F}}_{g(x')*}^{x'y'} \\ y'\leq\widehat{W}x' \end{pmatrix} + g(W)$$
(13)

It follows directly from the definition of $\tilde{\mathcal{F}}_{uv}^{xy}$ and $\tilde{\mathcal{F}}_{q}^{xy}$ that

$$\tilde{\mathcal{F}}_{uv}^{xy} = \bigcup_{\substack{g:\widehat{W} \to V(G) \\ g(x) = u \land g(y) = v}} \tilde{\mathcal{F}}_{g}^{xy}$$

Our goal is to compute a family $\hat{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \tilde{\mathcal{F}}_{uv}^{xy}$ such that $|\hat{\mathcal{F}}_{uv}^{xy}| \leq s_{xy}$. Lemma 3.1 then implies that $\hat{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \mathcal{F}_{uv}^{xy}$. To that end, we define the function reduce. Given a family \mathcal{F} of sets of size p, the function reduce will run the algorithm of Theorem 6 on \mathcal{F} with $x = \frac{p}{2k-p}$ and produce a family of size $\left(\frac{2k-p}{p}\right)^p \left(\frac{2k-p}{2k-2p}\right)^{k-p} 2^{o(k)}$ that k-p represents \mathcal{F} .

We will compute for each $g: \widehat{W} \to V(G)$ such that g(x) = u and g(y) = v a family $\widehat{\mathcal{F}}_{g}^{xy}$ of size at most s_{xy} such that $\widehat{\mathcal{F}}_{g}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \widetilde{\mathcal{F}}_{g}^{xy}$. We will then set

$$\hat{\mathcal{F}}_{uv}^{xy} = \operatorname{reduce} \left(\bigcup_{\substack{g: \widehat{W} \to V(G) \\ g(x) = u \land g(y) = v}} \hat{\mathcal{F}}_{g}^{xy} \right).$$
(14)

To compute $\hat{\mathcal{F}}_{g}^{xy}$, inspect Equation 13. Equation 13 shows that $\tilde{\mathcal{F}}_{g}^{xy}$ basically is a long chain of \bullet operations, specifically

$$\tilde{\mathcal{F}}_{g}^{xy} = \left(\hat{F}_{1} \bullet \hat{F}_{2} \bullet \hat{F}_{3} \dots \bullet \hat{F}_{\ell}\right) + g(W)$$
(15)

We define (and compute) $\hat{\mathcal{F}}_q^{xy}$ as follows

$$\hat{\mathcal{F}}_{g}^{xy} = \operatorname{reduce}\left(\operatorname{reduce}\left(\dots\operatorname{reduce}\left(\hat{F}_{1} \bullet \hat{F}_{2}\right) \bullet \hat{F}_{3}\right) \bullet \dots\right) \bullet \hat{F}_{\ell}\right) + g(W)$$
(16)

 $\hat{\mathcal{F}}_{g}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \tilde{\mathcal{F}}_{g}^{xy}$ and thus also $\hat{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \tilde{\mathcal{F}}_{uv}^{xy} \subseteq_{rep}^{k-|C^{xy}|} \mathcal{F}_{uv}^{xy}$ follows from Lemma 3.3 and Theorem 6. Since the last operation we do in the construction of $\hat{\mathcal{F}}_{uv}^{xy}$ is a call to reduce, $|\hat{\mathcal{F}}_{uv}^{xy}| \leq s_{xy}$ follows from Theorem 6. To conclude the computation we set

$$\tilde{\mathcal{F}}_{u*}^{xy} = \operatorname{reduce}\left(\bigcup_{v \in V(G) \setminus \{u\}} \hat{\mathcal{F}}_{uv}^{xy} + \{v\}\right)$$
(17)

Lemma 3.3 and Theorem 6 imply that $\tilde{\mathcal{F}}_{u*}^{xy} \subseteq_{rep}^{k-|C^{xy}|-1} \mathcal{F}_{u*}^{xy}$ and that $|\hat{\mathcal{F}}_{u*}^{xy}| \leq s_{xy}^*$.

The algorithm computes the families $\hat{\mathcal{F}}_{u*}^{xy}$ and $\hat{\mathcal{F}}_{uv}^{xy}$ for every $x, y \in V(T)$ such that $y \leq x$. It then selects an arbitrary leaf ℓ of T and checks whether there exists a $u \in V(G)$ such that the family $\hat{\mathcal{F}}_{u*}^{r\ell}$ is non-empty. Since $\hat{\mathcal{F}}_{u*}^{r\ell} \subseteq_{rep}^{0} \mathcal{F}_{u*}^{r\ell}$ there is a non-empty $\mathcal{F}_{u*}^{r\ell}$ if and only if there is a non empty $\hat{\mathcal{F}}_{u*}^{r\ell}$. Thus the algorithm can answer that there is a subgraph isomorphism from T to G if some $\hat{\mathcal{F}}_{u*}^{r\ell}$ is non-empty, and that no such subgraph isomorphism exists otherwise.

It remains to bound the running time of the algorithm. Up to polynomial factors, the running time of the algorithm is dominated by the computation of $\hat{\mathcal{F}}_{uv}^{xy}$. This computation consists of $n^{\mathcal{O}(|\widehat{W}|)}$ independent computations of the families $\hat{\mathcal{F}}_{g}^{xy}$. Each computation of the family $\hat{\mathcal{F}}_{g}^{xy}$ consists of at most k repeated applications of the operation

$$\hat{\mathcal{F}}^{i+1} = \mathsf{reduce}(\hat{\mathcal{F}}^i \bullet \hat{\mathcal{F}}_{i+1}).$$

Here \mathcal{F}^i is a family of sets of size p, and so $|\mathcal{F}^i| \leq \left(\frac{2k-p}{p}\right)^p \left(\frac{2k-p}{2k-2p}\right)^{k-p} 2^{o(k)} \log n$. On the other

hand $\hat{\mathcal{F}}_{i+1}$ is a family of sets of size $p' \leq \frac{k}{c}$ since we used Lemma 5.8 to construct \widehat{W} . Thus,

$$\begin{aligned} |\hat{\mathcal{F}}_{i+1}| &\leq \left(\frac{2k-p'}{p'}\right)^{p'} \left(\frac{2k-p'}{2k-2p'}\right)^{k-p'} 2^{o(k)} \\ &\leq \left(\frac{2k}{p'}\right)^{p'} \left(\frac{2k}{2k-2p'}\right)^{k-p'} 2^{o(k)} \\ &\leq \binom{k}{p'} \cdot 2^{p'} \cdot 2^{o(k)} \\ &\leq \binom{k}{k/c} \cdot 2^{k/c} \cdot 2^{o(k)} \\ &\leq 2^{(\varepsilon+1/c)k} \cdot 2^{o(k)} \end{aligned}$$

Thus $|\hat{\mathcal{F}}^i \bullet \hat{\mathcal{F}}_{i+1}| \leq \left(\frac{2k-p}{p}\right)^p \left(\frac{2k-p}{2k-2p}\right)^{k-p} 2^{(\varepsilon+1/c)k+o(k)}$. Hence, when we apply Theorem 6 with $x = \frac{p+p'}{2k-p-p'}$ to compute $\mathsf{reduce}(\hat{\mathcal{F}}^i \bullet \hat{\mathcal{F}}_{i+1})$, this takes time

$$\begin{aligned} |\hat{\mathcal{F}}^{i} \bullet \hat{\mathcal{F}}_{i+1}| \left(\frac{2k-p-p'}{2k-2p-2p'}\right)^{k-p-p'} 2^{o(k)} \log n \\ &\leq |\hat{\mathcal{F}}^{i} \bullet \hat{\mathcal{F}}_{i+1}| \left(\frac{2k-p}{2k-2p}\right)^{k-p} \left(\frac{2k-2p}{2k-2p-2p'}\right)^{k-p-p'} 2^{o(k)} \log n \\ &\leq |\hat{\mathcal{F}}^{i} \bullet \hat{\mathcal{F}}_{i+1}| \left(\frac{2k-p}{2k-2p}\right)^{k-p} \left(1+\frac{p'}{k-p-p'}\right)^{k-p-p'} 2^{o(k)} \log n \\ &\leq |\hat{\mathcal{F}}^{i} \bullet \hat{\mathcal{F}}_{i+1}| \left(\frac{2k-p}{2k-2p}\right)^{k-p} e^{p'} 2^{o(k)} \log n \\ &\leq \left(\frac{2k-p}{p}\right)^{p} \left(\frac{2k-p}{2k-2p}\right)^{2k-2p} 2^{(\varepsilon+3/c)k+o(k)} \log n \end{aligned}$$

Since there are $n^{\mathcal{O}(|\widehat{W}|)}$ (which is equal to $n^{\mathcal{O}(c)}$, where c is a constant) independent computations of the families $\hat{\mathcal{F}}_{q}^{xy}$, the total running time is upper bounded by

$$\left(\frac{2k-p}{p}\right)^p \left(\frac{2k-p}{2k-2p}\right)^{2k-2p} 2^{(\varepsilon+3/c)k+o(k)} n^{\mathcal{O}(1)}$$

The maximum value of $\left(\frac{2k-p}{p}\right)^p \left(\frac{2k-p}{2k-2p}\right)^{2k-2p}$ is when $p = (1 - \frac{1}{\sqrt{5}})k$ and the maximum value is ϕ^{2k} , where ϕ is the golden ratio $\frac{1+\sqrt{5}}{2}$. Now we can choose the value of c in such a way that $\varepsilon + 3/c$ is small enough and the above running time is bounded by $2.619^k n^{\mathcal{O}(1)}$. This yields the following theorem.

Theorem 14. k-TREE can be solved in time $2.619^k n^{\mathcal{O}(1)}$.

The algorithm for k-TREE can be generalized to k-SUBGRAPH ISOMORPHISM for the case when the pattern graph F has treewidth at most t. Towards this we need a result analogous to Lemma 5.8 for trees, which can be proved using the separation properties of graphs of treewidth at most t. This will lead to an algorithm with running time $2.619^k \cdot n^{\mathcal{O}(t)}$.

5.6 Other Applications

Marx [42] gave algorithms for several problems based on matroid optimization. The main theorem in his work is Theorem 1.1 [42] on which most applications of [42] are based. The proof of the theorem uses an algorithm to find representative sets as a black box. Applying our algorithm (Theorem 1 of this paper) instead gives an improved version of Theorem 1.1 of [42].

Proposition 5.4. Let $M = (E, \mathcal{I})$ be a linear matroid where the ground set is partitioned into blocks of size ℓ . Given a linear representation A_M of M, it can be determined in $\mathcal{O}(2^{\omega k \ell} ||A_M||^{\mathcal{O}(1)})$ randomized time whether there is an independent set that is the union of k blocks. ($||A_M||$ denotes the length of A_M in the input.)

Finally, we mention another application from [42] which we believe could be useful to obtain single exponential time parameterized and exact algorithms.

 ℓ -MATROID INTERSECTION **Parameter:** k **Input:** Let $M_1 = (E, \mathcal{I}_1), \dots, M_1 = (E, \mathcal{I}_\ell)$ be matroids on the same ground set E given by their representations $A_{M_1}, \dots, A_{M_\ell}$ over the same field \mathbb{F} and a positive integer k. **Question:** Does there exist k element set that is independent in each M_i $(X \in \mathcal{I}_1 \cap \ldots \cap \mathcal{I}_\ell)$?

Using Theorem 1.1 of [42], Marx [42] gave a randomized algorithm for ℓ -MATROID INTER-SECTION. By using Proposition 5.4 instead we get the following result.

Proposition 5.5. ℓ -MATROID INTERSECTION can be solved in $\mathcal{O}(2^{\omega k \ell} ||A_M||^{\mathcal{O}(1)})$ randomized time.

6 Conclusion and Recent Developments

In this paper, we gave an efficient algorithm for computing a representative family of a family of independent sets in a linear matroid. For the special case where the underlying matroid is uniform we developed an even faster algorithm. We also showed interesting links between representative families of matroids and the design of single-exponential parameterized and exact exponential algorithms. We believe that these connections have a potential for a wide range of applications. This works opens up an interesting avenue for further research, we list some of the natural open problems below.

- What is the best possible running time of an algorithm that computes a q-representative family of size at most $\binom{p+q}{p}$ for a p-family \mathcal{F} of independent sets of a linear matroid? Does an algorithm with linear dependence of the running time on $|\mathcal{F}|$ exist, or is it possible to prove superlinear lower bounds?
- It would be interesting to find faster algorithms even for special classes of linear matroids. Uniform matroids and graphic matroids are especially interesting in this regard.
- Finally, the only matroids we used in our algorithmic applications were graphic, uniform, and partition matroids. It would be interesting to see what kind of applications can be handled by other kinds of matroids.

The results and methods from the preliminary conference version of this paper have already been utilized to obtain several deterministic parameterized algorithms [20, 27, 28, 50, 52, 53]. The results also have been used in the context exact learning [1] and linear time constructions of some *d*-restriction problems [10]. Lokshtanov et al. [37] obtained a deterministic algorithm for computing a ℓ -truncation of a given matrix and using this obtained a deterministic version of Theorem 4 for those matroids whose representation can be found in deterministic polynomial time. Very recently Zehavi [58] has announced a further improvement for *k*-PATH algorithm. The algorithm presented in [58] runs in time $2.597^k \cdot n^{\mathcal{O}(1)}$. It has also been brought to out attention by Marek Cygan [16], in a private communication, that one can obtain single exponential time algorithms for MINIMUM EQUIVALENT GRAPH based on the methods described in [8, 17].

References

- H. ABASI, N. H. BSHOUTY, AND H. MAZZAWI, On exact learning monotone DNF from membership queries, in Algorithmic Learning Theory - 25th International Conference, ALT 2014, Bled, Slovenia, October 8-10, 2014. Proceedings, 2014, pp. 111–124. 56
- [2] N. ALON, R. YUSTER, AND U. ZWICK, *Color-coding*, J. Assoc. Comput. Mach., 42 (1995), pp. 844–856. 4, 5, 19
- [3] O. AMINI, F. V. FOMIN, AND S. SAURABH, Counting subgraphs via homomorphisms, SIAM J. Discrete Math., 26 (2012), pp. 695–717. 5
- [4] J. BANG-JENSEN AND G. GUTIN, *Digraphs*, Springer Monographs in Mathematics, Springer-Verlag London Ltd., London, second ed., 2009. Theory, algorithms and applications. 6, 39, 40
- [5] A. BJÖRKLUND, T. HUSFELDT, P. KASKI, AND M. KOIVISTO, Narrow sieves for parameterized paths and packings, CoRR, abs/1007.1161 (2010). 4, 5
- [6] A. BJÖRKLUND, T. HUSFELDT, AND S. KHANNA, Approximating longest directed paths and cycles, in Proceedings of the 31st International Colloquium, Automata, Languages and Programming (ICALP 2004), vol. 3142 of Lecture Notes in Comput. Sci., Springer, 2004, pp. 222–233. 6
- [7] H. L. BODLAENDER, On linear time minor tests with depth-first search, J. Algorithms, 14 (1993), pp. 1–23. 4, 50
- [8] H. L. BODLAENDER, M. CYGAN, S. KRATSCH, AND J. NEDERLOF, Solving weighted and counting variants of connectivity problems parameterized by treewidth deterministically in single exponential time, CoRR, abs/1211.1505 (2012). 6, 14, 57
- [9] B. BOLLOBÁS, On generalized graphs, Acta Math. Acad. Sci. Hungar, 16 (1965), pp. 447– 452. 2
- [10] N. H. BSHOUTY, Linear time constructions of some \$d\$-restriction problems, CoRR, abs/1406.2108 (2014). 57
- [11] J. BUNCH AND J. HOPCROFT, Triangular factorization and inversion by fast matrix multiplication, Mathematics of Computation, 28 (1974), pp. 231–236. 14
- [12] J. CHEN, J. KNEIS, S. LU, D. MÖLLE, S. RICHTER, P. ROSSMANITH, S.-H. SZE, AND F. ZHANG, Randomized divide-and-conquer: improved path, matching, and packing algorithms, SIAM J. Comput., 38 (2009), pp. 2526–2547. 4, 5

- [13] J. CHEN, S. LU, S.-H. SZE, AND F. ZHANG, Improved algorithms for path, matching, and packing problems, in Proceedings of the18th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA 2007), SIAM, 2007, pp. 298–307. 5
- [14] N. COHEN, F. V. FOMIN, G. GUTIN, E. J. KIM, S. SAURABH, AND A. YEO, Algorithm for finding k-vertex out-trees and its application to k-internal out-branching problem, J. Comput. System Sci., 76 (2010), pp. 650–662. 5
- [15] T. H. CORMEN, C. LEISERSON, R. RIVEST, AND C. STEIN, Introduction to Algorithms, The MIT Press, Cambridge, Mass., second ed., 2001. 6
- [16] M. CYGAN, private communication., (2013). 57
- [17] M. CYGAN, J. NEDERLOF, M. PILIPCZUK, M. PILIPCZUK, J. M. M. VAN ROOIJ, AND J. O. WOJTASZCZYK, Solving connectivity problems parameterized by treewidth in single exponential time, in Proceedings of the 52nd Annual Symposium on Foundations of Computer Science (FOCS 2011), IEEE, 2011. 6, 57
- [18] R. G. DOWNEY AND M. R. FELLOWS, Parameterized complexity, Springer-Verlag, New York, 1999. 4
- [19] J. EDMONDS, Optimum branchings, J. Res. Nat. Bur. Standards Sect. B, 71B (1967), pp. 233–240. 42
- [20] F. V. FOMIN AND P. A. GOLOVACH, Long circuits and large euler subgraphs, SIAM J. Discrete Math., 28 (2014), pp. 878–892. 56
- [21] F. V. FOMIN AND D. KRATSCH, Exact exponential algorithms, Springer, 2011. 6
- [22] F. V. FOMIN, D. LOKSHTANOV, F. PANOLAN, AND S. SAURABH, Representative sets of product families, in Algorithms - ESA 2014 - 22th Annual European Symposium, Wroclaw, Poland, September 8-10, 2014. Proceedings, vol. 8737, 2014, pp. 443–454. 4, 16
- [23] F. V. FOMIN, D. LOKSHTANOV, V. RAMAN, S. SAURABH, AND B. V. R. RAO, Faster algorithms for finding and counting subgraphs, J. Comput. System Sci., 78 (2012), pp. 698– 706. 5
- [24] F. V. FOMIN, D. LOKSHTANOV, AND S. SAURABH, Efficient computation of representative sets with applications in parameterized and exact algorithms, in Proceedings of the Twenty-Fifth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2014, Portland, Oregon, USA, January 5-7, 2014, 2014, pp. 142–151. 4, 16
- [25] P. FRANKL, An extremal problem for two families of sets, European J. Combin., 3 (1982), pp. 125–127. 2
- [26] H. N. GABOW AND S. NIE, Finding a long directed cycle, ACM Transactions on Algorithms, 4 (2008). 6
- [27] P. GOYAL, N. MISRA, AND F. PANOLAN, Faster deterministic algorithms for rdimensional matching using representative sets, in IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2013, December 12-14, 2013, Guwahati, India, vol. 24, 2013, pp. 237–248. 56

- [28] P. GOYAL, P. MISRA, F. PANOLAN, G. PHILIP, AND S. SAURABH, *Finding even subgraphs even faster*, in 35th IARCS Annual Conference on Foundation of Software Technology and Theoretical Computer Science, FSTTCS 2015, December 16-18, 2015, Bangalore, India, 2015, pp. 434–447. 56
- [29] H. T. HSU, An algorithm for finding a minimal equivalent graph of a digraph, J. Assoc. Comput. Mach., 22 (1975), pp. 11–16. 6
- [30] R. IMPAGLIAZZO, R. PATURI, AND F. ZANE, Which problems have strongly exponential complexity, Journal of Computer and System Sciences, 63 (2001), pp. 512–530. 6
- [31] S. JUKNA, Extremal combinatorics, Springer Verlag Berlin Heidelberg, 2011. 3
- [32] T. KLOKS, Treewidth, Computations and Approximations, vol. 842 of Lecture Notes in Computer Science, Springer, 1994. 44
- [33] J. KNEIS, D. MÖLLE, S. RICHTER, AND P. ROSSMANITH, *Divide-and-color*, in Proceedings of the 34th International Workshop Graph-Theoretic Concepts in Computer Science (WG 2008), vol. 4271 of Lecture Notes in Computer Science, Springer, 2008, pp. 58–67. 4
- [34] I. KOUTIS, Faster algebraic algorithms for path and packing problems, in Proceedings of the 35th International Colloquium on Automata, Languages and Programming (ICALP 2008), vol. 5125 of Lecture Notes in Computer Science, 2008, pp. 575–586. 4
- [35] I. KOUTIS AND R. WILLIAMS, Limits and applications of group algebras for parameterized problems, in Proceedings of the 36th International Colloquium on Automata, Languages and Programming (ICALP 2009), vol. 5555 of Lecture Notes in Computer Sci., Springer, 2009, pp. 653–664. 5
- [36] S. KRATSCH AND M. WAHLSTRÖM, Representative sets and irrelevant vertices: New tools for kernelization, in Proceedings of the 53rd Annual Symposium on Foundations of Computer Science (FOCS 2012), IEEE, 2012, pp. 450–459. 3
- [37] D. LOKSHTANOV, P. MISRA, F. PANOLAN, AND S. SAURABH, Deterministic truncation of linear matroids, in Automata, Languages, and Programming - 42nd International Colloquium, ICALP 2015, Kyoto, Japan, July 6-10, 2015, Proceedings, Part I, 2015, pp. 922–934. 57
- [38] L. LOVÁSZ, Flats in matroids and geometric graphs., in In Combinatorial surveys (Proc. Sixth British Combinatorial Conf., Royal Holloway Coll., Egham), Academic Press, London, 1977, pp. 45–86. 2, 3, 11
- [39] S. MARTELLO, An algorithm for finding a minimal equivalent graph of a strongly connected digraph, Computing, 21 (1978/79), pp. 183–194. 6
- [40] S. MARTELLO AND P. TOTH, Finding a minimum equivalent graph of a digraph, Networks, 12 (1982), pp. 89–100. 6
- [41] D. MARX, Parameterized coloring problems on chordal graphs, Theor. Comput. Sci., 351 (2006), pp. 407–424. 3
- [42] —, A parameterized view on matroid optimization problems, Theor. Comput. Sci., 410 (2009), pp. 4471–4479. 2, 3, 8, 9, 10, 12, 56

- [43] M. MITZENMACHER AND E. UPFAL, Probability and computing: Randomized algorithms and probabilistic analysis, Cambridge University Press, 2005. 18
- [44] B. MONIEN, How to find long paths efficiently, in Analysis and design of algorithms for combinatorial problems (Udine, 1982), vol. 109 of North-Holland Math. Stud., North-Holland, Amsterdam, 1985, pp. 239–254. 2, 3, 4
- [45] D. M. MOYLES AND G. L. THOMPSON, An algorithm for finding a minimum equivalent graph of a digraph, J. ACM, 16 (1969), pp. 455–460. 6, 39
- [46] K. MUROTA, Matrices and matroids for systems analysis, vol. 20, Springer, 2000. 12
- [47] M. NAOR, L. J. SCHULMAN, AND A. SRINIVASAN, Splitters and near-optimal derandomization, in Proceedings of the 36th Annual Symposium on Foundations of Computer Science (FOCS 1995), IEEE, 1995, pp. 182–191. 3, 15
- [48] J. G. OXLEY, Matroid theory, vol. 3, Oxford University Press, 2006. 8, 10
- [49] C. H. PAPADIMITRIOU AND M. YANNAKAKIS, On limited nondeterminism and the complexity of the V-C dimension, J. Comput. Syst. Sci., 53 (1996), pp. 161–170. 4
- [50] R. Y. PINTER, H. SHACHNAI, AND M. ZEHAVI, Deterministic parameterized algorithms for the graph motif problem, in Mathematical Foundations of Computer Science 2014 - 39th International Symposium, MFCS 2014, Budapest, Hungary, August 25-29, 2014. Proceedings, Part II, vol. 8635, 2014, pp. 589–600. 56
- [51] J. PLEHN AND B. VOIGT, Finding minimally weighted subgraphs, in Proceedings of the 16th Workshop on Graph-Theoretic Concepts in Computer Science (WG 1991), vol. 484 of Lecture Notes in Comput. Sci., Springer, 1991, pp. 18–29. 4
- [52] H. SHACHNAI AND M. ZEHAVI, Parameterized algorithms for graph partitioning problems, in Graph-Theoretic Concepts in Computer Science - 40th International Workshop, WG 2014, Nouan-le-Fuzelier, France, June 25-27, 2014. Revised Selected Papers, vol. 8747, 2014, pp. 384–395. 56
- [53] —, Representative families: A unified tradeoff-based approach, in Algorithms ESA 2014
 22th Annual European Symposium, Wroclaw, Poland, September 8-10, 2014. Proceedings, vol. 8737, 2014, pp. 786–797. 4, 56
- [54] Z. TUZA, Applications of the set-pair method in extremal hypergraph theory, in Extremal problems for finite sets (Visegrád, 1991), vol. 3 of Bolyai Soc. Math. Stud., János Bolyai Math. Soc., Budapest, 1994, pp. 479–514. 3
- [55] —, Applications of the set-pair method in extremal problems. II, in Combinatorics, Paul Erdős is eighty, Vol. 2 (Keszthely, 1993), vol. 2 of Bolyai Soc. Math. Stud., János Bolyai Math. Soc., Budapest, 1996, pp. 459–490. 3
- [56] R. WILLIAMS, Finding paths of length k in $O^*(2^k)$ time, Inf. Process. Lett., 109 (2009), pp. 315–318. 4, 5
- [57] V. V. WILLIAMS, Multiplying matrices faster than Coppersmith-Winograd, in Proceedings of the 44th Symposium on Theory of Computing Conference (STOC 2012), ACM, 2012, pp. 887–898. 8

[58] M. ZEHAVI, Mixing color coding-related techniques, in Algorithms - ESA 2015 - 23rd Annual European Symposium, Patras, Greece, September 14-16, 2015, Proceedings, 2015, pp. 1037–1049. 57