

## Enabledness-based Testing of Object Protocols

Javier Godoy<sup>1,2</sup>, Juan Pablo Galeotti<sup>2</sup>, Diego Garbervetsky<sup>2</sup>, and  
Sebastián Uchitel<sup>2,3</sup>

<sup>1</sup> Universidad Nacional de General Sarmiento

<sup>2</sup> Departamento de Computación, FCEyN-UBA. ICC/CONICET

<sup>3</sup> Department of Computing, Imperial College London

**Abstract.** A significant proportion of classes in modern software introduce or use object protocols, prescriptions on the temporal orderings of method calls on objects. This paper studies search-based test generation techniques that aim to exploit a particular abstraction of object protocols (enabledness preserving abstractions, EPAs) to find failures. We define coverage criteria over an extension of EPAs that includes abnormal method termination and define a search-based test case generation technique aimed at achieving high coverage. Results suggest that the proposed case generation technique with a fitness function that aims at combined structural and extended EPA coverage can provide better failure-detection capabilities not only for protocol failures but also for general failures when compared to random testing and search-based test generation for standard structural coverage.

This article was published in ACM Transactions on Software Engineering and Methodology, Volume 30. Issue 2: <https://doi.org/10.1145/3415153>.

**Keywords:** Automatic Test Generation, Enabledness-Preserving Abstractions, Genetic Algorithms.